Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 322698

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image:

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

This unit is Made In USA - Manufactured in Texas

MPD-CS2-309.60AF-YT0-Z-1.E28-2.L22-4.N10-M1 Portable Spider Box
Line-In: 560B9W IEC Pin & Sleeve Inlet [120/208V]
Line-Out: 560R9W IEC Pin & Sleeve Receptacle [120/208V]
Primary Voltage: 208Y/120V AC Wye
Primary Phase: 3-Phase (3PH)
Primary Frequency: 60 Hz (60-cycles)
Primary Panel: 208Y/120V 3PH 60A MLO Yellow Spider Box N3R
Primary Breaker(s): (2) 30A 2P MCB [250V]; (4) 20A 1P MCB [125V]
Primary Outlet(s): (2) L14-30R NEMA Twist-Lock Receptacles [125/250V]; (4) 5-20R NEMA Duplex-GFCI [125V]
Primary Protection: MCB Circuit Breakers; Weatherproof Covers; GFCI's
Housing Material: Steel
Form Factor: Yellow Powder Coated Spider Box w/ Legs
Mounting: Portable/Base Stand
Dimensions: -
Weight: -

Ratings/Approvals
Max Primary OCP: 60A @ 208V
Max Secondary Output: N/A
NRTL Certified to UL 1640
NEMA 3R Weatherproof
Overload Protection
Short Circuit Protection

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

This unit is Made In USA - Manufactured in Texas

The MPD-CS2-309.60AF-YT0-Z-1.E28-2.L22-4.N10-M1 from Larson Electronics is a

Portable Spider Box for indoor, outdoor, and rugged applications. This unit allows operators to use three-phase 208Y/120V AC Wye power via a 60-amp 560B9W pin and sleeve male inlet. The device is equipped with six output receptacles for equipment. For robust protection, the safety yellow spider box is NEMA 3R rated and protected by impact/flame resistant weatherproof covers.

Operation:

• Primary Voltage: 208Y/120V AC Wye 3PH

• Primary Panel: 208Y/120V 3PH 60A MLO Yellow Spider Box N3R

• Primary Breaker(s): (2) 30A 2P MCB [250V]; (4) 20A 1P MCB [125V]

• Primary Outlet(s): (2) L14-30R NEMA Twist-Lock Receptacles [125/250V]; (4) 5-20R NEMA Duplex-GFCI [125V]

• Transformer: N/A

• Secondary Voltage: N/A

• Secondary Panel: N/A

• Secondary Breaker(s): N/A

• Secondary Outlet(s): N/A

*See specification table at the top of the page for more information about the power distribution system.

This portable spider box has a 60-amp 560B9W IEC 60309 208Y/120V pin and sleeve male inlet for bringing three-phase 208/120V AC Wye power into the unit as well as a 60-amp 560R9W IEC 60309 208Y/120V feed-thru female receptacle. Operators may access two 30-amp 2-pole 250V miniature circuit breakers protecting two 30-amp NEMA L14-30R twist lock outlets and four 20-amp 1-pole 125V miniature circuit breakers protecting four 20-amp NEMA 5-20R GFCI duplex outlets on the system. The receptacles are protected by weatherproof covers.

The MPD-CS2-309.60AF-YT0-Z-1.E28-2.L22-4.N10-M1 spider box features short circuit, overload, open neutral, and reverse phasing protection. Should circuit overload occur, the unit will automatically shut down to protect the spider box from damage.

The housing on the MPD-CS2-309.60AF-YT0-Z-1.E28-2.L22-4.N10-M1 is constructed of steel with a NEMA 3R enclosure rating. This safety yellow device is approved for wet locations and features heavy-duty impact/flame resistant weatherproof covers. Two angled black legs at the base of the unit and low center of gravity ensures this spider box does not tip over in the field.

Certification: All units are built in accordance to NFPA 70 (National Electric Code). All equipment is NEMA 3R rated for indoor and outdoor use and provide a degree of protection against dirt, water, and ice. NEMA 4 and NEMA 4x equipment can be equipped upon request.

Applications: Indoor or outdoor applications including but not limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits, and shipyard operations. These units are popularly used in applications where external power sources are often necessary. We also offer class rated transformers for use within explosion proof and hazardous location environments.

Larson Electronics is a manufacturer and we can build portable power distribution systems to your specifications. Although we carry several models of portable power distribution systems in stock, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664




Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 322698

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **ANSI Certificate 1**(https://www.larsonelectronics.com//images/product/ANSICert1/322698.PDF)
- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(https://www.larsonelectronics.com//images/product/CECCert/322698.PDF)
- **Catalog Page - Product Series**(https://www.larsonelectronics.com//images/product/CatalogPage/322698.PDF)
- **CE Certificate**(https://www.larsonelectronics.com//images/product/CECert/322698.PDF)
- **Certificate 1, Misc**(https://www.larsonelectronics.com//images/product/Cert1/322698.PDF)
- **Certificate 5, Misc**(https://www.larsonelectronics.com//images/product/Cert5/322698.PDF)
- **MSDS (Material Safety Data Sheet**(https://www.larsonelectronics.com//images/product/Msds/322698.PDF)
- **RoHS Certificate (Restriction of Hazardous Substances)**(https://www.larsonelectronics.com//images/product/RoHSCert/322698.PDF)
- **Single Line Diagram (One-Line Diagram)**(https://www.larsonelectronics.com//images/product/Oneline/322698.PDF)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(https://www.larsonelectronics.com//images/product/NECCert/322698.PDF)
- **Wiring Diagram**(https://www.larsonelectronics.com//images/product/WiringDiagram/322698.PDF)
- **HigResPic1**(https://www.larsonelectronics.com//images/product/HigResPic1/322698.JPG)
- **HigResPic2**(https://www.larsonelectronics.com//images/product/HigResPic2/322698.JPG)
- **HigResPic3**(https://www.larsonelectronics.com//images/product/HigResPic3/322698.JPG)
- **HigResPic4**(https://www.larsonelectronics.com//images/product/HigResPic4/322698.JPG)
- **HigResPic5**(https://www.larsonelectronics.com//images/product/HigResPic5/322698.JPG)
- **HigResPic6**(https://www.larsonelectronics.com//images/product/HigResPic6/322698.JPG)
- **HigResPic7**(https://www.larsonelectronics.com//images/product/HigResPic7/322698.JPG)
- **HigResPic8**(https://www.larsonelectronics.com//images/product/HigResPic8/322698.JPG)
- **HigResPic9**(https://www.larsonelectronics.com//images/product/HigResPic9/322698.JPG)
- **Video1**(https://www.youtube.com/watch?v=iEU4ZBzsfpg)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)