

MT-PRC-XX-SP9538

Paper Resin Core Bushing For Transformers - 3000A, 27.5KV Class

Product ID: 324128

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MT-PRC-XX-SP9538

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PRC-XX-SP9538 Paper Resin Capacitor Core Bushing Connector

Unit Type: Paper Resin Capacitor Core Bushing Connector, Condenser Bushing

Voltage Class: 27.5 kV

BIL and Full Wave Crest: 200 kV

Current Rating: 3000A

Minimum Creepage: -

Minimum Strike: -

Bottom Terminal Type: Hole

Color: Grey

Immersion Type - Above Flange: Air

Immersion Type - Below Flange: Oil

Material - Flange: Aluminum

Material - Insulation: Porcelain

Mounting Position: -

Number of Flange Mounting Holes: -

Number of Sheds: -

Test Tap: -

Top Terminal Plating: -

Top Terminal Type: -

Ratings:

IEEE Standards

Features:

High seismic

Oil-impregnated paper wound core with external

Above Flange Length: -
Below Flange Length: -
Diameter - Above Flange, Maximum: -
Diameter - Below Flange, Maximum D 1": -
Diameter - Below Flange Maximum P: -
Diameter - Conductor Outside: -
Diameter - Live Part Top: -
Diameter - Top Terminal Outside: -
Dimensions: 60.38 in x 10.75 in x 60.38 in
Effective Length - Top Terminal: -
Flange Mounting Hole Bolt Circle: -
Flange Mounting Hole Diameter: -
Flange Outside Diameter: -
Height: 60.38 inches
Length: 60.38 inches
Length - Drawlead Above Flange: -
Length - Ground Shield: -
Length - Live Part Top: -
Length - Minimum Oil Immersion Level: 21.00 inches
Sealing Surface Outside Diameter: -
Stud Inside Diameter: -
Thickness - Flange Plate: -
Thread Size - Drawlead Connector: -
Weight: 130 lbs
Width: 10.75 inches

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The MT-PRC-XX-SP9538 Transformer-Circuit Breaker Bushing, Paper-Resin-Capacitor Type, Rated for 27.5kV-3000A per IEEE C57.19.01, Draw-Lead/Bottom Connected for Air-to-Oil Applications, 21.00" Min. Oil Immersion Level.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

Bushing Features: This MT-PRC-XX-SP9538 features resin-impregnated paper wound core with external porcelain insulator, High creep upper porcelain, High seismic rating.

Bushing Applications: Transformer-Oil Circuit Breaker

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.



Frequently Asked Questions (FAQ)

There are no Faqs



Export Control Classification Number (ECCN): EAR99



Links (Click on the below items to view):

- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/324128.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)