Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-CW15-CLP6.400AB-DE400YT.J-VZ-10.V05-10.N10-M1

400 kVA Portable Power Distribution, 480V to 208Y/120 x 415Y/240V 3PH, Camlock Input, (10) ADR1044 (10) 5-20R GFCI Duplex Outlets, NEMA 3R

Product ID: 324967

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-CW15-CLP6.400AB-DE400YT.J-VZ-10.V05-10.N10-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-CW15-CLP6.400AB-DE400YT.J-VZ-10.V05-10.N10-M1 Temporary Power Distribution System

Line In: N/A
Line-in Cord Cap: (1 Set) 400A Single-pole 16-Ser. Male Camlock Receptacles [Green, Brown, Orange, Yellow] [600V] w/ Flip Covers
Primary Voltage (V): 480V AC Delta
Primary Phase (PH): 3-Phase (3PH)
Primary Frequency (HZ): 60 Hz (60-cycles)
Primary Panel: N/A
Primary Breaker(s): (1) 400A 3P MCCB [600V]
Primary Outlet(s): N/A
Primary Protection: MCCB Circuit Breaker; Flip Covers

Transformer Specifications:

Capacity: 400 KVA
Frequency: 60 Hz
Primary Voltage: 480V AC Delta
Secondary Voltage: 208Y/120 x 415Y/240V AC, Dual rated
FCAN (Above) Taps: 2
FCAN (Below) Taps: 4

Ratings

Max Primary OCP: 400A @ 600V
Max Secondary Output: 1110.3A @ 208V
NEMA 3R Indoor or Outdoor Use
Made in the USA
NRTL Certified to UL 1640
NRTL Certified to CSA C22.2 No. 14

Powder Coat Finish Standards:

Complies with ASTM D-523
Complies with ASTM D-3359
Complies with ASTM D-2794
Complies with ASTM D-522
Complies with ASTM D-3363

Tap %: 2.5
Impedance: 4.0%
Winding Material: Copper
Insulation: 220°C
Temperature Rise: 150°C
K-Factor Rating: K-13
Electrostatic Shield: Included
Core Material: Grain Oriented Silicon Steel

Secondary Panel: 208Y/120 x 415Y/240V 3PH 1110.3A MLO N3R
Secondary Breaker(s): (10) 100A 3P MCCB [250V]; (10) 20A 1P MCB [125V]
Secondary Outlet(s): (10) ADR1044 UL 1682/1686 Pin-Sleeve [208Y/120V]; (10) 5-20R NEMA GFCI DPLX [125V]
Secondary Protection: MCCB Circuit Breakers; MCB Circuit Breakers; GFCI's
Form Factor: Blue Powder Coated Steel Open Cube w/ Casters
Doors: (2)
Frame Material: Steel
Frame Finish: High-Strength TGIC Polyester Powder Coated Blue
Cart Handle Orientation: Horizontal
Lifting Eyelet: (4) Top Located
Skid Pockets: (2) Bottom Located
Casters: (4) Locking Casters
Dimensions: (*Please note that dimensions are approximate and subject to change*) 58"-L x 48"-W x 62"-H
Weight: (*Please note that weight is approximate and subject to change*) 3150 lb
Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements
Contact us for special requirements
Intl: 1-214-616-6180
Toll Free: 1-800-369-6671
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in Texas

The MPD-CW15-CLP6.400AB-DE400YT.J-VZ-10.V05-10.N10-M1 from Larson Electronics is a Power Distribution Substation that converts three-phase 480V AC Delta electrical current to three-phase 208Y/120 x 415Y/240V AC Wye. This fully enclosed power distribution unit provides operators the ability to safely tap into and distribute 600V AC Delta power from a variety of sources including generators and direct grid power.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

The MPD-CW15-CLP6.400AB-DE400YT.J-VZ-10.V05-10.N10-M1 temporary power distribution system gives operators the ability to power their 208Y/120 or 415Y/240V AC equipment from a single system.

Operation:

• Primary Voltage: 480V AC Delta 3PH

• Primary Panel: N/A

• Primary Breaker(s): (1) 400A 3P MCCB [600V]

• Primary Outlet(s): N/A

• Transformer: 400KVA 480V - 208Y/120 x 415Y/240V 3PH N3R

• Secondary Voltage: 208Y/120 x 415Y/240V AC Wye 3PH

• Secondary Panel: 208Y/120 x 415Y/240V 3PH 1110.3A MLO N3R

• Secondary Breaker(s): (10) 100A 3P MCCB [250V]; (10) 20A 1P MCB [125V]

• Secondary Outlet(s): (10) ADR1044 UL 1682/1686 Pin-Sleeve [208Y/120V]; (10) 5-20R NEMA GFCI DPLX [125V]

*See specification table at the top of the page for more information about the power distribution system.

Protective Construction: Unlike many portable power distribution boxes made of plastic and utilizing thin gauge, low grade metals in their construction, this unit is designed for serious use and is ruggedly constructed to withstand demanding conditions and heavy duty industrial applications. The transformer and load assembly is mounted on a 3/16" thick carbon steel mounting platform and the load center/distribution assembly is mounted to the standard cube carbon steel tubing frame, resulting in an extremely stable, durable and well protected power distribution platform. This model is equipped with forklift skid pockets, locking casters, and a top located lifting eyelet which allows easy lifting with cable or chain hooks. This can be replaced for an additional cost with stainless steel, hot dip galvanized steel, or aluminum depending on the customer's needs. Larger units are available upon request, and can be equipped with skids or trailer mounted.

The transformer and load center/distribution assembly is mounted to a standard steel cube style frame resulting in an extremely stable, durable, and mobile power distribution platform. This temporary power distribution solution can be modified to meet the needs of job-site receptacle requirements. Larger units are available upon request and can be equipped with skids or trailer mounted.

Certification: All units are built in accordance to NFPA 70 (National Electric Code) and NRTL certified to UL 1640. The primary and secondary panels are NEMA 4X rated for indoor and outdoor use and provide a degree of protection against dirt, water, ice, and corrosion. NEMA 3R and NEMA 4 equipment can be equipped upon request.

Grounding: Transformer is grounded to the frame and we provide a grounding lug on the frame for the earth ground.
~Please check all motor loads for dual rated motors that will work 208 or 240.~

Applications: This power distribution system is ideal for indoor or outdoor use and applications including but not limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits, and shipyard operations. These power distribution systems are popularly used in applications where external power sources are often necessary. We also offer class rated transformers for use within explosion proof and hazardous location environments.

Custom Built Systems Available: Larson Electronics is a manufacturer and we can build portable power distribution systems to your specifications. Although we carry several models of portable power distribution systems in stock, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CW15-CLP6.400AB-DE400YT.J-VZ-10.V05-10.N10-M1



Image: MPD-CW15-CLP6.400AB-DE400YT.J-VZ-10.V05-10.N10-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CW15-CLP6.400AB-DE400YT.J-VZ-10.V05-10.N10-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CW15-CLP6.400AB-DE400YT.J-VZ-10.V05-10.N10-M1

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/324967.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/324967.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/324967.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/324967.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/324967.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/324967.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/324967.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/324967.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)