Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

HLP-EX-20A-3P4W-208V.3P

Hazardous Location Pin and Sleeve Plug - 3 Pole 4 Wire - 30 Amp - ATEX Rated - 3P4W 208V

Product ID: 325234

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).

Image: HLP-EX-20A-3P4W-208V.3P

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HLP-EX-20A-3P4W-208V.3P Explosion Proof Plug

Amp Rating: 20
Dimensions: 8.3"H x 3.9"W
Configuration: 3-Pole 4-Wire
Cord O.D.: 0.6" to 1.1"
Compatibility: HLO-EX-20A-3P4W-208V.3P
Terminal Capacity: 1 Wire, 14 to 8 AWG
Voltage: 208V AC @ 50/60 Hz

Certifications - Compliance

Class I, Division 2, Groups A, B, C, D
Class I, Zone 1 & 2, Groups IIC, IIB, IIA
Class II, Div 1 & 2, Groups E, F, G
Class III
NEMA 3, 4, 4X
IP66 Waterproof
ATEX Rated
IECEx Zones 1, 2, 21 & 22

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The Larson Electronics HLP-EX-20A-3P4W-208V.3P Hazardous Location Pin and Sleeve Plug is a ATEX rated cord cap approved for use in hazardous environments where flammable or explosion gases, vapors, or dusts stand the potential to exist and where flammable dusts, fibers, or flyings exist. This 3-pole, 4-wire plug is designed to provide

a secure connection for electrical equipment within the hazardous location.

This hazardous location 3-pole 4-wire pin and sleeve plug is compatible with our HLO-EX-20A-3P4W-208V.3P hazardous location power receptacles. This plug is rated for 20 amps and is suitable for II 2 G, Ex de IIC T6 and II 2D Ex tD A21 IP 66 T80°C. With NEMA Type 3, 4, 4x and IP66 ratings, this plug is suitable for outdoor, marine and wet location. This hazardous location plug features polyamide construction, a 20 amp current rating, and is operates on 208V AC. This plug is coded blue to indicate its voltage rating and ground pin position of 7. The color coding of these units makes it impossible to connect different voltages and current ratings, to ensure safe power connection.

Suggested Applications: Chemical and pharmaceutical manufacturing, petrochemical operations, offshore applications, coal mining and other refinery or industrial operations.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/325234.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)