Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R

3 kVA Prewired Distribution Transformer - 120V Primary - 230V Secondary - NEMA 3R - 1PH/Fully Potted - (2) 6' Cords w/ Cord Caps

Product ID: 325642

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R Fully Potted Distribution Transformer

Transformer Type: Prewired Fully Potted Transformer
Phase: Single Phase
Frequency: 60 Hz
kVA: 3
Primary Voltage: 120 V
Taps: -
Secondary Voltage: 230 V
Winding Material: Aluminum
Insulation: 180°C
Temperature Rise: 125°C
Impedance (Std): 1% - 5%
Seismic: Yes
Sound Level: Meets NEMA ST-20 Standards
Primary Wiring: 6' 12/3 SOOW Cord w/ 20A NEMA 250V 6-20P
Secondary Wiring: 6' 12/3 SOOW Cord w/ 15A NEMA 250V L6-15R
Enclosure Material: NEMA Type 3R - Encapsulated
Finish: ANSI 61 Grey, UL50 Finish
Dimensions: 14.38"H x 10.31"W x 7.13"D
Weight: 75 lb

Ratings

Listed for United States and Canada
ANN Cooling
IP24 Rated
Distribution Transformer
Fully Potted

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664

Mounting: Wall Mount

E-mail: sales@larsonelectronics.com

The MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R 120 V 1 Phase Energy Efficient Prewired Fully Potted Distribution Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 3 kVA, the MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R fully potted distribution transformer is a single phase unit with a primary voltage of 120 V. It also provides a secondary voltage of 230 V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be wall mounted. The unit also features 220°C insulation with a 150°C temperature rise and is rated IP24.

Wiring: The primary side is equipped with a 6' 12/3 SOOW cord with a 20-amp 250V NEMA 6-20P male straight blade plug. The secondary side has a 6' 12/3 SOOW cord with a 15-amp 250V NEMA L6-15R twist-lock female receptacle.

Benefits: The MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R distribution transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This distribution transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated mounting brackets make installation fast and easy and the offset outward facing installation holes allow for easy power tool access.

Safety: The MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R is a distribution transformer which means that it provides operators with an increased level of protection against electric shock. A distribution transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664




Image: MPD-MT-ISX-FP-1P-120V-3KVA-230V-N3R-2X6FT-620P-L615R

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/325642.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/325642.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/325642.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/325642.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/325642.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/325642.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/325642.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)