Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1

Industrial Weatherproof Control Station with a Fiberglass Enclosure Isolator Switch - Fused - Three Pole - 63A - 415V Rated - (1) Open Auxiliary Contact

Product ID: 326267

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1 Weatherproof Fused Disconnect / Isolator Switch

Unit Type: Weatherproof Fused Disconnect/Isolator Switch
Dimensions: -
Weight: -
Rated Voltage: Max to 400 V
Rated Current: Max to 63 Amps
Utilization Category: AC-23, AC-3
Rated Insulation Voltage (Ui): 800 V
Rated Withstand Impulse Voltage (Uimp): 6 kV
Rated Short-Time Withstand Current (Icw): 10 kA
Rated Short-Time Marking Capacity (Icm): 17 kA
Fuse Type: BS 3036:1958
Short-Circuit Protection of Fuse: 500 V / 63 A
Protection Characteristic of Fuse: gG(Conformity to IEC/EN60269-1)
Ambient Temperature: -55°C to + 55°C
Selector Switch: (1) 3-Pole, 2-Position Selector Switch Labeled "ON", "OFF"
Selector Switch Safety: Lockout/Tag Out Lock
Auxiliary Contact: (1) Normally Open
Terminals: (1) 35 mm Terminal w/ Internal Wiring

Ratings/Details:

IP66
GRP Construction
WF2 Corrosion-Proof Mark

Special Orders - Special Requirements

Materials: Glass Fiber Reinforced Polyester (GRP) - Black
Cable Entry: (2) Cable Entries - Each w/ M50 Plastic Cable Glands
Mount: Surface
Cable Diameter: Can Accomodate 0.86" to 1.38" (22-35 mm) Cable

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1 from Larson Electronics is a Weatherproof Fused Disconnect / Isolator Switch that is rated for 415 V, 50 Hz and is also rated IP66 for use in areas where exposure to dust or powerful water jets is possible. This weatherproof fused disconnect/isolator switch prevents all ingress of dust and immune to water sprayed from powerful jets. The IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1 features a two position selector switch and one normally open auxillary contact. The IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1 is constructed from glass fiber reinforced polyester (GRP) and is black in color.

The IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1 is a durable weatherproof fused disconnect/isolator switch designed for areas that encounter dusty or wet conditions. Featuring an voltage rating of 415 V, 50 Hz, this unit features one normally open auxillary contact in addition to the two-position selector switch. This isolator switch is equipped with two M50 moulded plastic cable glands with a diameter of 22-35 mm.

The two position selector switch on the IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1 is labeled "ON" and "OFF". The switch is key lockable for lock out or tag out.

Voltage: The IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1 has a voltage rating of 415 V, 50 Hz.

Wiring/Mounting: The IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1 features two cable entries. Each entry is equipped with a M40 plastic cable gland and can accommodate cables with a diameter of between 0.86" to 1.38" (22-35 mm). The IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1 has one 35 mm terminal with internal wiring on the inside.

Materials: The IND-WPCS-FG-FDS-415V-3P-63A-AUX.1-R1 is built from glass fiber reinforced polyester (GRP) and is black in color.

Applications: Situations requiring a weatherproof fused disconnect/isolator switch.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/326267.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)