Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-CD1-862.40AB-SN7.5SW-GZ-1.N07-2.N03-1.R8-M1

7.5 KVA Medical Grade Portable Power Distro Cart, 250V 1PH - 120V 1PH, (1) 5-20R Hospital Grade Simplex (2) 5-15R Hospital Grade Simplex (3) 5-15R NEMA Simplex Outlets, 10' 6/3 Type W Cord w/ HBL25615 Mobile X-ray Male Plug, NEMA 3R

Product ID: 326357

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-CD1-862.40AB-SN7.5SW-GZ-1.N07-2.N03-1.R8-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-CD1-862.40AB-SN7.5SW-GZ-1.N07-2.N03-1.R8-M1 - Medical Grade Temporary Power Distribution System

Line-in Cord: 10' #6/3 AWG Type W Cord [600V]
Line-in Cord Cap: HBL25615 Mobile X-ray Male Plug [250V]
Primary Voltage (V): 250V AC
Primary Phase (PH): 1-Phase (1PH)
Primary Frequency (HZ): 60 Hz (60-cycles)
Primary Panel: 250V 1PH 40A MCCB N4R Stainless Steel Panel
Primary Breaker(s): N/A
Primary Outlet(s): N/A
Primary Protection: MCCB Circuit Breaker
Transformer (KVA): 7.5KVA 250V to 120V 1PH N3R
Secondary Voltage (V): 120V AC
Secondary Phase (PH): 1-Phase (1PH)
Secondary Frequency (HZ): 60 Hz (60-cycles)
Secondary Panel: 120V 1PH 62.5A MLO N4X Stainless Steel Panel
Secondary Breaker(s): (1) 20A 1P MCB [125V]; (3) 15A 1P MCB [125V]
Secondary Outlet(s): (1) 5-20R Hospital Grade Simplex Receptacle [125V]; (2) 5-15R Hospital Grade Simplex Receptacle [125V]; (3) 5-15R NEMA Simple Receptacle [125V]
Secondary Protection: MCB Circuit Breakers

Ratings

Max Primary OCP: 40A @ 250V
Max Secondary Output: 62.5A @ 120V
NEMA 3R Indoor or Outdoor Use
NEMA 3R In-Use Weather Shield
Made in the USA
NRTL Certified to UL 1640
NRTL Certified to CSA C22.2 No. 14

Powder Coat Finish Standards:

Complies with ASTM D-523
Complies with ASTM D-3359
Complies with ASTM D-522
Complies with ASTM D-3363
Complies with ASTM D-2794

Form Factor: Medical Grade Powder Coated Steel Dolly Cart w/ Run Flat Tires
Front Cover: Weatherproof Lid w/ Front-located Handle and Lock
Cover Locking Position: Upward w/ Internal Locks on Both Sides of the Lid
Vibration Isolators: Transformer and Breakers
Drain Plug: Panel
Cart Material: Steel
Cart Finish: High-Strength TGIC Polyester Powder Coated Blue
Cart Handle Orientation: Horizontal
Lifting Eyelet: (1) Center Point
Wheels: (2) Runflat Inflatable Tires [Rear] & (2) Swivel Casters [Front]
Dimensions: -
Weight: -

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements
Contact us for special requirements
Intl: 1-214-616-6180
Toll Free: 1-800-369-6671
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in Texas

The MPD-CD1-862.40AB-SN7.5SW-GZ-1.N07-2.N03-1.R8-M1 from Larson Electronics is a Medical Grade Temporary Power Distribution System that converts single-phase 250V AC electrical current into single-phase 120V AC. This unit provides operators the ability to safely tap into and distribute 250V AC power from a variety of sources including generators and direct grid power.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

The MPD-CD1-862.40AB-SN7.5SW-GZ-1.N07-2.N03-1.R8-M1 temporary power distribution system gives operators the ability to power their 120 volt equipment from a single system.

Operation:

• Primary Voltage: 250V AC 1PH

• Primary Panel: 250V 1PH 40A MCCB N4R Stainless Steel Panel

• Primary Breaker(s): N/A

• Primary Outlet(s): N/A

• Transformer: 7.5KVA 250V to 120V 1PH N3R

• Secondary Voltage: 120V AC 1PH

• Secondary Panel: 120V 1PH 62.5A MLO N4X Stainless Steel Panel

• Secondary Breaker(s): (1) 20A 1P MCB [125V]; (3) 15A 1P MCB [125V]

• Secondary Outlet(s): (1) 5-20R Hospital Grade Simplex Receptacle [125V]; (2) 5-15R Hospital Grade Simplex Receptacle [125V]; (3) 5-15R NEMA Simple Receptacle [125V]

*See specification table at the top of the page for more information about the power

distribution system.

Protective Construction: A weatherproof flip cover at the front of the unit can be lifted upwards via an accessible handle, which serves as protection for (primary and secondary) breakers and receptacles in rugged environments when deployed at the site. Operators may access locks on the door and on the ears (accessible from the inside of the lid) of the panel. The panel can be positioned upwards and locked in place for easy access to receptacles and breakers. A drain plug on the panel helps the power distribution system achieve a NEMA 3R rating, allowing the unit to be used in both indoor and outdoor locations.

The transformer is protected by vibration isolators that reduce damage to exterior jacket of wiring components and decrease noise during operation. In MGL-style power distribution systems, the presence of vibration isolators ensures wiring between the transformer and panel is well protected and does not have to be frequently replaced. Vibration isolators can also be found on the breakers, which protect the breakers from damage, prevent loose bolts/nuts and reduce overall noise during use in the field.

The medical grade power distribution system is constructed of steel with a polyester powder coated blue finish for durability against dirt, moisture, and mild corrosion. This special coating creates a high-strength barrier for protection from accidental bumps and scratches. The TGIC polyester powder coat finish offers reliable resistance against chemicals, UV light (sun light), and degrading elements in outdoor locations. Our powder coating solution ensures robust color retention for many years without fading. Custom colors, such as black, grey, desert tan, or forest green, and galvanized finishes are available upon request. Non-standard powder coat colors or galvanized finishes may increase price and lead times.

The transformer and load center/distribution assembly is mounted to a standard steel cart style frame resulting in an extremely stable, durable, and mobile power distribution platform. Two rotating urethane casters in the front and two inflatable run-flat tires in the rear on this cart style mounting platform provides easier substation mobility, and a center point lift eye allows easy lifting with cable or chain hooks. This temporary power distribution solution can be modified to meet the needs of job-site receptacle requirements. Larger units are available upon request and can be equipped with skids or trailer mounted.

Certification: All units are built in accordance to NFPA 70 (National Electric Code) and certified to UL 1640. All equipment is NEMA 3R rated for indoor and outdoor use and provide a degree of protection against dirt, water, and ice. NEMA 4 and NEMA 4X equipment can be equipped upon request.

Grounding: Transformer is grounded to the frame and we provide a grounding lug on the frame for the earth ground.
~Please check all motor loads for dual rated motors that will work 208 or 240.~

Applications: This power distribution system is ideal for indoor or outdoor use and applications including but not limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits, and shipyard operations. These power distribution systems are popularly used in applications where external power sources are often necessary. We also offer class rated transformers for use within explosion proof and hazardous location environments.

Custom Built Systems Available: Larson Electronics is a manufacturer and we can build portable power distribution systems to your specifications. Although we carry several models of portable power distribution systems in stock, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CD1-862.40AB-SN7.5SW-GZ-1.N07-2.N03-1.R8-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CD1-862.40AB-SN7.5SW-GZ-1.N07-2.N03-1.R8-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CD1-862.40AB-SN7.5SW-GZ-1.N07-2.N03-1.R8-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CD1-862.40AB-SN7.5SW-GZ-1.N07-2.N03-1.R8-M1

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Links (Click on the below items to view):

- **ANSI Certificate 1**(https://www.larsonelectronics.com/images/product/ANSICert1/326357.PDF)
- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(https://www.larsonelectronics.com/images/product/CECCert/326357.PDF)
- **Catalog Page - Product Series**(https://www.larsonelectronics.com/images/product/CatalogPage/326357.PDF)
- **CE Certificate**(https://www.larsonelectronics.com/images/product/CECert/326357.PDF)
- **Certificate 1, Misc**(https://www.larsonelectronics.com/images/product/Cert1/326357.PDF)
- **Certificate 2, Misc**(https://www.larsonelectronics.com/images/product/Cert2/326357.PDF)
- **Certificate 5, Misc**(https://www.larsonelectronics.com/images/product/Cert5/326357.PDF)
- **MSDS (Material Safety Data Sheet**(https://www.larsonelectronics.com/images/product/Msds/326357.PDF)
- **Operations Manual**(https://www.larsonelectronics.com/images/product/Manual/326357.PDF)
- **RoHS Certificate (Restriction of Hazardous Substances)**(https://www.larsonelectronics.com/images/product/RoHSCert/326357.PDF)
- **Single Line Diagram (One-Line Diagram)**(https://www.larsonelectronics.com/images/product/Oneline/326357.PDF)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(https://www.larsonelectronics.com/images/product/NECCert/326357.PDF)
- **Wiring Diagram**(https://www.larsonelectronics.com/images/product/WiringDiagram/326357.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/326357.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/326357.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/326357.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/326357.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/326357.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/326357.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/326357.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/326357.JPG)
- **HigResPic9**(https://www.larsonelectronics.com/images/product/HigResPic9/326357.JPG)
- **HigResPic10**(https://www.larsonelectronics.com/images/product/HigResPic10/326357.JPG)
- **Video1**(https://www.youtube.com/watch?v=1Fm9YWJrT-Y)
- **Video2**(https://www.youtube.com/watch?v=rR-PuRIWQzI)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)