Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-HV-PT-R7-A11-GTD-115KV-SX.LM-C0.15WXMYZ-Z-60HZ-OL-OD-M1

115 KV Potential Transformer, Oil Filled - 92000Y/55200 Grounded Wye Primary, 115/69V Secondary, 0.15 WXMYZ Metering Accuracy Class, Outdoor

Product ID: 327021

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MT-HV-PT-R7-A11-GTD-115KV-SX.LM-C0.15WXMYZ-Z-60HZ-OL-OD-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-HV-PT-R7-A11-GTD-115KV-SX.LM-C0.15WXMYZ-Z-60HZ-OL-OD-M1 Potential Transformer

Unit Type: Potential Transformer, Oil Filled, Wound Type
Phase: Single Phase
Primary Voltage: 92000Y/55200
Maximum System Voltage: 115 KV
Primary Phasor: Grounded Wye
Primary BIL: 450 KV
Creepage Distance: 75.2 inches

Strike Distance: 45.25 inches

Secondary Voltage: 115/69V
Number of Secondary Windings: 2
Ratio: 480/800:1:1

Frequency: 60 Hz

No. of Bushings: (1)
Burden Rating: ZZ (400 VA)
ANSI Accuracy Class Operation at Rated Voltage (Metering Accuracy): 0.15 WXMYZ
Protection Accuracy Class: N/A
Insulating Material: PMP Insulation Paper

Ratings

Meets IEEE C57.13 Standard
Meets ANSI C12.11 Standard
Outdoor Service
Non-corroding Nameplate

Factory Tests

Induced Voltage Test
Applied Voltage Dielectric Test (Between windings and between winding and ground)
Polarity Test
Ratio Test
Power Factor Test
Impedance, Excitation, and Composite Error Measurements
Ratio and Phase Angle Measurement and Calculations
Resistance Measurements
Capacitance and Dissipation Factor Test
Dielectric Tests
Partial Discharge Measurements

Cooling Class: ONAN
Insulator Type: Molded Epoxy
Primary Connection: NEMA 4-hole Terminal Pad, 0.4" Thickness
Secondary Connection: TBD
Secondary Terminal Box: Included, w/ 1" NPT Conduit on Both Sides
Ground Lug: Included
Winding Material: Copper
Nameplate Material: Stainless Steel
Operation Temperature Range: 5°C to +40°C
Humidity: 100%
Service Condition: Outdoor
Wind Speed Rating: 160 mph, with a 1.1 Overload Factor
Altitude: 3,300 ft Above Sea Level

Seismic Qualification: High Level, IEEE 693

Painting: Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)
Housing Materials: Epoxy Resin
Mount: Base Mounting
Cantilever Strength: 1100 lbs
Dimensions (Approximate): 17.7"-W x 20.5"-D x 47.9"-H
Weight (Approximate): 375 lbs

Accuracy Test

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MT-HV-PT-R7-A11-GTD-115KV-SX.LM-C0.15WXMYZ-Z-60HZ-OL-OD-M1 Potential Transformer from Larson Electronics facilitates power distribution in outdoor locations and is designed for power utility applications. The low operating costs, low heat emissions and low cost of ownership make this transformer an ideal solution for metering, protective relaying, high voltage system control and more. This outdoor service instrument transformer is equipped with galvanized I-beam pedestals for installation.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: The potential transformer is rated for 92000Y/55200 primary and 115/69V secondary and has a metering accuracy class of 0.15 WXMYZ at 60 Hz. The system has heavy-duty windings for high strength and thermal/electrical conductivity.

Primary Connections: The transformer has standard terminals for primary connections.

Secondary Connections: The potential transformer is equipped with a terminal block protected by a removable cover.

Benefits: The MT-HV-PT-R7-A11-GTD-115KV-SX.LM-C0.15WXMYZ-Z-60HZ-OL-OD-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

Applications: Electric power distribution, utilities, protective relaying, utility power generation, power grids, substations, metering, high voltage system control, step down transmission and more.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/327021.JPG)
- **Video1**(https://www.youtube.com/watch?v=4-JEyYeYcn8)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)