

Product ID: 327196

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image:

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-DS-WM-NFDS-3P-3W-480V-400A-DF-BM-N1 Disconnect Switch - Non Fused Disconnect

Unit Type: Service Entrance Non Fused Disconnect Switch

Line-In: N/A (customer provided)

Line-In Cord Cap: N/A (customer provided)

Line-In Connections: Terminal Lugs

Line-In Orientation: Bottom Feed

Voltage (V): 480V AC Delta or Wye

Phase (PH): 3-Phase

Frequency (Hz): 60 Hz (60-Cycles)

Protection Method: N/A (customer provided)

Protection Type: N/A (customer provided)

Protection Ampacity: -

Mains Rating (Amps): 400A

Interrupting Rating: 200 kA @ 480V AC

Horsepower (Standard): 100 HP at 480V

Horsepower (Max): 250 HP at 480V

Disconnect Means: Manual via Handle

Neutral Connection: -

Line-Out: N/A (customer provided)

Line-Out Cord Cap: N/A (customer provided)

Line-Out Connection: Terminal Lugs, Accepts 750MCM-1/0

Line-Out Orientation: Bottom Feed

Form Factor: Rectangular, Slim-profile Enclosure w/ Lockable Door

Door: (1) Left Hinged Door w/ Pad Lockable Handle

Ratings

NRTL Listed Service Equipment

NRTL Listed to UL 891 Dead Front Switch Boards

NEMA 1 Rated for Indoor Use

Made in the USA



Enclosure Material: Steel

Enclosure Finish: Painted

Enclosure Type: NEMA 1

Mount: Wall Mount

Dimensions: Steel

Weight: 102 lb

Shipping Dimensions:

Shipping Weight:

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The MPD-DS-WM-NFDS-3P-3W-480V-400A-DF-BM-N1 from Larson Electronics is a Power Distribution Non Fused Disconnect Switch designed for safe, reliable and convenient power disconnection in industrial facilities. This wall-mounted unit is housed in a NEMA 1 rated steel enclosure for indoor locations where basic protection from dust and access to live parts is required.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

The MPD-DS-WM-NFDS-3P-3W-480V-400A-DF-BM-N1 disconnect switch provides operators with a secure method of isolating three-phase 480V AC power. This 3-pole, 3-wire non-fused disconnect features a manual operating handle for straightforward on/off control of circuits and equipment.

Operation: The dead front disconnect switch features a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power.

Enclosure Design: The unit is protected by a durable steel enclosure with a painted finish. Rated NEMA 1, the enclosure is intended for indoor dry-location use and protects internal components from incidental contact and limited dust exposure.

Certification: This disconnect switch is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.

Mount: Operators can mount the disconnect switch on walls or flat vertical surfaces.

Customization: The MPD-DS-WM-NFDS-3P-3W-480V-400A-DF-BM-N1 can be customized to meet specific operating and power requirements. Example of customizations include:

- Making the non-fused disconnect portable and certified to NRTL UL 1640 for portable equipment
- Adding single pole camlock connectors for quick connections
- Adding heaters for cold environments
- Aiding alarm relays for trip notification down stream

- Adding powering meters

Applications: This disconnect switch is suitable for indoor industrial applications including, but not limited to, manufacturing floors, mechanical rooms, pump control, HVAC systems, electrical distribution points, panelboard isolation, and general facility power control.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Faqs



Image:




Image:



Image:



Image:



Product ID: 327196

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/327196.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/327196.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/327196.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/327196.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/327196.JPG>)
- **Video1**(<https://www.youtube.com/watch?v=IDLo7pSOYvw>)
- **Video2**(<https://www.youtube.com/watch?v=aOJY5E9e33I>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)