Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-MES-SF6-3P3W-13-15.5KV-600A-BE-FM-MET-CU-N3R-SS-M5

Metal Enclosed Switchgear, SF6 Gas Insulated Vacuum Fault Interruption, 600 Amp, 15.5 KV AC, 3-Pole 3-Wire, 1 IN 3 OUT, Floor Mount, Bottom Entry, Copper Bus, NEMA 3R, 304L Stainless Steel

Product ID: 327652

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-MES-SF6-3P3W-13-15.5KV-600A-BE-FM-MET-CU-N3R-SS-M5

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-MES-SF6-3P3W-13-15.5KV-600A-BE-FM-MET-CU-N3R-SS-M5 Metal Enclosed Switchgear

Unit Type: Metal Enclosed Switchgear, SF6 Gas Insulated Vacuum Fault Interruption
Unit Configuration: Double-Sided
Line-In Connections: Dead Front HV Bushings, Equipped with Insulated Connectors
Line-In Orientation: Bottom Feed
Nominal Voltage: 15000V
Voltage Rating: 15.5 KV AC, 3 Phase, 3 Wire
BIL Rating: 95 KV
Frequency: 60 Hz
Current: Alternate 3 Phase Current
Protection Method: N/A
Protection Type: N/A
Protection Fuses: N/A
Bus Rating: 600 A
Continuous Current Rating: 600 A
Interrupting Fault Current Rating: 12.5 kA
Short Circuit Current Rating: 12.5 kA
Bus Type: Silver-plated copper

Ratings

NRTL Listed Service Equipment
NRTL Listed to UL 891 Dead Front Switchboards
NEMA 3R Rated for Indoor/Outdoor Use
Made in the USA

Bay #1 (Source Way)
(1) 15kV, 600A, Load Interrupter Switch

Bay #2 (Load Way)
(1) 600 Ampere Deadbreak: 15 kV, 95 kV BIL, SF6

Bay #3 (Load Way)
(1) 600 Ampere Deadbreak: 15 kV, 95 kV BIL, SF6

Bay #4 (Load Way)
(1) 600 Ampere Deadbreak: 15 kV, 95 kV BIL, SF6

Bushing Rating/Material: 600A rated bushings with removable silver-plated copper threaded studs
Parking Stands: Included, adjacent to each bushing to accommodate horizontal feedthroughs and standoff insulators
Provision of Motor Operator Controllers: Included, w/ Close/Open Pushbuttons for manual operation
Viewing Window: Included
Control Cabinet: Mounted on the side of the enclosure, 18”-Width
Space Heaters: Included, w/ Thermostat
Metering Current & Potential Transformer (CT/PT): Included Mount and Termination CT/PT
Operating Positions: Open/Close/Ground with Padlock Positions
Ground Pad: Included, 2-Hole, 15.5 kV Rated
Line-Out Connection: Dead Front HV Bushings, Equipped with Insulated Connectors
Line-Out Orientation: Bottom Feed
Lifting Brackets: Included, Fitted on the Top of the Enclosure
Form Factor: Rectangular, Slim-profile Enclosure w/ Lockable Door, 1 incoming panels, 3 outgoing panel
Panel Configuration: 1 x Incoming panels, 3 x Outgoing panel
Mounting: Pad Mount
Enclosure Material: 304L Stainless Steel
Enclosure Finish: Munsell™ 7GY 3.29/1.5 Green
Enclosure Type: NEMA 3R, Ventilated
Dimensions: 67”H x 85”W x 47”D
Weight: 992.08 lbs
Shipping Dimensions: -
Shipping Weight: -
Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The Larson Electronics MPD-MES-SF6-3P3W-13-15.5KV-600A-BE-FM-MET-CU-N3R-SS-M5 Metal Enclosed Switchgear is designed for reliable, safe and convenient power distribution at industrial work sites. Designed for floor mounting installations. This bottom feed switchgear is protected by a NEMA 3R rated, stainless steel enclosure with a ventilated design.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

The MPD-MES-SF6-3P3W-13-15.5KV-600A-BE-FM-MET-CU-N3R-SS-M5 service entrance

switchgear provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. Compatible with 15.5 KV AC, the switchgear features a manual operating handle. This bottom feed disconnect carries a 12.5 kA at 15.5 KV AC interrupt rating.

Operation: The switchgear features front control panel and rear termination equipped with a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power and busbars (at rear). A dead front cover protects operators from the switches for safety. Operators can inspect the switches through the dead front via a vented cover. Removing the dead front allows access to the switches

Enclosure Design: The switchgear is protected by a stainless steel enclosure with ANSI green finish. A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3R rated for protection against water, moisture and debris. This rating allows the fused disconnect to be used in indoor/outdoor areas.

Certification: This switchgear is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.

Mount: Operators can mount the service entrance disconnect on floors and flat surfaces.

Customization: The MPD-MES-SF6-3P3W-13-15.5KV-600A-BE-FM-MET-CU-N3R-SS-M5 can be customized to meet specific operating and power requirements. Example of customizations include:

• Making the disconnect switches portable and certified to NRTL UL 1640 for portable equipment

• Adding single pole camlock connectors for quick connections

• Adding heaters for cold environments

• Aiding alarm relays for trip notification downstream

• Adding power meters

Applications: This switchgear is suitable for indoor/outdoor use and applications including, but not limited to, solar equipment, construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-MES-SF6-3P3W-13-15.5KV-600A-BE-FM-MET-CU-N3R-SS-M5

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-MES-SF6-3P3W-13-15.5KV-600A-BE-FM-MET-CU-N3R-SS-M5

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-MES-SF6-3P3W-13-15.5KV-600A-BE-FM-MET-CU-N3R-SS-M5



Image: MPD-MES-SF6-3P3W-13-15.5KV-600A-BE-FM-MET-CU-N3R-SS-M5

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1** (https://www.larsonelectronics.com/images/product/HigResPic1/327652.JPG)
- **HigResPic2** (https://www.larsonelectronics.com/images/product/HigResPic2/327652.JPG)
- **HigResPic3** (https://www.larsonelectronics.com/images/product/HigResPic3/327652.JPG)
- **HigResPic4** (https://www.larsonelectronics.com/images/product/HigResPic4/327652.JPG)
- **HigResPic5** (https://www.larsonelectronics.com/images/product/HigResPic5/327652.JPG)
- **HigResPic6** (https://www.larsonelectronics.com/images/product/HigResPic6/327652.JPG)
- **HigResPic7** (https://www.larsonelectronics.com/images/product/HigResPic7/327652.JPG)
- **HigResPic8** (https://www.larsonelectronics.com/images/product/HigResPic8/327652.JPG)
- **HigResPic9** (https://www.larsonelectronics.com/images/product/HigResPic9/327652.JPG)
- **ISO 9001 Certification** (http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate** (https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map** (https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)