

MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1

Automatic Circuit Recloser, 630 Amp, 11000V AC, 3-Phase, NEMA 3R, Pole Mounted

Product ID: 327827

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1 Automatic Circuit Recloser

Ratings/Approvals

Product Type: Automatic Circuit Recloser

Complies with ANSI C37.60-2012

Current Type: AC

Phases: 3 Phase

Nominal Operating Voltage: 11 kV

Rated Maximum Voltage: 15.5 kV

Rated lightning impulse withstand voltage: 75 kV

Creepage Distance: 224.84 inches

Rated power frequency: 50 Hz

Rated Continuous Current: 630 A

Short-Time Breaking Capacity: 12.5 kA, 1 sec.

Making Current (Peak): 25 kA

Protection: o/c & e/f digital relay

Closing Voltage: 90 V

Tripping Voltage: 90 V

Interrupting Medium: Vacuum

Mechanical Operation: 10,000

Full Load Operation: 10,000

Closing Mechanism: Magnetic Actuator

Tripping Mechanism: Magnetic Actuator

Bushing Type: Silicon Rubber

Factory Tests

High potential withstand test

Pressure test for sealing verification

Functional and TCC trip tests

Production tests per IEEE C37.60

Dielectric, mechanical life, and heat run tests

Terminals: 2-4 Hole Pad Terminals

Operating mechanism: Dual-Coil (Bi-stable), Magnetic actuator

Manual Operation Handle: Yellow, under sleet hood

Energy Storage: Close and trip capacitors for 100 operations after power loss

Current Transformers: (3) 400:1 Ratio

SCADA Interface: RS-232 (DNP) & Ethernet 100 Base FX (DNP, Modbus, IEC 60870-5)

Programmable I/O: (8) inputs and (8) outputs

Operating Modes: Mode A: Three-phase trip, three-phase lockout / Mode B: Single-phase trip, three-phase lockout / Mode C: Single-phase trip, single-phase lockout

Lockout Feature: Manual handle in open position prevents electrical closing

Position Indicator: Red/green flag for open/closed status

Ambient Temperature: -40°C to +55°C

Humidity: 0-100%

Altitude: 9,850 Ft

Protection Degree: NEMA 3R

Mounting: Pole-mounted Through Mounting Brackets

Mounting Frame: Galvanized cluster-mounting frame for pole mounting

Finish Paint: Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)

Weight: 837.76 lbs

Dimensions: 30.71"-W x 11.3"-D x 24.53"-H

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

Made in the USA

The MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1 from Larson Electronics is an Automatic Circuit Recloser (ACR), which designed for use on overhead distribution lines as well as distribution substation applications for voltage class 15.5 KV.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

The MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1 is completely supplied with an RC control and communications cubicle. The RC control cubicle provides all the protection, data logging and communications functions in a single device. The MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1 has been designed for use as a stand alone device that is easily integrated into distribution automation and remote control schemes using the in-built communications capability.

The MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1 incorporates vacuum interrupters inside solid dielectric insulated poles which are housed within the arc fault venting designed, stainless steel tank. This ensures maximum life and reliability with a fully insulated arrangement inside the long life housing.

Operation: Each phase of the recloser mechanism is operated by an individual magnetic actuator. In the MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1 three phase operation the magnetic actuators are mechanically interlocked to guarantee correct operation. The device is latched in the closed position by magnetic latching and each magnetic actuator uses a single coil. The recloser can be mechanically tripped using the yellow mechanical hook stick operated lever in the base of the tank. The device Open/Close indication, also located in the base of the tank, uses a green 'O' to designate contacts are open and a red 'I' to designate contacts closed.

Mount: The MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1 is pole mounted.

Certification: This MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1 complies with the ISO 9001 Standards, certified by an external independent organization, complies with the AS/NZS ISO 14001 & AS/NZS 4801 Standards, certified by an external independent organization and OHSAS 18001 Standards

Applications: This MT-ACR-VA-R7-3P-AC-DMV-630A-12.5KA-5-UPM-Z-Z-N3R-M1 is used in power distribution to control and protect lines, transformer and distribution substations, motors, transformers, capacitor banks, etc.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Fags



Export Control Classification Number (ECCN): EAR99



Links (Click on the below items to view):

- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/327827.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)