
HST-0.25-3.1-2KV-PF

1/4" Dual Wall Irradiated Polyolefin Heat Shrink Tubing – 2 kV Rated - Red-Black Color - Sold per Foot

Product ID: 329100

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

1/4" Dual Wall Irradiated Polyolefin Heat Shrink Tubing – Sold per Foot

The HST-0.25-3.1-2KV-PF heat shrink tubing has a shrink ratio of 3:1, 2 kV Rated, Finished with Red-Black Color

HST-0.25-3.1-2KV-PF is sold by the foot. For example, an order with a quantity of 1 equals 1 foot of tubing.



Frequently Asked Questions (FAQ)

There are no Fags



Export Control Classification Number (ECCN): EAR99



Links (Click on the below items to view):

- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)