Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPP-PSU-250A-3P4W-S20-1.7N

Explosion Proof Plug - C1D1/ATEX Rated - 3P4W - 600V Rated - 250A NEC/CEC, 260A ATEX

Product ID: 330172

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPP-PSU-250A-3P4W-S20-1.7N

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPP-PSU-250A-3P4W-S20-1.7N C1D1/ATEX Rated Connector

Listing: NRTL Listed for United States, Canada and International; ATEX Rated

Unit Type: Explosion Proof Plug with Attachment Cover

Dimensions: -

Weight: -
Voltage Rating: 600V AC Rated
Configuration: 3-pole, 4-wire
Amp Rating: 250A for NEC/CEC, 260A for ATEX
Materials: 6061-T6 Copper-free Aluminum
Finish: Anodized
Mating Receptacle: EPO-PSU-250A-3P4W
Cable Diameter: 1.5" - 1.625"
Color: Black

Ratings

Class I, Divisions 1 & 2 Groups C, D @ 480V AC; 60/400Hz, Circuit Breaking
Class I, Divisions 1 & 2 Groups B, C, D @ 600V AC; 60/400Hz, Circuit Breaking
Class II, Division 1 Groups F, G @ 600V AC; 60/400Hz, Circuit Breaking
AEx d IIC T6
Ex II 2 GD Ex d IIC IP 66/67 T 70°C 1000V AC, 500V DC
MIL-STD 202, Method 101, Condition D
Corrosion Resistant
Factory Sealed

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The EPP-PSU-250A-3P4W-S20-1.7N from Larson Electronics is an Explosion Proof Plug for use in flammable work sites and industrial facilities. This 600V rated unit features a 3-pole, 4-wire configuration. Constructed of copper-free aluminum, the explosion proof plug is protected by an attachment cover.

The EPP-PSU-250A-3P4W-S20-1.7N offers secure power connections in Class I, Divisions 1 & 2, Class II, Division 1 and ATEX rated combustible facilities. This explosion proof plug is rated at 600V AC and takes on a 3-pole, 4-wire configuration. The unit carries a 250-amp NEC/CEC rating and a 260-amp ATEX rating (applicable rating depends on classification). Suitable for hazardous locations, this plug is pre-wired and factory sealed. This unit is compatible with 1.5" - 1.625" cable diameter.

Durability: The explosion proof plug is constructed of 6061-T6 copper-free aluminum with an anodized finish. This corrosion-resistant power device complies with MIL-STD 202, Method 101, Condition D.

Applications: Hazardous locations, flammable work sites, oil and gas, chemical processing, wet and damp locations, warehouses, industrial plants, confined spaces, paint spray booths and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPP-PSU-250A-3P4W-S20-1.7N

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPP-PSU-250A-3P4W-S20-1.7N

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/330172.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/330172.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/330172.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)