Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

XLE-CR-10A-690V-2XNO.2XNC-DRM

10A Control Relay - 690V AC - 125V DC Coil, 2NO/2NC - DIN Rail or Screw Mount

Product ID: 330413

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

XLE-CR-10A-690V-2XNO.2XNC-DRM Control Relay

Unit Type: Control Relay
Dimensions: 2.3"H x 1.8"W x 2.2"D
Weight: 0.49 lbs
Operating Voltage: 690V AC, 400 Hz
Coil Voltage: 125V DC
Rated Current: 10A
Rated Making Capacity: 110A
Associated Fuse Rating: 10A gG
Rated Insulation Voltage: 690V
Coil Type: Built-in Bi-directional Peak Limiting Diode Suppressor
Contacts: 2 NO, 2 NC
Operating Temperature: -25°C to 50°C
Materials: -
Mounting: 35mm DIN Rail or Screw Mount
Connections: Screw Terminals

Features/Ratings

EN/IEC 60947-5-1
UL 60947-5-1
CSA C22.2 No 60947-5-1
IP2X

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Made in the USA

The XLE-CR-10A-690V-2XNO.2XNC-DRM from Larson Electronics is a Control Relay for industrial sites. The device is rated for 690V AC operating voltage with 125V DC coil voltage. This unit caters to 35mm DIN rail or screw mount installations.

The XLE-CR-10A-690V-2XNO.2XNC-DRM is a control relay for reliable switching or controlling functions. This unit comes with two NO and two NC contacts. Rated at 10 amps, the control relay features a built-in bi-directional peak limiting diode suppressor type coil. Operators can access screw terminals for connections. The control relay is compatible with 35mm DIN rail or screw mounting.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson

Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)