Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-CW11-TB.125AB-DE75YT25HV-LZ-1.L35-L09-8.N10-M1

75 KVA Mobile Power Distribution, 480V-208Y/120V 3PH & 125V DC 1PH, (1) L21-30R (2) L6-30R (8) 5-20R GFCI Duplex Outlets, NEMA 3R

Product ID: 330709

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-CW11-TB.125AB-DE75YT25HV-LZ-1.L35-L09-8.N10-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-CW11-TB.125AB-DE75YT25HV-LZ-1.L35-L09-8.N10-M1 - Temporary Power Distribution System

Line-in Cord: Not Included - Requires Minimum Use Wiring 125A Rated Cu @ [600V] (**Customer Provided**)
Line-in Cord Cap: Not Included – Requires Minimum Use Device 125A @ [480V] (**Customer Provided**)
Primary Voltage (V): 480V AC Delta
Primary Phase (PH): 3-Phase (3PH)
Primary Frequency (HZ): 60 Hz (60-cycles)
Primary Panel: 480V 3PH 100A MCCB N3R; 480V 3PH 30A MCCB N3R
Primary Breaker(s): N/A
Primary Outlet(s): N/A
Primary Protection: MCCB Circuit Breakers
Transformer (KVA): 75KVA 480V – 208Y/120V 3PH N3R Transformer; 25KW 480V 3PH – 125VDC Power Supply
Secondary Voltage (V): 208Y/120V AC Wye; 125V DC
Secondary Phase (PH): 3-Phase (3PH); 1-Phase (1PH)
Secondary Frequency (HZ): 60 Hz (60-cycles)
Secondary Panel: 208Y/120V 3PH 225A MLO N3R; 125V DC 200A N3R
Secondary Breaker(s): (1) 30A 3P MCB [250V]; (2) 30A 2P MCB [250V]; (8) 20A 1P MCB [125V]

Ratings

Max Primary OCP: 125A @ 480V

Max Secondary Output: 225A @ 208V AC; 200A @ 125V DC
NEMA 3R Indoor or Outdoor Use
Made in the USA
NRTL Certified to UL 1640
NRTL Certified to CSA C22.2 No. 14

Powder Coat Finish Standards:

Complies with ASTM D-523
Complies with ASTM D-3359
Complies with ASTM D-522
Complies with ASTM D-3363
Complies with ASTM D-2794

Secondary Outlet(s): (1) L21-30R NEMA Twist-Lock Receptacle [208Y/120V]; (2) L6-30R NEMA Twist-Lock Receptacle [208V]; (8) 5-20R NEMA Duplex-GFCI [125V]
Secondary Protection: MCB Circuit Breakers; GFCI's
Form Factor: Blue Powder Coated Steel Open Cube Skid w/ Casters
Doors: N/A
Frame Material: Steel
Frame Finish: High-Strength TGIC Polyester Powder Coated Blue
Cart Handle Orientation: Horizontal
Lifting Eyelet: (1) Top Located
Skid Pockets: (2) Bottom Located
Casters: (4) Locking Casters
Dimensions: -
Weight: (*Please note that dimensions are approximate and subject to change*) 1,250 lb
Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in Texas

The MPD-CW11-TB.125AB-DE75YT25HV-LZ-1.L35-L09-8.N10-M1 from Larson Electronics is a Power Distribution Substation that converts three-phase 480V AC Delta electrical current to three-phase 208Y/120V AC Wye. This open cube style power distribution unit provides operators the ability to safely tap into and distribute 480V AC power from a variety of sources including generators and direct grid power.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

The MPD-CW11-TB.125AB-DE75YT25HV-LZ-1.L35-L09-8.N10-M1 temporary power distribution system gives operators the ability to power their 208 volt AC, 120 volt AC, and 125V DC equipment from a single system.

Operation:

• Primary Voltage: 480V AC Delta 3PH

• Primary Panel: 480V 3PH 100A MCCB N3R; 480V 3PH 30A MCCB N3R

• Primary Breaker(s): N/A

• Primary Outlet(s): N/A

• Transformer: 75KVA 480V – 208Y/120V 3PH N3R Transformer; 25KW 480V 3PH – 125VDC Power Supply

• Secondary Voltage: 208Y/120V AC Wye; 125V DC

• Secondary Panel: 208Y/120V 3PH 225A MLO N3R; 125V DC 200A N3R

• Secondary Breaker(s): (1) 30A 3P MCB [250V]; (2) 30A 2P MCB [250V]; (8) 20A 1P MCB [125V]

• Secondary Outlet(s): (1) L21-30R NEMA Twist-Lock Receptacle [208Y/120V]; (2) L6-30R NEMA Twist-Lock Receptacle [208V]; (8) 5-20R NEMA Duplex-GFCI [125V]

*See specification table at the top of the page for more information about the power distribution system.

Protective Construction: Unlike many portable power distribution boxes made of plastic and utilizing thin gauge, low grade metals in their construction, this unit is designed for serious use and is ruggedly constructed to withstand demanding conditions and heavy duty industrial applications. The transformer and load assembly is mounted on a 3/16" thick carbon steel mounting platform and the load center/distribution assembly is mounted to the standard 2" x 2" x 1/8" square carbon steel tubing frame, resulting in an extremely stable, durable, and well protected power distribution platform. This model is equipped with forklift skid pockets, locking polyurethane casters, and a top located lifting eyelet which allows easy lifting with cable or chain hooks. This can be replaced for an additional cost with stainless steel, hot dip galvanized steel, or aluminum depending on the customer's needs. Larger units are available upon request and can be equipped with skids or be trailer mounted.

The power distribution system is constructed of steel with a polyester powder coated blue finish for durability against dirt, moisture, and mild corrosion. This special coating creates a high-strength barrier for protection from accidental bumps and scratches. The TGIC polyester powder coat finish offers reliable resistance against chemicals, UV light (sun light), and degrading elements in outdoor locations. Our powder coating solution ensures robust color retention for many years without fading. Custom colors, such as black, grey, desert tan, or forest green, and galvanized finishes are available upon request. Non-standard powder coat colors or galvanized finishes may increase price and lead times.

The transformer and load center/distribution assembly is mounted to a standard steel cube style frame resulting in an extremely stable, durable, and mobile power distribution platform. This temporary power distribution solution can be modified to meet the needs of job-site receptacle requirements. Larger units are available upon request and can be equipped with skids or trailer mounted.

Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge



Grounding: Transformer is grounded to the frame and we provide a grounding lug on the frame for the earth ground.
~Please check all motor loads for dual rated motors that will work 208 or 240.~

Certification: All units are built in accordance to NFPA 70 (National Electric Code) and NRTL certified to UL 1640. All equipment is NEMA 3R rated for indoor and outdoor use and provide

a degree of protection against dirt, water, and ice. NEMA 4 and NEMA 4X equipment can be equipped upon request.

Applications: This power distribution system is ideal for indoor or outdoor use and applications including but not limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits, and shipyard operations. These power distribution systems are popularly used in applications where external power sources are often necessary. We also offer class rated transformers for use within explosion proof and hazardous location environments.

Custom Built Systems Available: Larson Electronics is a manufacturer and we can build portable power distribution systems to your specifications. Although we carry several models of portable power distribution systems in stock, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CW11-TB.125AB-DE75YT25HV-LZ-1.L35-L09-8.N10-M1



Image: MPD-CW11-TB.125AB-DE75YT25HV-LZ-1.L35-L09-8.N10-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CW11-TB.125AB-DE75YT25HV-LZ-1.L35-L09-8.N10-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CW11-TB.125AB-DE75YT25HV-LZ-1.L35-L09-8.N10-M1

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Links (Click on the below items to view):

- **ANSI Certificate 1**(https://www.larsonelectronics.com/images/product/ANSICert1/330709.PDF)
- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(https://www.larsonelectronics.com/images/product/CECCert/330709.PDF)
- **Catalog Page - Product Series**(https://www.larsonelectronics.com/images/product/CatalogPage/330709.PDF)
- **CE Certificate**(https://www.larsonelectronics.com/images/product/CECert/330709.PDF)
- **Certificate 1, Misc**(https://www.larsonelectronics.com/images/product/Cert1/330709.PDF)
- **Certificate 2, Misc**(https://www.larsonelectronics.com/images/product/Cert2/330709.PDF)
- **Certificate 5, Misc**(https://www.larsonelectronics.com/images/product/Cert5/330709.PDF)
- **MSDS (Material Safety Data Sheet**(https://www.larsonelectronics.com/images/product/Msds/330709.PDF)
- **Operations Manual**(https://www.larsonelectronics.com/images/product/Manual/330709.PDF)
- **RoHS Certificate (Restriction of Hazardous Substances)**(https://www.larsonelectronics.com/images/product/RoHSCert/330709.PDF)
- **Single Line Diagram (One-Line Diagram)**(https://www.larsonelectronics.com/images/product/Oneline/330709.PDF)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(https://www.larsonelectronics.com/images/product/NECCert/330709.PDF)
- **Wiring Diagram**(https://www.larsonelectronics.com/images/product/WiringDiagram/330709.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/330709.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/330709.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/330709.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/330709.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/330709.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/330709.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/330709.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/330709.JPG)
- **HigResPic9**(https://www.larsonelectronics.com/images/product/HigResPic9/330709.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)