

MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2

5000A Switchboard w/ 5000A Main Circuit Breaker - 480Y/277V 3PH 4W, 60Hz - NEMA 3R

Product ID: 331883

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2 Industrial Switchboard

Unit Type: Switchboard with Main Circuit Breaker

Bus Max Amp Rating: 5000 Amps

Input: N/A

Fuses: N/A

Receptacles: Included, GFCI

Bus Voltage Rating: 480Y/277V, 3PH, 4W, 60Hz

Wiring Configuration: 4-Wire

Poles: 3-Poles

Bus Max Available Fault Current (RMS): 65 kAIC

Incomer Main Circuit Breaker Rating: 5000A, 65 kAIC, w/ Shunt Trip coil

Incomer Current Transformer: Included, (3) Current Transformers

Outgoing(s): (3) 2000A-3P CBs

CT/PT Metering Cabinet: Included

Protection: Long Time, Short Time, Instantaneous, Ground Fault, Overcurrent Trip Switch

Dynamic Arc Flash Sentry (DAS) Capability: Included

Display: N/A

Aux Contacts: (4) Form C

Ratings/Features

NEMA 1 Indoor Enclosure
Rodent Barrier
24V Trip Unit Display Power
Certified to UL Dead front
Switchboard Standards
24/7 Utility Lockable and
Accessible
Service Entrance Rated



Ground Bus: 1/4 x 2 IN copper, continuous over length of switchboard and solidly grounded to each vertical section structure

Temperature Rise: 65°C

Thermostat: Included, Strip Type

Space Heaters: Included, Thermostatically Controlled

Terminal Blocks: Included

Contact Wear Indication: Visual

Ground Lug: Provided

Bus Material: Silver Plated Copper

Enclosure Material: Stainless Steel

Entry Point: Front Access

Connection Type: Cable

Cable Entry: Bottom Feed

Enclosure Type/Rating: NEMA 3R, Indoor/Outdoor

Enclosure Paint Color: ANSI 49

Mounting Type: Floor Mounted

Dimensions: 36.00"-W x 47.5"-D x 91.5"-H

Weight: 1,405 lbs

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-765-7664

E-

mail: sales@larsonelectronics.com

The MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2 from Larson Electronics is a Switchboard with Main Circuit Breaker for power distribution systems. This 5,000-amp rated power distribution unit is compatible with three-phase 480Y/277V AC, 60Hz. Equipped with an open-bottom configuration, the system is encased in a NEMA 3R enclosure that is painted ANSI 49.

The MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2 AC is designed for power distribution in industrial facilities. This 4-wire unit operates with three-phase 480Y/277V, 60 Hz. With a 5000-amp system ampacity, the switchboard with circuit breaker has a 65 kA RMS short circuit rating and four, form c auxiliary contacts with visual contact wear indication. Protective features include: ammeter trip unit, long time, short time, instantaneous, ground fault, overcurrent trip switch and rodent barrier. This system contains a 24V trip unit display power. The Type 3R unit comes with ground lugs and is painted ANSI 49.

Wiring: The MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2 accepts cable connections with a phase wire range of 3/0 - 750 kcmil.

Mount: The MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2 can be securely mounted to any flat surface. This non-walk-in system is accessible through the front with a left of lineup through the bottom entry point.

Applications: Residential and light commercial applications, air conditioning units and any other power distribution systems that require overload breaker protection.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more



information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Faqs



Image: MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2



Image: MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2




Image: MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2



Image: MPD-MDS-CB-480Y.277-3P-5000A-N3R-M2



Export Control Classification Number (ECCN): EAR99



Links (Click on the below items to view):

- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/331883.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/331883.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/331883.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/331883.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/331883.JPG>)
- **HigResPic6**(<https://www.larsonelectronics.com/images/product/HigResPic6/331883.JPG>)
- **HigResPic7**(<https://www.larsonelectronics.com/images/product/HigResPic7/331883.JPG>)
- **HigResPic8**(<https://www.larsonelectronics.com/images/product/HigResPic8/331883.JPG>)
- **Video1**(<https://www.youtube.com/watch?v=Ua6P4b84gPw>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)