Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 332443

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image:

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

This unit is Made In USA - Manufactured in Texas

MPD-CS2-309.100AF-SZ0-Z-1.E34-2.L09-10.N10-M1 Spider Box
Line-In: 4100B12W IEC Pin & Sleeve Inlet [125/250V]
Line-Out: 4100R12W IEC Pin & Sleeve Receptacle [125/250V]
Extension Cord: 50' #2 AWG 4/C Type W [2000V] w/ 4100P12W IEC Pin & Sleeve Male Plug and 4100C12W IEC Pin & Sleeve Connector [125/250V]
Primary Voltage: 120/240V AC
Primary Phase: 1-Phase (1PH)
Primary Frequency: 60 Hz (60-cycles)
Primary Panel: 120/240V 1PH 100A MLO Yellow Spider Box N3R
Primary Breaker(s): (2) 30A 2P MCB [250V]; (10) 20A 1P MCB [125V]
Primary Outlet(s): (2) L6-30R NEMA Twist-Lock [250V]; (10) 5-20R NEMA Duplex-GFCI [125V]
Primary Protection: MCB Circuit Breakers; GFCI's
Transformer: N/A
Secondary Voltage: N/A
Secondary Breaker(s): N/A
Secondary Outlet(s): N/A
Secondary Protection: N/A
Housing Material: Steel
Form Factor: Yellow Powder Coated Spider Box w/ Legs
Mounting: Portable/Base Stand
Dimensions: -
Weight: -

Ratings/Approvals
Max Primary OCP: 100A @ 240V
Max Secondary Output: -
NRTL Certified to UL 1640
NEMA 3R Weatherproof
Overload Protection
Short Circuit Protection

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-765-7664
E-mail:

This unit is Made In USA - Manufactured in Texas

The MPD-CS2-309.100AF-SZ0-Z-1.E34-2.L09-10.N10-M1 from Larson Electronics is a Portable Spider Box for indoor, outdoor, and rugged applications. This unit allows operators to use single-phase 120/240V AC power via a 4100B12W IEC pin & sleeve inlet. The device is equipped with two 30-amp twist lock outlets, ten 20-amp duplex outlets for equipment, and a 50' #2 AWG 4/C Type W extension cord terminated in a 4100P12W IEC pin & sleeve male plug and 4100C12W IEC pin & sleeve connector. For robust protection, the powder coated yellow spider box is NEMA 3R rated and protected by impact/flame resistant weatherproof covers.

Operation:

• Primary Voltage: 120/240V AC 1PH

• Primary Panel: 120/240V 1PH 100A MLO Yellow Spider Box N3R

• Primary Breaker(s): (2) 30A 2P MCB [250V]; (10) 20A 1P MCB [125V]

• Primary Outlet(s): (2) L6-30R NEMA Twist-Lock [250V]; (10) 5-20R NEMA Duplex-GFCI [125V]

• Transformer: N/A

• Secondary Voltage: N/A

• Secondary Panel: N/A

• Secondary Breaker(s): N/A

• Secondary Outlet(s): N/A

*See specification table at the top of the page for more information about the power distribution system.

This portable spider box has a 4100B12W IEC pin & sleeve inlet for bringing single-phase 120/240V AC power power into the unit. The device supports two 30-amp 2-pole 250V miniature circuit breakers protecting two 30-amp L6-30R twist lock 250V outlets and ten 20-amp 1-pole 125V miniature circuit breaker protecting ten 20-amp 5-20R NEMA 125V GFCI duplex outlets. This unit is also equipped with a 50' #2 AWG 4/C Type W extension cord terminated in a 4100P12W IEC pin & sleeve male plug and 4100C12W IEC pin & sleeve connector. The MPD-CS2-309.100AF-SZ0-Z-1.E34-2.L09-10.N10-M1 spider box features short circuit, overload, open neutral, and reverse phasing protection. Should circuit overload occur, the unit will automatically shut down to protect the spider box from damage.

The housing on the MPD-CS2-309.100AF-SZ0-Z-1.E34-2.L09-10.N10-M1 is constructed of steel with a NEMA 3R enclosure rating. This powder coated yellow device is approved for wet locations and features heavy-duty impact/flame resistant weatherproof covers. Two angled legs at the base of the unit and low center of gravity ensures this spider box does not tip over

in the field.

Certification: All units are built in accordance to NFPA 70 (National Electric Code). All equipment is NEMA 3R rated for indoor and outdoor use and provide a degree of protection against dirt, water, and ice. NEMA 4 and NEMA 4X equipment can be equipped upon request.

Applications: Indoor or outdoor applications including but not limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits, and shipyard operations. These units are popularly used in applications where external power sources are often necessary. We also offer class rated transformers for use within explosion proof and hazardous location environments.

Larson Electronics is a manufacturer and we can build portable power distribution systems to your specifications. Although we carry several models of portable power distribution systems in stock, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 332443

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **ANSI Certificate 1**(https://www.larsonelectronics.com//images/product/ANSICert1/332443.PDF)
- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(https://www.larsonelectronics.com//images/product/CECCert/332443.PDF)
- **Catalog Page - Product Series**(https://www.larsonelectronics.com//images/product/CatalogPage/332443.PDF)
- **CE Certificate**(https://www.larsonelectronics.com//images/product/CECert/332443.PDF)
- **Certificate 1, Misc**(https://www.larsonelectronics.com//images/product/Cert1/332443.PDF)
- **Certificate 5, Misc**(https://www.larsonelectronics.com//images/product/Cert5/332443.PDF)
- **MSDS (Material Safety Data Sheet**(https://www.larsonelectronics.com//images/product/Msds/332443.PDF)
- **RoHS Certificate (Restriction of Hazardous Substances)**(https://www.larsonelectronics.com//images/product/RoHSCert/332443.PDF)
- **Single Line Diagram (One-Line Diagram)**(https://www.larsonelectronics.com//images/product/Oneline/332443.PDF)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(https://www.larsonelectronics.com//images/product/NECCert/332443.PDF)
- **Wiring Diagram**(https://www.larsonelectronics.com//images/product/WiringDiagram/332443.PDF)
- **HigResPic1**(https://www.larsonelectronics.com//images/product/HigResPic1/332443.JPG)
- **HigResPic2**(https://www.larsonelectronics.com//images/product/HigResPic2/332443.JPG)
- **HigResPic3**(https://www.larsonelectronics.com//images/product/HigResPic3/332443.JPG)
- **HigResPic4**(https://www.larsonelectronics.com//images/product/HigResPic4/332443.JPG)
- **HigResPic5**(https://www.larsonelectronics.com//images/product/HigResPic5/332443.JPG)
- **HigResPic6**(https://www.larsonelectronics.com//images/product/HigResPic6/332443.JPG)
- **HigResPic7**(https://www.larsonelectronics.com//images/product/HigResPic7/332443.JPG)
- **HigResPic8**(https://www.larsonelectronics.com//images/product/HigResPic8/332443.JPG)
- **HigResPic9**(https://www.larsonelectronics.com//images/product/HigResPic9/332443.JPG)
- **Video1**(https://www.youtube.com/watch?v=iEU4ZBzsfpg)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)