Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPNFDS-250A-3P-AXC.2

250A Explosion Proof Non Fused Disconnect Switch - Class I, II, III - 3-Pole, (2) 10A Rated Aux Contacts - (3) NPT Hubs

Product ID: 332830

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPNFDS-250A-3P-AXC.2

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPNFDS-250A-3P-AXC.2 Explosion Proof Disconnect Switch / Breaker

Listing: NRTL Listed for United States and Canada
Dimensions: 41.25"-H x 17.25"-W x 12.73"-D
Weight: 425 lbs
Configuration: 3-Pole
Voltage Rating: 600V AC Max
Amps: 400
Fusible: No
Aux Contacts: (2) NO Contact
Aux Contact Ratings: 10A Rated
Materials: Cast Aluminum
Hardware Materials: Stainless Steel
Mounting: Surface Mount
Hub Qty: (4)
Hub Locations: (1) 3" NPT, (1) 0.75" NPT @ Top, (1) 3" NPT, (1) 0.5" NPT @ Bottom
Conduit: Operator Provided
All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Features/Ratings

Class I, Division 1 & 2 Groups B, C & D
Class I, Zones 1 & 2 Groups IIB+ H2 & IIA
Class II, Division 1 & 2 Groups E, F & G
Class III, Divisions 1 & 2
NRTL Listed to UL 1203
NRTL Listed to CSA C22.2 No. 30, 25
NEMA 3, 4, 4X, 7(B,C,D) 9(E,F,G)

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EPNFDS-250A-3P-AXC.2 Explosion Proof Non-fused Disconnect Switch provides operators with a Class I and II, Divisions 1 and 2 cast aluminum enclosure that provides overcurrent and short circuit protection of service entrance, feeder or branch circuits, lighting, heating, appliance and motor circuits. This 250-amp explosion proof disconnect switch features an EHD frame, two 10-amp rated auxiliary contacts and a 3-pole configuration. The EPNFDS-250A-3P-AXC.2 operates on a maximum of 600V AC and features three NPT hubs for wiring connections.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO EXPLOSION PROOF ENCLOSURES

The EPNFDS-250A-3P-AXC.2 explosion proof disconnect switch is made of cast aluminum and features a rectangular bolted cover design for uniform and attractive installations. The cover bolts and hinges are made from stainless steel. The external on/off lever can be locked into the "off" position with room for up to three padlocks for superior security. The internal circuit breaker handle mechanism is a sliding plate type mounted to the cover. The circuit breaker is trip free of the external handle mechanism. Two 10-amp rated auxiliary contacts are available inside the system.

Hubs: For completing electrical connections, three NPT hubs are provided on the enclosure. one 3" NPT and one .075" NPT Hubs are located at the top of the unit; and one 3" NPT and one 0.5" NPT hub can be found at the bottom of the disconnect.

Applications: Petroleum refineries, chemical and petrochemical plants, storage areas, and other processing facilities where hazardous substances are handled or stored.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPNFDS-250A-3P-AXC.2

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPNFDS-250A-3P-AXC.2

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPNFDS-250A-3P-AXC.2

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPNFDS-250A-3P-AXC.2

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Wiring Diagram**(https://www.larsonelectronics.com/images/product/WiringDiagram/332830.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/332830.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/332830.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/332830.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/332830.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/332830.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/332830.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/332830.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/332830.JPG)
- **HigResPic9**(https://www.larsonelectronics.com/images/product/HigResPic9/332830.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)