Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPS-PB10-MS-2XC

10A Explosion Proof Push Button Switch - Class I, II, III - 600V Rated, (2) Contact Block, Momentary - NEMA

Product ID: 333435

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPS-PB10-MS-2XC

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPS-PB10-MS-2XC Explosion Proof Push Button

Listing: NRTL Listed for United States, Canada
Dimensions: -
Weight: -
Voltage: 600V AC Rated
Amps: 10A
Push Button Type: Momentary
Contacts: Double Poles (NO or NC or Both)
Button Color: Red, Green or Black
Nameplate Marking: -
Ambient Operating Temp Range: -
Materials: Aluminum
Mounting: Surface
Termination: Dead End or Feed Through
Hub Size: 1/2" NPT or 3/4" NPT

Ratings/Features

Class I, Divisions 1&2, Groups C,D
Class I, Zones 1&2, Groups IIB,IIA
Class II, Divisions 1&2, Groups E,F,G
Class III
NEMA 7 (C,D), 9 (E,F,G)

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The Larson Electronics EPS-PB10-MS-2XC Explosion Proof Momentary Push Button Switch is designed for Class I, II and III rated combustible environments. This 10-amp

switch is rated at 600V AC. Manufactured using non-sparking materials, the explosion proof unit is suitable for surface mounting installations.

The EPS-PB10-MS-2XC is built to be heavy duty, and is rated for 10 amps at 600V AC. The momentary button is offered in red, green, and black. double Poles (2) Contact Block options include: normally open or normally closed or both.

The EPS-PB10-MS-2XC housing is made out of malleable aluminum body with an aluminum cover, and is epoxy powder coated for a natural finish. This switch is enclosed in a separate sealing chamber, and the sealing chamber has smooth, double flanges that mate both to the cover and the mounting enclosure to provide flame tight joints. The screws consist of stainless steel captive screws and attach the sealing chamber to cover and mounting enclosure.

Wiring: This explosion proof unit is offered in a dead end or feed through configuration. Hub size options include: 1/2" NPT or 3/4" NPT. Operators connect to the switch via an internal terminal strip.

Mount: The EPS-PB10-MS-2XC is compatible with surface mounting applications. There are two openings at the back of the device for installation.

Applications: Manufacturing, industrial, warehouse, lighting, motor-generator sets, compressors, wet areas or locations where combustible dusts, fibers or flying are present or where explosive gases or vapors may be present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPS-PB10-MS-2XC

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664




Image: EPS-PB10-MS-2XC

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPS-PB10-MS-2XC

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPS-PB10-MS-2XC

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPS-PB10-MS-2XC

Product ID: 333435

Export Control Classification Number (ECCN): EAR99

Options:

EPS-PB10-MS-2XC-Termination-Contacts-Button Color
Example: EPS-PB10-MS-2XC-0.5-DE-NO-RED

Termination	
1/2IN DEAD END	-0.5-DE
3/4IN DEAD END	-0.75-DE
1/2IN FEED THRU	-0.5-FT
3/4IN FEED THRU	-0.75-FT

Contacts	
NORMALLY OPEN	-NO
NORMALLY CLOSED	-NC
NORMALLY OPEN / NORMALLY CLOSED	-NO.NC

Button Color	
RED	-RED
GREEN	-GRN
BLACK	-BLK
BLUE	-BLU

Links (Click on the below items to view):

- **Wiring Diagram**(https://www.larsonelectronics.com/images/product/WiringDiagram/333435.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/333435.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/333435.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/333435.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/333435.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/333435.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/333435.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/333435.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/333435.JPG)
- **HigResPic9**(https://www.larsonelectronics.com/images/product/HigResPic9/333435.JPG)
- **Video1**(https://www.youtube.com/watch?v=9O8mHjkpxBI)
- **Video2**(https://www.youtube.com/watch?v=LCYOu15ez4s)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)