

LM-20-6.5-5S-145

20' Five Stage Telescoping Light Mast - Extends up to 20 Feet - Collapses Down to 6.5 Feet, Fold Over - 145 MPH Wind Rating

Product ID: 335131

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: LM-20-6.5-5S-145

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LM-20-6.5-5S-145 - 20' Five Stage Telescoping Light Tower

Length: Telescoping from 7.12' to 20.16'

Weight: +-360 lbs

Capacity: 180 lbs

Materials: Steel

Finish: Powder Coated - Gloss Blue

Operation: (2) 3,500lbs Manual Winches, Electric Optional

Cable: 3/16" Aircraft Cable

Mounting: 1/4" thick, 18"x18" Base Plate

Anchor Bolts: (6) 9/16" Bolts

Shipping: Common Freight

Shipping Dimensions: 9.5'-L x 4'-W x 5'-H

Shipping Weight: +-1100 lbs

Options: Length- Mounting-Fixtures/ Call Us for Special Requirements

Quick Summary

6.5' to 20' Foot Fold Over Light Mast

Steel Construction

Powder Coated Finish

Removable Mast Head

145 mph Wind Resistance

Manual or Optional Electric Operation

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics LM-20-6.5-5S-145 fold over 5-stage light mast provides a safe and effective way for operators to quickly deploy lights, security cameras and other

equipment to elevations of up to twenty feet. This light tower collapses down to six and a half feet and folds over for easy transportation, features a articulating boom that allows for 360° of rotation, and a removable mast head for storing mounted equipment when not in use.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO LIGHT MASTS OR LIGHT TOWERS

This telescoping five stage steel light mast from Larson Electronics is designed to allow operators to quickly and safely deploy lighting, cameras, and other electrical equipment in locations where this equipment must be elevated to heights up to 20' for effective coverage. This light boom can be extended to 20' for maximum area coverage and collapsed to 6.5' for applications where a smaller footprint is required. The tower is constructed of square steel tubing with a base section 4.49' in length and 7" by 7" by 1/4" thick, second section 4.78' in length and 5" by 5" by 3/16" thick, third section 4.96' in length and 4" by 4" by 3/25" thick, fourth section 5.15' in length and 3" by 3" by 1/8" thick, and top section 5.40' in length and 2" by 2" by 3/25" thick. Each section has a 1' overlap. The mast is elevated using an included 3,000 lbs hand winch with 3/16" galvanized steel cable and extended to its full height using a second 3,000 lbs hand winch.



The LM series of telescoping towers are powder coated with glossy blue finish for corrosion resistance and aesthetics. These light masts are typically mounted to trailers or other stable surfaces via a 18" by 18" by 1/4" thick mounting base-plate which has been drilled to accept six 9/16" anchor bolts. A 44" wide and 2" by 2" by 1/4" thick mounting plate is attached to the upper section of the mast which provides a strong and stable platform for light fixtures and

equipment.

The LM family of telescoping towers feature a proprietary mast guidance system, which provides increased stability during high winds. When lowered to 8.75', the mast can withstand winds up to 125 mph. When elevated to its full upright position, the mast can be rotated a full 360°. By loosening the T-Handle, operators can rotate the mast with ease in either direction. The mast can be positioned in one of four different directions, and locked back in place by re-tightening the T-handle. The mast itself spins freely, and can typically be rotated with a single hand.

This light tower weighs approximately 360 lbs and can easily support and lift 180 lbs fixtures. The entire tower assembly is shipped via common freight carrier and when shipped measures approximately 9.5' long, 4' wide, 5' tall and weighs approximately 1100 lbs. Larson Electronics can custom tailor these units to the customer's requirements with longer sections and larger mounting plates. We also offer a choice of either the manual 3,000 lbs hand winches included standard or optional electric winches.

Suggested Applications: Temporary lighting, construction sites, and security camera deployment. We can equip this mast with 1000W or 1500W Metal Halide lights or a wide variety of high powered LED lights with comparable power, including the [LED10WSA-160](#), [LEDLB-200X2E](#), [LEDLB-160X2E](#) or [LEDLB-80x2E](#).

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Faqs



Image: LM-20-6.5-5S-145



Image: LM-20-6.5-5S-145



Image: LM-20-6.5-5S-145



Image: LM-20-6.5-5S-145

LM-20-6.5-5S-145

Product ID: 335131

Export Control Classification Number (ECCN): EAR99

Options:

LM-20-6.5-5S-145-Finish

Example: LM-20-6.5-5S-145-PWDC.BLU

Finish	
POWDER BLUE	-PWDC.BLU
POWDER BLACK	-PWDC.BLK
GALVANIZED	-GLVD

Links (Click on the below items to view):

- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/335131.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/335131.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/335131.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/335131.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/335131.JPG>)
- **HigResPic6**(<https://www.larsonelectronics.com/images/product/HigResPic6/335131.JPG>)
- **HigResPic7**(<https://www.larsonelectronics.com/images/product/HigResPic7/335131.JPG>)
- **Video1**(<https://www.youtube.com/watch?v=wk4BEqRuPww>)
- **Video2**(<https://www.youtube.com/watch?v=e2aJtlkS9WM>)
- **Video3**(<http://www.youtube.com/watch?v=JihBBRtt5G4>)
- **Video4**(<http://www.youtube.com/watch?v=Q0gr6bYmJTs>)
- **Video5**(<https://www.youtube.com/watch?v=lg4S6c1p0M>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)