Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

## MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1

# 15 kV Electrical Metering Cabinet, Combinations (CT/PT) - 3-Phase - Dry Type - Pad Mount, Outdoor Service

**Product ID: 335442**

**Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



Image: MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1

**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1 Electrical Metering Cabinet Combinations (CT/PT)**

**Unit Type:** Electrical Metering Cabinet (EMC)
**Unit Configuration:** Combinations Current & Voltage Transformer (CT/PT), Dry Type
**Rated Frequency:** 60 Hz

**Phase:** Three Phase

**CT Specifications:**

**Quantity:** (3)

**Rated Voltage:** 15 kV
**Current Ratio:** 600:5
**CT Design Form:** Wound
**Accuracy Class:** 0.15S Class

**Secondary Terminals:**

- Provided with a manual shorting device

**Ratings**

Complies with ANSI / IEEE C57.13
Complies with ANSI / IEEE C57.13.6
Meets/Exceeds IEEE C57.12.28
Meets IEEE 386 for 200A separable load-break connectors

**Warranty**

Failure of any component due to defective design, material, or workmanship within 12 months of energization or 18 months from delivery, whichever occurs first, shall be repaired or replaced at no cost.

- Suitable for terminating #14 through #4 AWG copper conductors
- Sealable protective cover provided

**PT Specifications:**

**Quantity:** (3)
**Primary Voltage:** 7,200V (for 12,470Y/7,200V system)
**Primary Voltage Class:** 15 KV
**Secondary Voltage:** 120V
**Voltage Ratio:** 7200:120
**Accuracy Class:** 0.15 Class
**Thermal Burden:** 1500 VA @ 30°C
**Primary Protection:** Primary fuse mounted on each PT

**BIL:** 110 kV BIL
**Main Bus Rating:** 600A continuous
**Bus Bracing:** 20 kA symmetrical / 28 kA asymmetrical
**Bus Material:** Copper
**Jumpers:** Fused jumpers from main bus to CTs and VTs, Insulated for 15 kV
**Dead-Front Terminations:** 600A Separable Dead-Break Bushings
**Dead-Front Bushings Per Phase:** One (1) 600A Dead-Break Bushing Well
**Radial Feed:** One (1) 600A Dead-break connection per phase
**Test Switch Type:** 10-pole, reversed potentials, ST terminals, Lexan cover
**Test Switch Location:** Right interior wall of CT/PT compartment
**CT Wiring:** #10 AWG solid copper
**VT Wiring:** #12 AWG solid copper
**Color Coding:** VA Orange, VB Blue, VC Yellow, VN White, CT-A Black, CT-B Brown, CT-C Red, CTR Gray
**Terminal Order:** VA, VB, VC, VN, CTR-A, CT-A, CTR-B, CT-B, CTR-C, CT-C
**Meter Socket:** External mounting provision per EUSERC 339
**Continuous Thermal Current Rating Limit Factor (rf):** 1.5
**Minimum clearances measured from live part to bare metal:**
- Phase-to-Ground: 6.0 inches minimum
- Phase-to-Phase: 7.5 inches minimum
Additional stationary barriers provided to allow reduced clearance of 3.0 inches from barrier to live parts.
**Meter Socket:** External mounting provision per EUSERC 339
**Grounding Bosses:** Four (4) total, 1/2-13NC tapped holes, 7/16" deep, two per compartment; accepts #6 solid to #2/0 stranded copper.
**Compartment Layout:** Separate CT/PT and cable termination compartments, located on opposite sides of enclosure.
**Phase To Ground Compartment Barriers:** Red Reinforced Polyester
**Fault Venting:** Tamper-proof stainless screened vents rated for 10kA, 15 cycles.
**Winding Material:** Copper
**Service Condition:** Outdoor
**Roof:** Domed or sloped to prevent standing water
**Base:** Sealed bottom to prevent access to animals and foliage, Screened drain vents provided for drainage in case of flooding
**Altitude:** N/A
**Ambient Temperature Rating:** N/A
**Door Safety:** Internal door safety barrier
**Hardware Materials:** Stainless Steel
**Terminator Parking Stands:** Welded stainless steel, quantity suitable for number of bushings provided
**Enclosure Class:** NEMA 3R Weatherproof, Aluminum

**Nameplate Materials:** Corrosion Resistant Stainless Steel w/ Stainless Steel Screws or Rivets For CT & VT
**Markings:** Manufacturer Name, Manufacturer Serial Number, Nominal Operating Voltage, Rated Current, BIL, Equipment Manufacture Date, One-line diagram showing CT and PT ratios
**Paint Color:** Munsell™ 7GY 3.29/1.5 Bell Green
**Mounting Provisions:** Pad Mount
**Lifting Provisions:** Included
**Spare Parts:** three (3) spare primary fuses for the PTs.
**Dimensions:** 31.5" x 78.7" x 31.5"
**Weight:** 661.4 lbs

**Special Orders- Requirements**
Contact us for special requirements
**Toll Free:** 1-800-369-6671
**Intl:** 1-903-270-1187
**Fax:** 1-903-765-7664
**E-mail:** sales@larsonelectronics.com

**The MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1 Electrical Metering Cabinet from Larson Electronics is designed for power utility applications in outdoor locations. The low operating costs, low heat emissions and low cost of ownership make this transformer an ideal solution for metering, high voltage system control and more. This cabinet is compatible with pad mounting installations.**

***PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

**Cabinet Features:** The MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1 is rated for 15 kV, 60 Hz. The system has heavy-duty windings for high strength and thermal/electrical conductivity.

**Insulation Fluid:** The MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1 is a dry type.

**Primary Connections:** The cabinet has NEMA 4-inch, 2-hole copper pad terminals for primary connections. The terminal conducting surface is horizontal. The current transfer point is tinned or silver plated.

**Secondary Connections:** This CT/PT have accessible terminal blocks for secondary connections. The terminal block is protected by a weatherproof, metal junction box located on the transformer base housing and features a large access door. Operators can access three 1.5" openings for completing connections.

**Mount:** The MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1 is pad mounted.

**Benefits:** The MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1 cabinet offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

**Applications:** Electric power distribution, utilities, utility power generation, power grids, substations, metering, high voltage system control and more.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

# Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664




Image: MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1




Image: MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-EMC-R7-3P-GMR-15KV-YT-600.5CT-N3R-M1

**Export Control Classification Number (ECCN):** EAR99

Links (Click on the below items to view):

- **HigResPic1**( https://www.larsonelectronics.com/images/product/HigResPic1/335442.JPG )
- **HigResPic2**( https://www.larsonelectronics.com/images/product/HigResPic2/335442.JPG )
- **HigResPic3**( https://www.larsonelectronics.com/images/product/HigResPic3/335442.JPG )
- **HigResPic4**( https://www.larsonelectronics.com/images/product/HigResPic4/335442.JPG )
- **HigResPic5**( https://www.larsonelectronics.com/images/product/HigResPic5/335442.JPG )
- **Video1**( https://www.youtube.com/watch?v=4-JEyYeYcn8 )
- **ISO 9001 Certification**( http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF )
- **Business Certificate**( https://www.larsonelectronics.com/images/pdfdocs/w9.PDF )
- **Shipping Time Map**( https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf )