Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

## MT-PSTC-R7-3P-GEXS-180MVA-DRY-HT-LT-A6-BMFF-CZ-2ZZ-M1

# 180/240/300 MVA Substation Power Transformer, Conservator Type - 236000Y/136250 Grounded Wye Primary, 16000V Delta Secondary, ONAN/ONAF/ONAF, Mineral Oil - Dark Grey

**Product ID: 335582**

**Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



Image: MT-PSTC-R7-3P-GEXS-180MVA-DRY-HT-LT-A6-BMFF-CZ-2ZZ-M1

**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**MT-PSTC-R7-3P-GEXS-180MVA-DRY-HT-LT-A6-BMFF-CZ-2ZZ-M1 Conservator Autotransformer**

**Transformer Type:** Substation Power Autotransformer, Conservator Type
**Transformer Configuration:** Liquid Filled
**Transformer Feed Type:** Radial Feed
**Operation:** Step-Down Operation (Approved for Step-Up)
**Phase:** Three Phase
**Capacity (w/o Fans):** 180 MVA (180,000 KVA)
**Capacity (w/ Fans, Stage 1)** 240 MVA (240,000 KVA)
**Capacity (w/ Fans, Stage 2):** 300 MVA (300,000 KVA)
**Vector Group:** YNd1
**Primary Voltage:** 236000Y/136250
**Primary Voltage Switch:** N/A
**Primary Voltage Class:** 245 kV Class
**Primary Phasor:** Grounded Wye
**Primary BIL:** 750 KV
**Primary Neutral BIL:** 150 KV
**Secondary Voltage:** 16000V
**Secondary Voltage Class:** 25 kV Class
**Secondary Phasor:** Delta
**Secondary Line BIL:** 150 KV

**Ratings**

Meets/Exceeds DOE 2016 Efficiency Ratings
Meets/Exceeds CSA Efficiency Ratings
Complies with ANSI / IEEE C57.12.00
Complies with ANSI / IEEE C57 12.28
Complies with ANSI / IEEE C57 12.29
Complies with ANSI / IEEE C57 12.34
Complies with CSA C227.5
Complies with CSA C2.1-06
Complies with ANSI / IEEE C57 12.35
Complies with ANSI / IEEE C57.12.70
Complies with ANSI / IEEE C57.12.110
Complies with ANSI / IEEE C57.12.131
Complies with ANSI / IEEE C62.11
Complies with ANSI / IEEE C62.22
Complies with ANSI / IEEE C37.47
Complies with ANSI / IEEE 386
Complies with ANSI / IEEE C2
Complies with CSA C227.4
Complies with ANSI Z535.4

**Tertiary Voltage:** N/A
**Tertiary BIL:** N/A
**Tertiary Power Rating:** N/A
**Frequency:** 60 Hz
**Temperature Rise:** 65°C, 80°C Hot Spot
**Insulation Rating:** Class A Insulation
**Insulation Type/Material:** Paper + NOMEX (Weidmann materials)
**Cooling Class:** ONAN/ONAF/ONAF
**Forced Air (Fans):** Included, Two-Stages, Totally Enclosed, Individually Protected Type, Fan Blades Of One-Piece Cast aluminum, Galvanized Fan Guards. w/ Automatic - Off - Manual operation for cooling control, 208Y/120 VAC Supply
**Cooling Radiator:** Included, Interchangeable, Has Upper And Lower Drain Plugs, ANSI #70 Sky Grey
**H.V Tap Changer:** 5-Position De-energized Tap Changer (DETC), Rotary Type
**H.V Tap Qty:** (2) FCAN Above Taps, (2) FCBN Below Taps
**H.V Tap %:** 2.5%
**H.V Tap Changer Switch Rating:** 245 KV, ≥ 2× HV winding current
**H.V Tap Changer Switch Location:** H.V Side, Top Mounted
**L.V Tap Changer:** N/A
**L.V Tap Qty:** N/A
**L.V Tap %:** N/A
**L.V Tap Changer Switch Rating:** N/A
**L.V Tap Changer Switch Location:** N/A
**Impedance:** 9.767% @ 180 MVA
**Emergency Rating:** 125% for 30 minutes
**Overvoltage Capability:** 110% (60 min), 120% (20 sec)
**Undervoltage Capability:** 90% (60 min), 70% (20 sec)
**Primary Connection Type:** Live Front, Porcelain Insulator w/ Capacitance tap and Doble testing compatible
**Primary Termination Arrangement:** Inline, Top Mounted, ≥ 8.5 ft above base
**Primary Termination:** NEMA CC1 4-Hole Pad connectors
**Primary Bushing Qty:** (4)
**Primary Bushing Rating:** 245 KV Class, 900 kV BIL, Porcelain, ANSI #70 Sky Grey
**Primary Neutral Connection:** Included, 25 KV Class, 150 kV BIL, Porcelain, ANSI #70 Sky Grey
**Primary Surge Arrestors:** Included, (3) metal-oxide station type, Porcelain, ANSI #70 Sky Grey
**Primary Surge Arrestor Voltage Rating:** 230 KV
**Primary Surge Arrestor MCOV Rating:** 140 KV
**Primary Overcurrent Protection (OCP):** N/A
**Primary Bushing CT:** Included, (2) Per Each Phase, 1200:5 Ratio MR, C800 Accuracy Class, 5-Lead, 1.0 Thermal Rating Factor, (1) Per Each Phase, 3000:5 Ratio MR, C800 Accuracy Class, 5-Lead, 1.0 Thermal Rating Factor, (1) on H2 Bushing, 1200:5 Ratio MR, C50 Accuracy Class, 5-Lead, 1.0 Thermal Rating Factor
**Primary Neutral Bushing CT:** Included, (1) 600:5 MR, C400 Accuracy Class, 5-Lead, 1.0 Thermal Rating Factor
**Primary Overcurrent Protection (OCP):** N/A
**Primary Grounding Provisions:** Two copper faced ground pad located at diagonal corners near base, w/ two-bolt terminal connectors
**Secondary Connection Type:** Live Front
**Secondary Termination Arrangement:** Inline, Top Mounted, ≥ 8.5 ft above base
**Secondary Termination:** NEMA CC1 4-Hole Pad connectors
**Secondary Bushing Qty:** (3)
**Secondary Bushing Rating:** 25 KV Class, 150 kV BIL, Porcelain, ANSI #70 Sky Grey
**Secondary Neutral Connection:** N/A
**Secondary Overcurrent Protection (OCP):** N/A
**Secondary Bushing CT:** Included, (2) Per Each Phase, 14000:5 Ratio SR, C800 Accuracy Class, 5-Lead, 1.0 Thermal Rating Factor, (1) on X2 Bushing, 14000:5 Ratio MR, C400

Complies with ASTM D6871
Complies with ASTM D3487
Complies with 10 CFR Part 431
Complies with CSA C802-3
Complies with CSA C88.1
Complies with CSA C88
Complies with CSA C88-16
Complies with CSA C802.1
Complies with CSA C50
Complies with NEMA 260-1996

**Features**

Hot Stick Included, HV Door Mount
Penta-head Bolt Entry Assembly
High-Fire Point Insulating Fluid
Non-PCB Insulating Fluid
Tamper Proof Housing
Hinged Front Compartment Doors, Pad Lockable
NEMA 4X Wiring Compartment

**Efficiency %:** N/A
*Based on transformer operating at 50% of nameplate base kVA.*

**Load Losses Based on 75°C Reference Temp.**
**Off-Load Loss (in watts):** TBD
**On-Load Loss (in watts):** TBD
**Total Load Loss (in watts) at 100%:** TBD

**Total Losses at 55°C LL Temp. & 20°C NL Temp.**
**Total Load Loss (in watts) at 50%:** TBD

Accuracy Class, 5-Lead, 1.0 Thermal Rating Factor
**Secondary Surge Arrestors:** Included, (3) metal-oxide station type, Porcelain, ANSI #70 Sky Grey
**Secondary Surge Arrestor Voltage Rating:** 18 KV
**Secondary Surge Arrestor MCOV Rating:** 15.3 KV
**Secondary Grounding Provisions:** Included, (2) Grounding Pads Located On Diagonally Opposite Corners Of The Tank Base For Grounding Of The Transformer With Bolt Type Connectors For Connection To 2/0 to 500 KCMIL Stranded Copper conductor
**Secondary Neutral Bushing CT:** N/A
**Tertiary CT:** N/A
**Tertiary Surge Arrestors:** N/A
**Tertiary Surge Arrestor Voltage Rating:** N/A
**Tertiary Surge Arrestor MCOV Rating:** N/A
**Metering Current Transformer (CT):** Included
**Metering Panel:** Included, SEL-2533 annunciator with DC power supply w/ support for DNP 3.0 comm protocol w/ 14 digital inputs and 7 digital outputs
**Auxiliary Control Panel :** Included, 120/208 VAC + 125 VDC
**Load Break Switch:** N/A
**Load Break Switch Qty:** N/A
**Load Break Switch Rating:** N/A
**Load Break Switch Location:** N/A
**Efficiency Standard(s):** Meets ANSI/IEEE Standards
**K-Factor Rating (Harmonic Mitigation):** K-1 (Standard)
**Pulse Drive Rating:** N/A
**Insulation Fluid:** Mineral Oil Fluid, Non-PCB Fluid
**Fluid (Oil) Capacity*:** TBD
**Fluid (Oil) Weight*:** TBD

**Transformer Monitoring:** Included Monitor SEL 2414 P/N: 241421ACA913A851130 with Annunciator 2533 P/N: 2533012130XA2X0

**Liquid Level Indicator:** Included, MESSKO type with alarm/trip
**Winding Temperature Indicator:** Included Thermometer, Messko, Type: MT-ST/60 VMR/4C/4M
**RTD:** Included, 100Ω Platinum (top oil & ambient)
**Liquid Temperature Indicator:** Included Thermometer, Messko, Type: MT-ST/60 RM/2C/2M
**Pressure/Vacuum Indicator:** Included, With Scale Range Of Plus Or Minus 10 PSI
**Rapid Rise Relay:** Included, Qualitrol 900 series
**Pressure Relief Device:** Included, Self-resetting (Messko MPreC)
**Nitrogen Oil Preservation System:** Included, Sealed conservator with nitrile bladder
**Fiber Optic Monitoring:** Included, Rugged Monitoring T301
**Breather :** Included, Silica gel, weatherproof

**Fault Indicator:** Included, Buchholz Relay (Messko MSAFE)

**Gas Relay:** Included
**Gas Analyzer:** Included, Camlin Power TOTUS TTM9
**Fill Valve:** Included, with vacuum filling
**Fill Valve Location:** Top Mounted
**Drain Valve:** Included W/ Sampling Port, with vacuum drying
**Drain Valve Location:** Side of transformer tank
**Winding Material:** Copper
**Ambient Temperature Rating:** 55°C

**Ambient Operating Temperature Range:** -20°C to +55°C

**Isokeraunic Level :** 50 thunderstorm - days/year
**Wind Velocity:** 120 MPH
**Sound Level:** Complies with C57.12.90
**Elevation (Altitude):** 3300ft (1000 meters) Above Sea Level

***Note:*** *Losses offered are typical only, not guaranteed*

**Labeling:**
Externally Stenciled (Painted) KVA Rating
Externally Stenciled (Painted) Voltage Rating
External Non-PCB Label
External Warning & Danger Label
External Barcode Label
Internal Busing & Accessory Labeling
Stainless Steel Riveted Nameplate

**Factory Tests:**
Winding Resistance Test
Short-circuit Impedance Test (will not result in an impedance change exceeding 2% of the impedance value measured prior to short circuit testing)
Insulation Resistance Test
Voltage Ratio Error Test
Load Loss (Wattage) Test
Separate Source Voltage Withstand Test
Induced Voltage Withstand Test
No-load Loss (Wattage) Test
Pressure Integrity Test

**Special Tests:**
Temperature Rise Test
Insulation Power Factor Test - winding to winding & winding to ground
Lightning Impulse Test

**Shipping:**
Shipped on pallet on open flatbed
Palletized on Wooden Pallet w/ Skid Pockets
Pallet Skid Facing Outward Sides of Truck
***Note:*** *Crated shipping in lieu of palletizing can be done upon request for an additional fee*

**Core Material:** Silicon Steel Laminations, Grain Oriented, cold-rolled, non-aging, Round Core/Coil Design
**Tank Material:** Coated Steel
**Cabinet Material:** Coated Steel
**Base Platform Material:** Coated Steel
**Hardware Material:** Stainless Steel
**Portability:** Lifting lugs, provisions for jacking under base, w/ base construction suitable for using rollers or skidding
**Housing Type:** Metal Casing Liquid Filled Transformer
**Enclosure Rating:** NEMA 4X Weatherproof
**Seismic Rating:** High seismic, According to IEEE-693 & IEEE C57.114
**Paint Type:** Applied corrosion-resisting primer to all surfaces, Applied top coat baked enamel to provide a minimum of 3 mils (.75 mm) thick, The top of the main tank and LTC compartment is a non-skid coating, Radiator is electrostatic coated
**Finish Color:** Dark Grey
**Mounting:** Supporting Structures
**Conduit Opening:** N/A
**Tank Cover Access Handhole:** Included, 2 × 24" manholes + additional access covers
**Dimensions*:** 456"-W x 228"-D x 396"-H
**Weight*:** 660,000 lbs
*Please note that numbers are approximate and subject to change

**Special Orders - Special Requirements**
Contact us for special requirements
**Toll Free:** 1-800-369-6671
**Intl:** 1-903-270-1187
**Fax:** 1-903-765-7664
**E-mail:** sales@larsonelectronics.com

**The MT-PSTC-R7-3P-GEXS-180MVA-DRY-HT-LT-A6-BMFF-CZ-2ZZ-M1 Conservator Substation Transformer from Larson Electronics offers powerful, reliable, and efficient power distribution in outdoor locations. The low operating costs, low heat emissions, and low cost of ownership make this transformer ideal for a wide range of applications and businesses. This transformer ensures extra space for storing oil and is equipped with breathers to facilitate air flow. The conservator transformer should be installed on supporting structures.**

***PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

**Transformer Features:** The industrial transformer features a primary voltage of three-phase 236000Y/136250 Grounded Wye and a secondary voltage of three-phase 16000V Delta. This system is rated for 180 MVA (180,000 KVA) natural cooled, 240 MVA (240,000 KVA) first stage fan cooled and 300 MVA (300,000 KVA) second stage fan cooled. We offer systems with loop or radial feed, as well as dead front or live front primary connections. The transformer features a 5-position off-load tap changer with two +2.5% taps above and two -2.5% taps below to allow small changes in voltage. There is a rapid rise relay present on the system.

The system features copper windings for high strength and thermal/electrical conductivity. This transformer consists of a rectangular coil and a five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).

The MT-PSTC-R7-3P-GEXS-180MVA-DRY-HT-LT-A6-BMFF-CZ-2ZZ-M1 has fans for forced air cooling. This non-sealed system features breathers for cooling when operating temperatures increase.

**Temperature Rise:** This unit features 65°C temperature rise for reduced heat waste, increased reliability and longer life. At 65°C temperature rise, the transformer offers 180 MVA (180,000 KVA) natural cooled, 240 MVA (240,000 KVA) first stage fan cooled and 300 MVA

(300,000 KVA) second stage fan cooled. The transformer meets standard efficiency requirements. The combination of low temperature rise and high efficiency makes this unit suitable for use in outdoor areas.

**Insulation Fluid:** The MT-PSTC-R7-3P-GEXS-180MVA-DRY-HT-LT-A6-BMFF-CZ-2ZZ-M1 features mineral oil fluid (ONAN/ONAF/ONAF). We offer transformers with biodegradable or FR-3 fluids, if needed.

**Biodegradable Fluid:** Biodegradable cooling fluid (vegetable oil) has a higher heat capacity compared to mineral oil, making the liquid safer to use and more reliable during operations. Vegetable oil has a higher flash point and fire point than mineral oil, hydrocarbon oil, silicone oil and synthetic ester. This cooling fluid is also non-toxic and can tolerate higher breakdown voltages than mineral oil. When operating at high temperatures, biodegradable cooling liquid sustains up to 120% load conditions, which helps preserve the transformer's lifespan and performance.

**Gauges:** The following gauges are included with the system: liquid level indicator, Fluid temperature indicator, Winding Temperature Indicator, pressure/vacuum indicator. Standard liquid level, temperature and pressure/vacuum gauges are analog dial types.

**Fault Pressure Devices:** There is a Buchholz relay fault indicator on this unit.

**Gas Relay:** A gas relay with indicators for light gas and heavy gas is included with the transformer. The relay includes two Dry Type Form C auxiliary contacts (1NO + 1NC) for remote alarm when pressure rises above in-field set pressure located in auxiliary control cabinet.

**Surge arresters:** This system comes with surge arresters on both the primary and secondary sides.

**Load Break Switch:** The transformer is not equipped with a load break switch.

**Valves:** The MT-PSTC-R7-3P-GEXS-180MVA-DRY-HT-LT-A6-BMFF-CZ-2ZZ-M1 is equipped with a pressure relief valve.

**Protection Fuses:** This transformer does not have bayonet protection fuses on the primary side. For units without protection fuses, upstream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.

**Mount:** This conservator substation is installed on supporting structures, such as the roof of the transformer main tank.

**Benefits:** The MT-PSTC-R7-3P-GEXS-180MVA-DRY-HT-LT-A6-BMFF-CZ-2ZZ-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

**Applications:** General purposes, industrial sites, electrical rooms, underground vaults,

manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities and more.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

# Frequently Asked Questions (FAQ)

There are no Faqs



Image: MT-PSTC-R7-3P-GEXS-180MVA-DRY-HT-LT-A6-BMFF-CZ-2ZZ-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664




Image: MT-PSTC-R7-3P-GEXS-180MVA-DRY-HT-LT-A6-BMFF-CZ-2ZZ-M1

**Warranty:** 24 Months.

**Export Control Classification Number (ECCN):** EAR99

Links (Click on the below items to view):

- **HigResPic1**( https://www.larsonelectronics.com/images/product/HigResPic1/335582.JPG )
- **HigResPic2**( https://www.larsonelectronics.com/images/product/HigResPic2/335582.JPG )
- **HigResPic3**( https://www.larsonelectronics.com/images/product/HigResPic3/335582.JPG )
- **Video1**( https://www.youtube.com/watch?v=4-JEyYeYcn8 )
- **Video6**( https://www.youtube.com/watch?v=olihKUo24KU )
- **Video7**( https://www.youtube.com/watch?v=Yez7eCilgDE )
- **Video8**( https://www.youtube.com/watch?v=Ac5BDPSy964 )
- **ISO 9001 Certification**( http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF )
- **Business Certificate**( https://www.larsonelectronics.com/images/pdfdocs/w9.PDF )
- **Shipping Time Map**( https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf )