Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-C

IEC 60309 Waterproof Connector, 63 Amps 2P+E, 250V 1PH 2P3W, Pin & Sleeve, IP67

Product ID: 336058

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-C

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-C Water Tight Pin and Sleeve Connector

Device Series: IEC 60309 (International Standard)
Device Type: Connector
Dimensions: 6"-L x 3"-W x 3"-H
Weight: +/- 2 Lbs
Amperage Rating: 63A
Voltage: 250V
Frequency: 50/60 Hz
Phase: 1-Phase
Configuration: 2P3W (3P+N+E)
# of Poles: 2-Pole
# of Wires: 3-Wire
Max Voltage Rating: 250V 3PH

Clock Hour: 6H

Cord Range: .670 - 1.625

Dielectric Voltage: 2000V□ for 1 min
# of Operations: > 1000□ connects/disconnects under load, at full rated current and voltage

Minimum Withdrawal Force: 15lbs

Temperature Rise: Max +30°C at full-rated current after 50 cycles of OL at 150% rated current
Operating Temperature Range: -25°C to +65°C

Certifications - Compliance

Certified for United States & Canada
NRTL Certified to UL 1682, UL 1686
NRTL Certified to CAN/CSA C22.2 No 182.1
CE Certified, Low Voltage Directive 73/23/EEC
CE Certified, Low Voltage Directive 93/68/EEC
NRTL Certified to 60309-1, 60309-2
RoHS Certified
Compatible with IEC 60309 Compliant Products
IP67/IP69K Rated Weatherproof
IK07 Rated Drop Resistant
Flame Retardant (UL94 V2)
Certified for Full Load Interrupting
Current Interrupting: Certified for current interrupting at full rated current
Corrosion Resistance: Ferrous parts immersed in 20°C, 10 percent ammonium chloride solution for 10 min
Flammability: Rated V-2 per UL 94
Ingress Protection Rating: IP67/IP69K
Moisture Resistance: Immersed for 24 hours in 5cm of 25°C water per UL 1682

Crush Test: 250lbs for 1 min after -25°C for 6 hrs

Impact Resistance: Drop from 30" 8 times after

Waterproof Rating: IP67, IP69K, NEMA 4X

Shock Resistance: IK09

Flammability: V-2 Rated

Insulation Resistance: 500V for 1 min; >= 5MΩ

Cable Secureness: "Force: 150lb; Torque: 1.0 ft-lb; Max Disp: <= 3/32""

Seals: Neoprene
Material, Housing Body: Toughened PVC
Material, Housing Cover: Toughened PVC
Material, Contacts: Brass
Material, Contact Carrier: Nylon
Material, External Screws: Acid-Proof Stainless Steel
Material, Internal Screws: Zinc-plated steel
Material, Phase/Ground Sleeves: Brass
Material, Sleeve Spring: Stainless Steel
Material, Terminal Screws: Steel
Color: Blue
Shipping Dimensions: -
Shipping Weight: -

conditioning to -25°C for 6 hrs

Mating Plug: XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-P
Mating Receptacle: XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-B
Mating Connector: XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-C
Mating Inlet: XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-R

Cross Compatible: 363C6W

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The Larson Electronics XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-C is an IEC 60309 international standard industrial use waterproof Connector for industrial work sites. The 63-amp pin/sleeve Connector is configured to operate on 1-Phase 250V AC power and features an IP67 waterproof rating. Designed for rugged facilities, the Pole-pole, Wire-wire unit can be disconnected under load up to 1000 times.

The XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-C is an industrial grade Connector with waterproof properties. This pin/sleeve unit is compatible with 1-Phase 250V and holds a 63-amp rating. The IP67-rated Connector is constructed of toughened PVC, reinforced thermoplastic polyester and stainless steel.

The XLE-PA-IP67-309.NA series from Larson Electronics complies with the IEC 60309 standard for international equipment (not North American standard), is a direct cross for 363C6W, and is cross compatible with other equipment designed to the same standard. The XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-C is a Blue Connector with a grounding pin located at clock hour 6.
For North American standard configurations, please see XLE-PA-IP67-309.NA series product line.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: XLE-PA-IP67-309.INTL-1PH-63A-250V-2P3W-C

Warranty: 6 Months.

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/336058.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/336058.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)