

XLE-IM-20.35VDC-DIN

Switch / Proximity Detector Interface Module - Dual Channel - NAMUR Input - Relay Output - DIN Rail Mount

Product ID: 336489

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: XLE-IM-20.35VDC-DIN

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

XLE-IM-20.35VDC-DIN Switch / Proximity Detector Interface

Unit Type: Switch / Proximity Detector Interface

Module Type: Dual Channel Interface Module

Dimensions: -

Weight: -

Power Supply: 20–35 VDC

Input Type: NAMUR Proximity Detector / Dry Contact

Number of Channels: 2 Channel

Output Type: Relay Outputs (Changeover Contacts)

Contact Rating: 250 VAC / 40 VDC / 2A

Mounting: DIN Rail Mount

LED Indicator Lights: Power and Channel Status

Operating Temperature Range: -20°C to +60°C

Isolation: Intrinsically Safe Barrier Isolation

Ratings/Approvals

UL Listed

ATEX Certified

IECEX Certified

Suitable for Zone 0 Hazardous Areas

EN/IEC 60079 Compliant

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

The Larson Electronics XLE-IM-20.35VDC-DIN Switch / Proximity Detector Interface Module provides reliable signal isolation and monitoring solutions for industrial automation and hazardous location systems. Compatible with NAMUR proximity

detectors and switch inputs, the unit is designed for DIN rail mounting installations.

The XLE-IM-20.35VDC-DIN supports dual-channel operation for interfacing field devices with control and monitoring systems in industrial facilities. This unit operates on 20-35 VDC and features relay output contacts for seamless integration with Provox systems. The device includes LED status indicators, line fault detection capability and intrinsically safe isolation for hazardous area applications.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@microelectronics for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Fags



Warranty: 12 Months.

Export Control Classification Number (ECCN): EAR99



Links (Click on the below items to view):

- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/336489.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)