Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-DX-3P-480D-27KVA-400Y.230-N3R

27 KVA SCR Drive Isolation Transformer - 480V Delta Primary - 400Y/230 Wye-N Secondary - NEMA 3R

Product ID: 337662

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MT-DX-3P-480D-27KVA-400Y.230-N3R

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DX-3P-480D-27KVA-400Y.230-N3R Drive Isolation Transformer

Unit Type: SCR Drive Isolation Transformer, Dry Type
Phase: Three Phase
Frequency: 60 Hz
Capacity: 27 KVA
Primary Voltage: 480V
Primary Current: 32.5 A
Primary Connection: Delta
Primary FCAN: 1 x 5%
Primary FCBN: 1 x 5%
Secondary Voltage: 400Y/230V
Secondary Current: 39 A
Secondary Connection: Wye-N
Winding Material: Aluminum
Efficiency: No Efficiency Specification
Insulation Class: 220°C (Class R)
Temperature Rise: 150°C
Secondary Phase Angle: 30°
Impedance (@ 170°C): 5.5%
Cooling Class: Class AA

Ratings

Listed for United States and Canada
AA Cooling
NEMA 3R Rated
Drive Isolation Transformer

Seismic Zone: Zone 4
Thermal Protective Device: Normally Closed (All Coils) Thermostatswith 200°C Setpoint
Sound Level: 45 dBA (ST-20)
Primary Termination: Terminal Block
Secondary Termination: Mechanical Lugs
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated
Finish: ANSI 61 Grey, UL50 Finish
Dimensions: 19.37"-L x 24.39"-W x 25.5"-H
Weight: 320 lbs
Mounting: Floor

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-DX-3P-480D-27KVA-400Y.230-N3R 480V Delta 3 Phase Energy Efficient Drive Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DX-3P-480D-27KVA-400Y.230-N3R provides increased reliablity and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 27 KVA, the MT-DX-3P-480D-27KVA-400Y.230-N3R drive isolation transformer is a three phase unit with a primary voltage of 480V Delta. It also provides a secondary voltage of 400Y/230 Wye-N. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 220°C insulation with a 150°C temperature rise.

Benefits: The MT-DX-3P-480D-27KVA-400Y.230-N3R general purpose transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This drive isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-DX-3P-480D-27KVA-400Y.230-N3R

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-DX-3P-480D-27KVA-400Y.230-N3R

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-DX-3P-480D-27KVA-400Y.230-N3R

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-DX-3P-480D-27KVA-400Y.230-N3R

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/337662.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/337662.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/337662.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/337662.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/337662.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)