Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3

9 kVA 3PH DOE Transformer, 480V Delta Primary, 208Y/120 Wye-N Secondary, NEMA 1, Ventilated, 60 Hz - Copper Winding - 115 DegC Temp - K Factor 9

Product ID: 337771

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3 DOE Efficiency Isolation Transformer

Transformer Type: Isolation Transformer
Transformer Configuration: Dry Type
Phase: Three Phase
Frequency: 60 Hz
Primary Voltage: 480V AC
Primary Connection: Delta
Capacity: 9 KVA
Secondary Voltage: 208Y/120V AC
Secondary Connection: Wye-Neutral
Knockouts: -
FCAN (Above) Taps: 2
FCAN (Below) Taps: 4
Tap %: 2.5
Impedance: 2.5-6.5% typical

Efficiency: Exceeds DOE 2016 minimum efficiency by 25–50% in loss reduction.

Harmonic Mitigation (K-Factor Rating): K-9

Winding Material: Copper

Approvals/Features

NRTL listed for United States
NRTL listed for Canada
NEMA 1 Indoor Steel Enclosure
Meets or Exceeds NEMA ST-20 Standards
Seismic Qualified for Earthquake Loads
Distribution Type Transformer
Built to UL-50 Standards
CE Certified
RoHS
32-year pro rated warranty
Service life beyond 30 years
ISO 17025 Certified
ISO 14001 Certified
UL Listed
Lockable hinged doors and 360 degree Rotatable IR Ports to reduce arc flash risk
Integrated metering (capacity utilization, load profiles, power quality, energy use)
Thermal sensors (170°C and 200°C alarm points)

Primary Termination (Std): Terminal Lugs
Secondary Termination (Std): Terminal Lugs
Mounting: Wall
Cooling: Air/Dry
Insulation: 220°C
Temperature Rise: 115°C
Sound Level: Meets NEMA ST-20 Standards
Seismic Bracing: 2.28g
Feeder Entry Point: Bottom Back Mid
Secondary Entry Point: Bottom Back Mid
Enclosure Material: NEMA Type 1 Heavy Duty Ventilated - Steel
Finish: ANSI 61 Grey
Dimensions: 19.37"L x 24.39"W x 25.5"H
Weight: 290 lbs
Shipping Method: Pallet Freight - LTL
Shipping Weight: 355 lbs
Shipping Dimensions: 48"L x 40"W x 290"H

Very Low Inrush (VLI) option
Surge protection device (SPD) integration
Nonlinear Load Test with Certificate (NLT)

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3 Three Phase 480V to 208Y/120 9 KVA DOE Efficiency Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3 provides increased reliability and protection against critical equipment failures. This 9 KVA isolation is designed for distribution loads and potential seismic activity. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: The MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3 DOE Efficiency transformer is a three phase transformer with a 9 KVA capacity rating. This isolation transformer is configured with an input voltage of 480V Delta 3-Phase AC on the primary side and an output voltage of 208Y/120 Wye-Neutral 3-Phase AC on the secondary side. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The standard NEMA Type 1 enclosure makes the unit suitable for indoor applications and is designed to be wall mounted. Wall mount brackets or additional mounting accessories can be purchased separately. This 9 KVA distribution transformer features 220°C insulation with a 115°C temperature rise.

Benefits: The MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3 480V to 208Y/120 general purpose transformer offers many benefits to the consumer. Precision cut copper transformer winding material helps to improve performance. The close tolerances used during manufacturing also eliminate burrs, which hinder performance. Each core is specially coated to prevent the ingress of moisture and is electrically balanced to minimize axial forces during short circuit situations.

This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

The MT-DOE series of transformers from Larson Electronics meets or exceeds efficiency standards for United States and Canada. This results is overall lower cost of ownership throughout the life of the transformer.

Safety: The MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3 is an isolation transformer which means that it provides operators with an increased level of protection against electric shock and injury. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3 achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: Converting 480V local grid power to 208Y/120 for on-site equipment. This 9 KVA power transformer is ideal for sensitive equipment such as CNC equipment, computers, medical devices, ovens, or laboratory instruments.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-DOE16-3P-480D-9KVA-208Y.120-N1-CU-K9-M3

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/337771.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/337771.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/337771.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/337771.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/337771.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)