Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-GOAB-NFDS-3P-3W-15KV-3000A-EF-BM-HM-N1-M1

Non-Fused Gang Operated Air Break Switch, 3000 Amp, 15.5 kV, 3-Pole, Horizontally Mounted, Indoor Enclosed, Left-Side Operated, NEMA 1, 95kV BIL

Product ID: 337867

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-GOAB-NFDS-3P-3W-15KV-3000A-EF-BM-HM-N1-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-GOAB-NFDS-3P-3W-15KV-3000A-EF-BM-HM-N1-M1 Gang Operated Air Break Switch, Non-Fused Disconnect

Unit Type: Non-Fused Gang Operated Air Break Switch
Line-In: N/A (customer provided)
Line-In Cord Cap: N/A (customer provided)
Line-In Connections: IEEE / NEMA 4-Hole & 6-Hole Compatible Terminal Pads
Line-In Orientation: Horizontal Mount
Nominal Voltage: 15 kV Class
Rated Voltage: 15.5 kV
BIL: 95 kV
Current: 3000 Amps Continuous
Peak Momentary Rating: 130 kA
Short-Time Withstand: 50 kA for 3 Seconds
No. of Poles: (3)
Wires: (3)
Protection Method: N/A
Protection Type:
Protection Fuses:
Protection Ampacity: -
Mains Rating (Amps): 3000A

Ratings

NRTL Listed Service Equipment
NRTL Listed to UL 891 Dead Front Switch Boards
NEMA 3R Rated for Indoor and Outdoor Use
Made in the USA

Interrupting Rating: N/A
Disconnect Means: Manual Gang Operation
Line-Out: N/A (customer provided)
Line-Out Cord Cap: N/A (customer provided)
Line-Out Connection: IEEE / NEMA 4-Hole & 6-Hole Compatible Terminal Pads
Line-Out Orientation: Horizontal Mount
Form Factor: Indoor Enclosed Steel Assembly
Terminal Pads: Silver Plated
Current Carrying Parts: Copper
Switch Base: Galvanized Steel
Hinges: Stainless Steel
Break Type: Visible Air Break Disconnect
Minimum Open Gap: 4.5 Inches
Insulators: A30-6 Station Post Insulators
Interphase Barriers: GPO-3 Arc Barriers
Ground Clearance: Minimum 6 Inches Energized Parts to Ground
Ground Studs: 1 Inch Diameter
Door: Handle with 3-Point Latch
Enclosure Top Cover: Red GPO-3
Enclosure Bottom Cover: Aluminum
Enclosure Material: Galvanized Structural Steel
Enclosure Finish: ANSI 70 Gray Smooth Powder Coat (Exterior), White Smooth Powder Coat (Interior)
Enclosure Type: NEMA 1 Indoor Rated
Mounting: Horizontally Mounted
Linear Travel: 7 Inches
Radius Arm: 3.75 Inches
Dimensions: 42"-W x 30"-D x 78"-H Enclosure
Assembly Weight: Approx. 1,100 lbs
Pole Weight: Approx. 72 lbs per Pole
Shipping Dimensions: TBD
Shipping Weight: TBD

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The Larson Electronics MPD-GOAB-NFDS-3P-3W-15KV-3000A-EF-BM-HM-N1-M1 Gang Operated Air Break (GOAB) Switch provides operators with a reliable and visible means of isolating medium-voltage feeders and electrical equipment in industrial facilities, substations, switchgear lineups, and power distribution systems. This non-fused indoor disconnect switch features a visible air break design that provides safe circuit isolation during maintenance and servicing operations. The horizontally mounted assembly is housed within a rugged NEMA 1 indoor enclosure and utilizes silver-plated copper contacts for dependable long-term performance.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

The MPD-GOAB-NFDS-3P-3W-15KV-3000A-EF-BM-HM-N1-M1 indoor GOAB switch is

designed for 15.5 kV class systems and provides a continuous current rating of 3000 amps. The switch assembly offers a 95 kV BIL rating, 130 kA peak momentary withstand rating, and 50 kA short-time withstand rating for 3 seconds. This manually operated switch utilizes a customer-supplied gang-operated mechanism with left-side operator configuration for positive open and close control. The visible air gap allows operators to visually verify isolation status for enhanced safety.

Operation: The enclosed GOAB switch features a handle-operated disconnect mechanism using customer-supplied linkage and operating hardware. The switch assembly includes stainless steel hinges, silver-plated terminal pads, and copper current-carrying components for reliable operation under demanding industrial conditions. A visible open-gap configuration provides confirmation that the circuit has been disconnected prior to maintenance activities.

Enclosure Design: The GOAB switch is housed within a heavy-duty 11-gauge steel indoor enclosure with ANSI 70 gray powder-coated exterior finish and white powder-coated interior finish. The enclosure includes a 3-point latch handle, red GPO-3 top cover, aluminum bottom cover, and GPO-3 interphase arc barriers for enhanced insulation and phase separation. IEEE/NEMA 4-hole and 6-hole compatible terminal pads are provided for flexible conductor termination options.

Construction: This medium-voltage disconnect switch features silver-plated contacts, silver-plated terminal pads, galvanized steel switch base construction, stainless steel hinges, and all copper current-carrying parts. The assembly utilizes A30-6 station post insulators rated for 95 kV BIL performance and includes 1-inch diameter ground studs. The switch complies with IEEE C37.30.1-2022 standards for medium-voltage switch applications.

Certification: This GOAB switch is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.

Mount: Operators can horizontally mount the indoor enclosed GOAB switch within electrical rooms, substations, switchgear lineups, and industrial power distribution systems.

Customization: The MPD-GOAB-NFDS-3P-3W-15KV-3000A-EF-BM-HM-N1-M1 can be customized to meet specific operating and power requirements. Example of customizations include:

• Modified enclosure dimensions and configurations

• Custom operating mechanisms and linkage arrangements

• Alternate insulator ratings and BIL configurations

• Additional grounding provisions

• Specialized terminal pad configurations

Applications: This gang operated air break switch is suitable for indoor medium-voltage isolation applications including industrial plants, substations, utility distribution systems, manufacturing facilities, power generation sites, maintenance disconnect systems, and electrical infrastructure upgrades.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-GOAB-NFDS-3P-3W-15KV-3000A-EF-BM-HM-N1-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-GOAB-NFDS-3P-3W-15KV-3000A-EF-BM-HM-N1-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-GOAB-NFDS-3P-3W-15KV-3000A-EF-BM-HM-N1-M1



Image: MPD-GOAB-NFDS-3P-3W-15KV-3000A-EF-BM-HM-N1-M1

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1** (https://www.larsonelectronics.com/images/product/HigResPic1/337867.JPG)
- **HigResPic2** (https://www.larsonelectronics.com/images/product/HigResPic2/337867.JPG)
- **HigResPic3** (https://www.larsonelectronics.com/images/product/HigResPic3/337867.JPG)
- **HigResPic4** (https://www.larsonelectronics.com/images/product/HigResPic4/337867.JPG)
- **HigResPic5** (https://www.larsonelectronics.com/images/product/HigResPic5/337867.JPG)
- **HigResPic6** (https://www.larsonelectronics.com/images/product/HigResPic6/337867.JPG)
- **HigResPic7** (https://www.larsonelectronics.com/images/product/HigResPic7/337867.JPG)
- **HigResPic8** (https://www.larsonelectronics.com/images/product/HigResPic8/337867.JPG)
- **HigResPic9** (https://www.larsonelectronics.com/images/product/HigResPic9/337867.JPG)
- **ISO 9001 Certification** (http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate** (https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map** (https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)