Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 338584

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image:

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-SPI-161KV-750KV-62IN-M2 Station Post Insulator
Unit Type: Station Post Insulator, Porcelain Type, Uniform Stack, Underhung
System Voltage: 161 kV
Low Frequency Withstand Voltage, Wet, 10 sec.: 315 kV
Low Frequency Withstand Voltage, Dry: 485 kV
BIL Voltage: 750 kV
Min. Arcing Distance: 52 inches
Min. Creepage Distance: 132 inches
Total Length: 62 ± 0.03 inches
Number of Sections: (1)
Cantilever Strength: 1850 lbs
Tension Strength: 25000 lbs
Torsion Strength: 90000 in-lbs
Compression Strength: 75000 lbs
Housing Material: Porcelain
Fitting Material: Galvanized Steel
Top Bolt Circle: 5.0 inches
Bottom Bolt Circle: 5.0 inches
Top (Tap + 0.015): 5/8-11
Top (Min. Thread): 0.71
Bottom (Tap + 0.015): 5/8-11
Bottom (Min. Thread): 0.63
Color: ANSI 70 Grey

Ratings
Complies with ANSI C29.9
Compliant with Coastal Environment

Special Orders - Special Requirements
Contact us for special requirements

Mount: Underhung (Inverted)

Weight: -

Shipping Dimensions: 13.78" x 13.78" x 51.18"

Shipping Weight: 190 lbs

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The robust range of station post insulators is designed to support and stabilize power station infrastructure. Our station post insulators are engineered for superior durability and reliability, ensuring optimal performance under various operational conditions. Ideal for enhancing the efficiency and safety of power grids, the MT-SPI-161KV-750KV-62IN-M2 station post insulator meets the highest standards of quality.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

The MT-SPI-161KV-750KV-62IN-M2 Station Post Insulator, Porcelain type, is compatible with 161 kV rated voltage systems. It's Basic Insulation Level is 750 kV with total length 62 inches

Mount: Operators can mount the SPI underhungly.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 338584

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com//images/product/HigResPic1/338584.JPG)
- **Video1**(https://www.youtube.com/watch?v=aOJY5E9e33I)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)