Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

C-MTW-20-STR-GRN.YLW

1' 20 AWG Single Conductor Machine Tool Wire (MTW) - PVC Insulated - Stranded - Green/Yellow

Product ID: 339642

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: C-MTW-20-STR-GRN.YLW

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

20 AWG Single Conductor Machine Tool Wire (MTW) - PVC Insulated - Stranded - Green/Yellow

The C-MTW-20-STR-GRN.YLW is a high-quality Machine Tool Wire (MTW) designed for use in industrial machinery, control panels, electrical equipment, and internal wiring applications. MTW wire is manufactured to provide excellent flexibility, durability, and reliable performance in demanding industrial environments. It comes with the following characteristics:

Conductors: 20 AWG stranded copper conductor
Wire Material: Copper
Jacket: Durable Polyvinyl Chloride (PVC) insulation
Color: Green/Yellow (Grounding)

The flexible stranded copper conductor allows for easy routing and

installation in control cabinets, machine tools, and other electrical equipment. The durable PVC insulation provides resistance to abrasion, moisture, oil, grease, and many industrial chemicals, ensuring long service life and dependable performance.

Ratings

- UL Listed
-
- Machine Tool Wire (MTW) Rated
- Approved for up to 600V
- Rated for 90°C in dry locations
- THHN/THWN-2 dual rated for use in both dry and wet applications
- Suitable for use in industrial control panels, machine tools, and electrical equipment
- Flexible stranded construction for easy installation and wiring in confined spaces

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

C-MTW-20-STR-GRN.YLW

Product ID: 339642

Export Control Classification Number (ECCN): EAR99

Options:

C-MTW-20-STR-GRN.YLW-Color
Example: C-MTW-20-STR-GRN.YLW-BLK

Color	
BLACK	-BLK
WHITE	-WHT
RED	-RED
BLUE	-BLU
GREEN	-GRN
YELLOW	-YLW
ORANGE	-ORN
BROWN	-BRN

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/339642.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)