Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

## DCP-48A-125VDC-DP-WP

# 6 KW 1-Ph AC to DC Rectifier - 120V AC Input, 125V DC Output - 60 Hz

**Product ID: 339665**

**Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



Image: DCP-48A-125VDC-DP-WP

**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**DCP-48A-120VDC-DP-WP AC to DC Rectifier**

**Unit Type:** AC to DC Rectifier, Weatherproof
**Dimensions:** 130 × 450 × 600 mm
**Front Panel Dimensions:** 132 × 483 mm (19″ – 3U)
**Weight:** TBD
**Input Voltage:** 120V AC 1Ph (±5%), 60 Hz
**Output Voltage:** 125V DC Nominal
**Output Current:** 48 A
**Capacity Rating:** 6.25 KW
**Startup Time:** 400 mS
**Efficiency Factor:** 0.95
**Power Factor:** 0.95
**Polarity:** Output is Floating and Can Used on Either Polarity
**Drift:** +/- 0.1% Over 8 Hours, After 30-minute Warm Up
**Temperature Coefficient:** +/- 0.02%/C
**Holdup Time:** 33 ms minimum
**Transient Response:** 300 µS to Return to ±1% of Output Setting. Maximum of ±3% Output Excursion Following a Load Step Change from 50% to 100%
**Remote Sensing:** Compensates up to 0.5V drop per Output Line
**Protection:** Overload, Over Voltage, Output Inhibit, Thermal Protection
**Efficiency:** 95%

**Ratings**

EN 60950
EN 61010
EN 61326-1

**Ripple/Noise:** 170 mV RMS
**Battery Type:** Lead-acid (PB) / 60 cells
**Switching Frequency:** 55 kHz
**Cooling:** Natural Ventilation
**Operating Ambient Temperature:** -20°C to +50°C
**Mechanical Protection:** IP20
**Cable Entry:** Bottom
**Materials:** Metal
**Mount:** Surface Mount Feet
**Wiring:** Terminals

**Special Orders - Special Requirements**
Contact us for special requirements
**Toll Free:** 1-800-369-6671

**Intl:** 1-903-270-1187
**Fax:** 1-903-765-7664
**E-mail:** sales@larsonelectronics.com

**The Larson Electronics DCP-48A-125VDC-DP-WP AC to DC Rectifier provides accurate voltage control and power management features for industrial operations. This unit is compatible with single-phase 120V AC @ 60 Hz input and provides 125V DC output. Equipped with protective functions, the device features remote sensing and surface mount feet at the bottom of the enclosure.**

The DCP-48A-125VDC-DP-WP is a compact AC to DC rectifier for industrial facilities. The universal input voltage unit accepts 120V AC @ 60 Hz power and offers 125V DC output. The device operates at 80% efficiency. Protective features include overload, overvoltage, output inhibit and thermal protection.

This enclosed unit is constructed of metal and features forced air cooling. Operators can access terminals for power connections.

**Mounting:** The power converter is equipped with surface mount feet at the bottom of the unit.

**Applications:** Industrial sites, factory control, automation, laser machines, manufacturing, voltage control, power management, digital broadcasting, RF applications, computerized systems and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

# Frequently Asked Questions (FAQ)

There are no Faqs

**Export Control Classification Number (ECCN):** EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Links (Click on the below items to view):

- **HigResPic1**( https://www.larsonelectronics.com/images/product/HigResPic1/339665.JPG )
- **Video1**( https://www.youtube.com/watch?v=1ZUP0hZxQIk )
- **ISO 9001 Certification**( http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF )
- **Business Certificate**( https://www.larsonelectronics.com/images/pdfdocs/w9.PDF )
- **Shipping Time Map**( https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf )