Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HID-BL-57-Flood

HID-BL-57-Flood HID Boat Light - 3200 Lumen - 250' Beam Projection - White

Product ID: 341

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

High Intensity Discharge Equipment Light - cast aluminum housing - 5X7 inch lens - powder coated white - flood pattern with 250`X250` foot flood beam pattern - internal ballast runs on 12 Volts DC and 24 Volts DC - stainless steel stud mounting hardware.

Click Photo to Enlarge **Click Photo to Enlarge** **Click Photo to Enlarge**

Specifications:

* Ballast & Igniter incorporated into lamp housing for easy installation
* 35W Xenon D2S bulb
* Over 50% less energy consumption compared to conventional lighting
* Heavy duty cast aluminum construction with durable, UV and saltwater resistant, white powder coat finish
* Uses common 12VDC or 24VDC power (ballast runs on 9 to 30 volts DC) - All models automatically sense 12 volts or 24 volts, so you do not need a specific 12V or 24V model.
* Average current draw @12VDC: Start: 12.2amp, Run: 3.3amp (in under 60 sec) - Average current draw @24VDC: Start 6.1 amp, Run: 1.7 amp (in under 60 sec)
* Components, coatings and construction selected for marine applications
* Swivel bracket design
* UV and salt water resistant design - cast aluminum housing and stainless steel

mounting hardware powder coated white
* Weight: 4lb 4oz
* Comes complete with 1 light, internal ballast, internal ignitor, Deutsch socket, Deutsch plug with 12 inch pig tail

* Flood pattern (Approximate pattern 250`L x 250`W

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









HID-BL-57-Flood

Product ID: 341

Harmonized System (HS) Code: 8512.20.2080
Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**