Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

CGB-LQT-N-90-0.5

Liquid Tight Connector - 90 Degrees, Non-insulated - Steel - (2) 1/2" NPT Hubs

Product ID: 341974

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: CGB-LQT-N-90-0.5

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

CGB-LQT-N-90-0.5 Industrial Connector

Device Type: Liquid Tight Connector

Dimensions: 1-19/32” x 1-15/16”
Weight: 0.37 lbs
Type: Non-insulated
Bend: 90 Degrees
Material: Steel
Finish: Zinc Plated
Gland Type: Split Nylon Ring
Hubs: (2) 1/2" NPT

Ratings
Suitable for Use in Hazardous Location Applications When Installed According to NEC

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The Larson Electronics CGB-LQT-N-90-0.5 is a Liquid Tight Connector for sealing out water, oil and dust in rugged work sites. The non-insulated unit features a 90-degree bend. Constructed of steel, the connector contains two, 1/2" NPT hubs.

The CGB-LQT-N-90-0.5 is designed to seal out contaminants, such as water, oil and dust in industrial facilities. This unit is non-insulated and contains a 90-degree bend. The connector is constructed of steel with a zinc-plated finish. Split nylon gland ring enables seamless installation and sealing. The unit features two, 1/2" NPT hubs.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/341974.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)