Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HID-BL-6R-Spot

HID-BL-6R-Spot HID Boat Light - 35 Watt HID - 3200 Lumen - 2700' Spot Beam - White Housing

Product ID: 342

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

High Intensity Discharge (HID) BoatLight - Cast Aluminum Housing - 6 inch round lens - Powder Coated White Finish - Spot pattern with 2700 foot spot beam projection - internal ballast runs on 12 Volts DC and 24 Volts DC - stainless steel stud mounting hardware
Specifications:
* Ballast & Igniter incorporated into lamp housing for easy installation
* 35W Xenon D2S bulb
* Over 50% less energy consumption compared to conventional lighting
* Heavy duty cast aluminum construction with durable, UV and saltwater resistant, white powder coat finish
* Uses common 12VDC or 24VDC power (ballast runs on 9 to 30 volts DC) - All models automatically sense 12 volts or 24 volts, so you do not need a specific 12V or 24V model.
* Average current draw @12VDC: Start: 12.2amp, Run: 3.3amp (in under 60 sec) - Average current draw @24VDC: Start 6.1 amp, Run: 1.7 amp (in under 60 sec)
* Components, coatings and construction selected for marine applications
* Swivel bracket design
* UV and salt water resistant design - cast aluminum housing and stainless steel mounting hardware powder coated white

* Weight: 4lb 4oz
* Comes complete with 1 light, internal ballast, internal ignitor, Deutsch socket, Deutsch plug with 12 inch pig tail
* Spot pattern (Approximate pattern 2700`L x 100`W at farthest point)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HID-BL-6R-Spot

Product ID: 342

Harmonized System (HS) Code: 8512.20.2080

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Dimensional Drawing 2D**
- **Operations Manual**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**