Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPO-30A-EC-3P4W-230.115V-AL-M1

Explosion Proof Receptacle - 230/115V - 30 Amp Rated - 3 Pole 4 Wire - 60 Hz - Hub Size 3/4" - NEMA 7

Product ID: 342004

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPO-30A-EC-3P4W-230.115V-AL-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPO-30A-DA-115.230V Explosion Proof Receptacle

Unit Type: Explosion Proof Single-Gang Receptacle
Dimensions: 4.63"W x 11.13"L x 3.5"H
Weight: 3.3 lbs
Voltage: 115/230V AC
Phase: Single
Configuration: 3 Pole, 2 Wire
Type: Pin & Sleeve
Hub Pattern: Feed-thru
Amps: 30A
Horsepower: 3
Materials: Copper-free Aluminum
Housing: Straight or angle boxes
Hubs: 3/4" NPT
Color: Natural Gray

Features/Ratings

Class I, Divisions 1 & 2 Groups C,D
Class I, Zones 1 & 2, IIB, IIA
NEMA 7 (C,D)
Factory Sealed Receptacle
Delayed Action Contacts

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPO-30A-EC-3P4W-230.115V-AL-M1 Explosion Proof Receptacle - 230/115V 30 Amp Rated - 3 Pole 4 Wire Ground Configuration

Voltage: 230/115V

Phase: Single Phase

Amp Rating: 30A

Horsepower Rating: 3HP

3-Pole 4-Wire Pin/Sleeve configuration

Delayed reaction twist lock design

Wet Location Approved

Aluminum, Copper Free Construction

Factory Sealed

Class I Division 1, Groups C & D

Class I, Zones 1 & 2, IIB, IIA

NEMA 7

Click Photo to Enlarge

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPO-30A-EC-3P4W-230.115V-AL-M1



Image: EPO-30A-EC-3P4W-230.115V-AL-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPO-30A-EC-3P4W-230.115V-AL-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPO-30A-EC-3P4W-230.115V-AL-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPO-30A-EC-3P4W-230.115V-AL-M1

Product ID: 342004

Export Control Classification Number (ECCN): EAR99

Options:

EPO-30A-EC-3P4W-230.115V-AL-M1-Termination-Hub Config
Example: EPO-30A-EC-3P4W-230.115V-AL-M1-DE-0.5IN

Termination	
DEAD END	-DE
FEED THRU	-FT

Hub Config	
1/2 NPT	-0.5IN
3/4 NPT	-0.75IN
1NPT	-1IN

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Links (Click on the below items to view):

- **HigResPic1** (https://www.larsonelectronics.com/images/product/HigResPic1/342004.JPG)
- **HigResPic2** (https://www.larsonelectronics.com/images/product/HigResPic2/342004.JPG)
- **HigResPic3** (https://www.larsonelectronics.com/images/product/HigResPic3/342004.JPG)
- **HigResPic4** (https://www.larsonelectronics.com/images/product/HigResPic4/342004.JPG)
- **HigResPic5** (https://www.larsonelectronics.com/images/product/HigResPic5/342004.JPG)
- **HigResPic6** (https://www.larsonelectronics.com/images/product/HigResPic6/342004.JPG)
- **HigResPic7** (https://www.larsonelectronics.com/images/product/HigResPic7/342004.JPG)
- **HigResPic8** (https://www.larsonelectronics.com/images/product/HigResPic8/342004.JPG)
- **HigResPic9** (https://www.larsonelectronics.com/images/product/HigResPic9/342004.JPG)
- **ISO 9001 Certification** (http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate** (https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map** (https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)