Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-HAL-WM-3P-480D-30KVA-208Y.120-N3R-CU

30 kVA Hazardous Location Transformer - 480V Delta Primary - 208Y/120 Wye-N Secondary - C1D2 - Wall-mounted

Product ID: 346018

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MT-HAL-WM-3P-480D-30KVA-208Y.120-N3R-CU

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-HAL-WM-3P-480D-30KVA-208Y.120-N3R-CU Isolation Transformer

Phase: Three Phase
Frequency: 60 Hz
kVA: 30
Primary Voltage: 480 V Delta
Primary Connection: Delta
Primary FCAN: 2 x 2.5%
Primary FCBN: 4 x 2.5%
Secondary Voltage: 208Y/120 V Wye-N
Secondary Connection: Wye-N
Winding Material: Copper
Efficiency: No Efficiency Specification
Insulation: 180°C
Temperature Rise: 115°C
Secondary Phase Angle: 30°C
Ambient Temperature Rating: 40°C
Temperature Class: T3A
Impedance (Std): -
Seismic Zone: Zone 4
Sound Level: 55 dBA (ST-20)
Primary Termination: Mounting Pads
Secondary Termination: Mounting Pads

Ratings

NRTL Listed for United States and Canada
Class I Division 2 Groups A, B, C, & D
Class I, Zone 2, Group IIC, T3
ANC Cooling
IP14 Rated
Isolation Transformer

Enclosure Material: NEMA Type 3R Heavy Duty Ventilated
Finish: ANSI 61 Grey Finish
Dimensions: 27.56" x 23.62" x 31.50"
Weight: 661.39 lbs
Mounting: Wall Mount

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-HAL-WM-3P-480D-30KVA-208Y.120-N3R-CU 480 V Delta 3 Phase Energy Efficient Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-HAL-WM-3P-480D-30KVA-208Y.120-N3R-CU provides increased reliablity and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses. The MT-HAL-WM-3P-480D-30KVA-208Y.120-N3R-CU transformer is rated for use in Class I Division 2 Groups A, B, C, and D hazardous areas.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 30 KVA, the MT-HAL-WM-3P-480D-30KVA-208Y.120-N3R-CU isolation transformer is a three phase unit with a primary voltage of 480 V Delta. It also provides a secondary voltage of 208Y/120 V Wye-N. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be wall mounted. The unit also features 180°C insulation with a 115°C temperature rise and is rated IP14.

Benefits: The MT-HAL-WM-3P-480D-30KVA-208Y.120-N3R-CU isolation transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated wall mounting brackets make installation fast and easy and the offset outward facing wall installation holes allow for easy power tool access.

Safety: The MT-HAL-WM-3P-480D-30KVA-208Y.120-N3R-CU is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-HAL-WM-3P-480D-30KVA-208Y.120-N3R-CU achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes in Class I Division 2 Groups A, B, C, & D hazardous

locations.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/346018.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)