

C-16-TP7

C-16-TP7 - 7 Prong Trailer Plug with 16 foot with 2 pin Connector

Product ID: 435

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

C-16-TP7

Stranding: 26/30

Insulation Wall: 0.030"

OD: 0.390"

Weight: 3.5 lbs

Max Amps: 13

Female Connector: Deutsch DT06-2S or 2-pin SAE connector

Male Connector: 7-Pin Trailer Connector w/ spring strain relief

Ambient Temp Rating: -40°C to +90°C

Ratings/Approvals

UL Listed SOOW 600V to NEC Article 400

CSA certified

MSHA approved for flame resistance in mining applications

ROHS Compliant

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

16 foot cord with 7 prong trailer plug. The cord is terminated with a 2 pin SAE or Deutsch connector that can be attached to any Larson Electronics magnetic light, Golight remote control spotlight and several direct connect and rechargeable HID lights. This cord is offered with either round pins (for commercial / agriculture) or flat pins (RVs and trucks). Most vehicles require 7-pin round plug with flat connectors.

Features:

Manufactured with advanced synthetic rubber compounds

Exceptional flexibility

Excellent resistance to flame, deformation, ozone, oils, acids and chemicals

Oil resistant insulation and jacket
Abrasion resistant
Flexible in cold temperatures

Frequently Asked Questions (FAQ)









C-16-TP7

Product ID: 435

Export Control Classification Number (ECCN): EAR99

Options:

C-16-TP7-Prong Type-Connector

Example: C-16-TP7-Flat-SAE

Prong Type	
FLAT	-Flat
ROUND	-Round

Connector	
SAE	-SAE
DEUTSCH	-DEU

Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)