Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

**LE-6020-F**

# LED Diffused Flood Light - 12-24V DC, 5000 Lumens - (1) Hardwired Remote w/ 20' Wiring Harness - Permanent Mount - White Housing

**Product ID: 45283**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**LE-6020-F LED Diffused Flood Light w/ Hardwired Remote**
**Lamp Technology: LED**
**Light Dimensions:** 5.9" x 7.1" x 7.5"
**Base Dimensions:** 6.06" x 6.06"
**Remote Qty:** (1)
**Weight:** 4.2 lb
**Voltage: 12 V DC or 24 V DC**
**Total Watts:** 50W
**Lumens:** 5,000
**Candela:** 550,000
**Beam Distance:** 4,915 Feet
**Luminous Efficacy:** 100 Lm/W
**LED Life Expectancy:** 50,000+ hours
**LED Light Color:** White
**Correlated Color Temperature:** 5,700-6,000K
**Beam Angle:** -
**Lighting Configuration:** Flood
**Light Head Rotation:** 360° - Continuous
**Elevation Angle:** 135°
**Rotation Speed:** 19° per Second (Fast), 19° per Second (Slow)
**Elevation Speed:** 11° per Second
**Wired Dash Mount Remote Type:** Joystick w/ 32' Cable
**Remote Controls:** On/Off, Up, Down, Left, Right, Speed Control
**Amps:** 4 A @ 12 V DC, 2 A @ 24 V DC
**Ambient Operating Temp Range:** -30°C to +70°C

**Ratings/Approvals**
IP68 Rated LED Module
IP56 Rated Housing
FCC Approved
Auto-Home Return

**Special Orders - Special Requirements**

**Housing Material:** Acrylonitrile Styrene Acrylate (ASA)
**Lens Material:** Hardened Polycarbonate
**Mount:** Permanent Mount - 4.92" x 4.92" Distance Between (4) Mounting Holes
**Wiring:** 20' Wiring Harness Between Light & Remote Control
**Housing Color:** White

Contact us for special requirements
**Toll Free: 1-800-369-6671**
**Intl: 1-903-270-1187**
**Fax: 1-903-498-3364**
**E-mail:** sales@larsonelectronics.com

**The LE-6020-F from Larson Electronics is a LED Diffused Flood Light that provides diffused light output in a flood pattern for outdoor locations and is recommended for area lighting, general illumination, landscape lighting, accent lighting, security lighting, and more. This LED light operates on 12 V or 24 V DC and provides 5000 Lumens of output during use. Equipped with a hardwired remote and 20' wiring harness, the LED light with white housing is compatible with permanent mounting installations.**

The LE-6020-F is a powerful lighting solution for outdoor areas, rugged environments, and remote locations. A total of ten, 5-watt LEDs provide an 8° spot light beam that can reach distances up to 4,915 feet. The low voltage LED search light generates 5000 Lumens of output. During use, this unit rotates at a rate of 19° per second in fast mode and 12° per second in slow mode, as well as elevates at a rate of 11° per second. The LED module carries an IP68 rating and the housing is IP56 rated. Equipped with an acrylonitrile styrene acrylate (ASA) housing, the lens is made out of hardened polycarbonate.

**Remote Control(s):** This unit comes with one hardwired remote control. The remote allows operators to turn the spotlight on and off and toggle the movement speed between slow and fast. Joystick controls allow for up, down, left, and right movement. The dash mount remote comes with a 20' cable.

**LED Benefits:** Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

**Voltage:** The LED diffused flood light operates on 12 V DC or 24 V DC.

**Mount:** This unit is compatible with permanent mounting installations via four mounting holes. There is a distance of 4.92" x 4.92" between the mounting holes.

**Applications:** Outdoor lighting, area lighting, general illumination, landscape lighting, accent lighting, security lighting, and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

# Frequently Asked Questions (FAQ)

**LE-6020-F**

**Product ID: 45283**

**Warranty:** 36 Months

**Export Control Classification Number (ECCN):** EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**