Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDSM-3X60-F

3 LED Spreader Lights in billet aluminum housing (flat)

Product ID: 46365

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LEDSM-3X60-F LED Spreader Light
Lamp Type: LED
Dimensions: 5.25" Length 2" Width .875" Depth
Amps: .2 on 12 volts
Voltage: 12 VDC Only
Mounting: Flat Surface Mount
Wiring: 2 Wires Each LED Hot and Ground
Lumens: 675
LED Life Expectancy: 50,000 hours
Materials: Billet Aluminum
Beam Size: 10`L x 10`W

Features
Compact Size
Flat surface mounting
Billet aluminum housing
Low .2 amp draw
High output

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Buy American Compliant

The LEDSM-3X60-F LED spreader light is designed as an extremely efficient and versatile lighting solution for boat walkways, cabin areas, stairs, vehicles and anywhere a compact and efficient lighting solution is needed. This LED strip light is designed for flat mounting surfaces and produces 675 lumens of bright pure light while using only .2 amps of power.

This high intensity LED spreader light consists of three LED potted and housed within a billet aluminum fixture that features a very small profile for easy and unobtrusive mounting in tight and space limited areas. These lights feature a thin

profile that makes them ideal for replacing older bulky incandescent or fluorescent fixtures. This LED spreader light is designed to mount to flat surfaces and each LED is independently wired to allow each LED to be operated on its own switch or circuit if desired.

Measuring only 5.25" long and 2” wide, these compact units are ideal for installation along railings, under cabinets, along stairs and wherever a powerful and compact light is needed. The 675 lumen output of these lights combined with low .2amp power consumption makes these units ideal for replacing older and less efficient fluorescent lights. These can be operated together or independently by either wiring all the LEDs into the same circuit or each one to its own circuit. Each LED has ane ground wire and one hot wire the fixture is predrilled with a through hole on each end for mounting. This LED light is designed to operate with 12 volt DC current and is equipped with a three foot pigtail for easy wiring installation. This LED spreader light runs cool to the touch, will illuminate an area approximately 10` x 10`, and has an operational life of 50,000 hours. The housing is available in either black anodize or clear anodize. Please choose your preference from the drop down menu below.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDSM-3X60-F

Product ID: 46365

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

LEDSM-3X60-F-Color-LED Color

Example: LEDSM-3X60-F-ALU-Wht

Color	
ALUMINUM	-ALU
BLACK	-BLK

LED Color	
WHITE	-Wht
BLUE	-Blu
GREEN	-Grn
RED	-Red
AMBER	-Amb

Links (Click on the below items to view):

- **Dimensional Drawing 2D**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**