Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LED10W-4RT

40 Watt LED Light - 3600 Lumen - 9-48VDC - Adjustable Surface Mount - 390'L X 90'W Spot Beam

Product ID: 46767

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LED10W-4RT LED Light Bar
LEDs: Seoul Z-Power 10 Watt LEDs
Dimensions: 8.75"-L 2.75"-H 2.5"-D
Watts: 40
Voltage: 9-48 VDC
Spot Beam: 390`L x 90`W
Weight: 3.4 Lbs
Lighting Configuration: 10° Spot or 35° Flood
Mounting: Adjustable Hinge Type Bracket
Wiring: 2 pin Deutsch plug
Amps: 3.3 (on 12 volts) 1.7 (on 24 volts)
Lumens: 3,600
LED Light Color: 6300K
LED Life Expectancy: 50,000 hours
Optics Efficiency: 80%
Materials: Aluminum Housing, Polycarbonate Lens
Housing Colors: Black or White
Lux At The Lens: 193,700
Lux At 1 Meter: 3,120
CRI: 70

LED10W-4RT LED Features
Seoul Z-Power 10 Watt LEDs
LEDs Driven At 80%
-40 C~ +80C Operating Temp Range
900 Lumens per LED
70% Lumen Retention @50,000 hours
IP67 Rated Waterproof to 1 meter
CE Certified
EN55015 EMI
EN61547 EMS
EN62471 Photobiological Safety
Download Spot and Flood Beam Specs

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Buy American Compliant

The Larson Electronics LED10W-4RT LED Light offers high light output from a light weight, durable and water tight fixture. This IP67 rated LED light bar is designed with

low profile hinge mounts that allow 180 degrees of angle adjustment and produces 3600 lumens of light while drawing only 3.3 amps on 12 volts. This light can run on any voltage from 9 to 48 volts and provides a durable and powerful lighting solution that is ideal for use in industrial and commercial applications such as machine vision system lighting, security illumination and vehicle lighting applications.

The LED10W-4RT LED light bar from Larson Electronics produces a 3,600 lumens of bright light while drawing only 40 watts @3.3amps from a 12 volt electrical system. Four Seoul Z-Power-10 watt LEDs producing a maximum of 900 lumens each are arranged in rows and paired with 10 degree optics to produce a well focused light beam approximately 390 feet in length by 90 feet wide. We also offer optional floodlight versions with 35 degree optics to produce a much wider beam with more light concentrated closer to the fixture, making these units ideal as spreader or work lights. The beam on this light in flood configurations is approximately 170` long by 130` wide and elliptical in shape. These LED light bars are IP67 rated and waterproof to 1 meter, sealed against intrusion by dust and dirt and constructed to withstand the demanding conditions found in marine environments.



LED10W-4RT unit used as headlights
Click Photo to Enlarge

Dark road with a street lamp approximately 525` away
Click Photo to Enlarge


The same road illuminated with the LED10W-4RT
Click Photo to Enlarge

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated Seoul Z-Power 10 watt LEDs. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours.
Voltage Control: These units contain an internal voltage regulator which allows them to adjust input current to provide the correct LED voltage levels regardless of input levels from 9 to 50 VDC. These LED10W series light bars can operate on current ranging from 9 to 50VDC without any modifications necessary as a result. This multi-voltage capability makes these units ideal for mobile and stand alone applications such as those found on boats and vehicles where power systems don't always operate with 12 volts and external generators, transformers or inverters are impractical.

LED10W-4RT 35° Flood Beam (Opt)



LED10W-4RT 10° Spot Beam (Stnd)



Durability: The LED10W series of LED light bars from Larson Electronics offer IP67 rated construction that is designed to withstand demanding environmental and operating conditions. These LED lights are designed for low profile mounting options, allowing them to be used in spaces where room is at a premium. They offer extruded aluminum housings, stainless steel hardware and polycarbonate lenses that provide good durability, yet are slimmer and lighter than extreme duty

LEDLB-E series lights. These units can operate in temperatures ranging from -40 degrees Celsius to 80 degrees Celsius, are waterproof to 1 meter and are sealed against the ingress of dust, dirt and humidity. The Seoul Z-Power 10 watt LEDs offer inherent LED resistance to shocks and vibrations, contributing to these unit's 8.6G rating of vibration tolerance.

Mounting: These LED light bars incorporate a hinge style mounting bracket design that provides 180 degrees of adjustability and allows the operator to attach one portion of the hinge bracket to the mounting surface first. The operator can then set the desired angle and attach the upper portion of the hinge style mount to the light. The operator then adjusts and tightens the hinge bolt to lock the light bar into position once the desired angle is set.

Note: Most Larson Electronics LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model. Some larger LED lights like the LEDLB-160X2 or LEDLB-200X2 or multiple function LED lights (i.e. high/low beam, modulating, IR/Visible combos) will have different Deutsch connectors.

On this particular unit there is a one foot pigtail attached to the LED light terminating in a 2 pin Deutsch plug. A wiring harness attaches to the Deutsch socket on the back of the LED light. The harness is terminated in a 2 pin Deutsch plug and includes 20 feet of cable, a relay and a toggle switch that will operate on 12 or 24 volts. The wiring harness is not necessary to installation. Operators can use existing wiring and switches, assuming they are rated for the amperage listed below.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LED10W-4RT

Product ID: 46767

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:

LED10W-4RT-Finish-Beam Type

Example: LED10W-4RT-BLK-SP

Finish	
BLACK	-BLK
WHITE	-WHT

Beam Type	
SPOT	-SP
FLOOD	-FL

Links (Click on the below items to view):

- **Dimensional Drawing 2D**
- **Operations Manual**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**