Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LED10W-22R

220 Watt LED Light - 19800 lumens - 9-48 Volts DC - Adjustable Surface Mount - Spot Beam

Product ID: 46792

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LED10W-22R LED Light Bar
LEDs: Seoul P7- 10 Watt LEDs
Dimensions: 40"-L 2.75"-H 2.5"-D
Watts: 220
Voltage: 9-48 VDC
Spot Beam: 1700`L x 280`W
Weight: 9 Lbs
Lighting Configuration: 10° Spot or 35° Flood
Mounting: Adjustable Hinge Style Brackett
Wiring: 2 pin Deutsch plug
Amps: 18.3 (on 12 volts) 9.2 (on 24 volts)
Lumens: 19,800
LED Light Color: 6300K
LED Life Expectancy: 50,000 hours
Optics Efficiency: 80%
Materials: Aluminum Housing, Polycarbonate Lens
Housing Colors: Black or White
Lux At The Lens: 189,600
Lux At 1 Meter: 17,700
CRI: 70

LED10W LED Features
Seoul P7- 10 Watt LEDs
LEDs Driven At 80%
-40 C~ +80C Operating Temp Range
900 Lumens per watt
70% Lumen Retention @65,000 hours
IP67 Rated Waterproof to 1 meter
CE Certified
EN55015 EMI
EN61547 EMS
EN62471 Photobiological Safety

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Buy American Compliant

The Larson Electronics LED10W-22R LED Light Bar offers high light output from a light weight/low profile, durable and water tight fixture. This IP67 rated LED light bar is designed with low profile hinge mounts that allow 270 degrees of angle adjustment and produces 19,800 lumens of LED light while drawing only 18.6 amps on 12 volts. This light can run on any voltage from 9 to 48 volts and provides a durable and powerful lighting solution ideal for use in marine environments as well as industrial and commercial applications such as machine vision system lighting, security illumination, vehicle lighting and applications where a slim form factor yet high intensity light production is required.

The LED10W-22R LED light bar from Larson Electronics produces a 19,800 lumens of bright light while drawing only 220 watts @18.4amps from a 12 volt electrical system. Twenty-two Seoul P7, 10 watt LEDs producing a maximum of 900 lumens each are arranged in rows and paired with 10 degree optics to produce a tightly focused spot beam with limited spread or light spillage. We also offer optional floodlight versions with 35 degree optics to produce a wider beam spread and more light over a larger area nearer the fixture, making flood versions ideal for use as work and area lights. These LED light bars are IP67 rated and waterproof to 1 meter, sealed against intrusion by dust and dirt and constructed to withstand the demanding conditions found in marine environments.


Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated Seoul P7 10 watt LEDs. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours.

Voltage Control: These units contain an internal voltage regulator which allows them to adjust input current to provide the correct LED voltage levels regardless of input levels from 9 to 50 VDC. These LED10W series light bars can operate on current ranging from 9 to 50VDC without any modifications necessary as a result. This multi-voltage capability makes these units ideal for mobile and standalone applications such as those found on boats, vehicles where power systems don't always operate with 12 volts and external generators, transformers or inverters are impractical.

LED10W-22R 35° Flood Beam (Opt)



LED10W-22R 10° Spot Beam (Stnd)



Durability: The LED10W series of LED light bars from Larson Electronics offer IP67 rated construction that is designed to withstand demanding environmental and operating conditions. These LED lights are designed for low profile mounting options, allowing them to be used in spaces where room is at a premium. They offer extruded aluminum housings and polycarbonate lenses that provide good durability yet are slimmer and lighter than our extreme duty LEDLB-E series lights. These units can operate in temperatures ranging from -40 degrees Celsius to 80 degrees Celsius, are waterproof to 1 meter and are sealed against the ingress of dust, dirt and humidity. The Seoul P7 10 LEDs offer inherent LED resistance to shocks and vibrations contributing to these unit's 8.6G rating of vibration tolerance.

Mounting: These LED light bars incorporate a hinge style mounting bracket design that provides 180 degrees of angle adjustment and allows the operator to attach one portion of the hinge bracket to the mounting surface first. The operator can then set the desired angle and attach the upper portion of the hinge style mount to the light. The operator then adjusts and tightens the hinge bolt to lock

the light bar into position once the desired angle is set.

Note: Most Larson Electronics LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model. Some larger LED lights like the LEDLB-160X2 or LEDLB-200X2 or multiple function LED lights (i.e. high/low beam, modulating, IR/Visible combos) will have different Deutsch connectors.

On this particular unit there is a one foot pigtail attached to the LED light terminating in a 2 pin Deutsch plug. A wiring harness attaches to the Deutsch socket on the back of the LED light. The harness is terminated in a 2 pin Deutsch plug and includes 20 feet of cable, a relay and a toggle switch that will operate on 12 or 24 volts. The wiring harness is not necessary to installation. Operators can use existing wiring and switches, assuming they are rated for the amperage listed below.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LED10W-22R

Product ID: 46792

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:

LED10W-22R-Finish-Beam Config

Example: LED10W-22R-Black-flood

Finish	
BLACK	-Black
WHITE	-White

Beam Config	
FLOOD	-flood
SPOT	-spot

Links (Click on the below items to view):

- **Dimensional Drawing 2D**
- **Operations Manual**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**