

FTL-1

High Output, LED Multi-Task Drop Light

Product ID: 46812

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

FTL-1 Cordless LED Drop Light

Lamp Type: High Output LEDs

Color: 5000K

Weight: 2 Lbs

Total Watts: 5 watts

Battery Pack: 7.2 Volt NiMH

Voltage: 120V AC 60 Hz

Cord Cap: 5-10P

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The FTL-1 Cordless LED High Output multi-task drop light is ideal for various applications where a flood beam is needed to illuminate a small area. The LED task light is not only lightweight, but durable as well. It comes complete with grappling hooks to

suspend from a location for better use of the LED beam.

The FTL-1 drop light comes standard with a 120 VAC wall charger. The battery will be fully charged in four hours. The 7.2 Volt NiMH rechargeable battery pack will operate the light for five hours on a full charge. A fuel gauge indicator light in the handle of the light blinks rapidly when the battery is charged and slows as the battery is depleted. A cut-off circuitry in the battery prevents damage from running the battery down too low.

The on and off button is located on the front of the light and controls the side and end LEDs. The LED features eight 1/2 watt high output side LEDs with a 120 degree angle to provide equivalent light pattern to a fluorescent lamp. It also has one 1 watt high output lensed end LED that provides a bright flashlight operation. The polycarbonate outer tube is virtually unbreakable.

Made in the USA Quality

1. 8) 1/2 Watt High Output LEDs
2. 1) 1 Watt High Output LED for flashlight use
3. Covered on/off Switch
4. Polycarbonate Outer Tube
5. Has a 4 hour charge time
6. 5 Hours of Operation Time
7. Low Maintenance
8. Low Profile - Light Weight

Superior LED Benefits

1. Long Lamp Life
2. High Efficiency and Low Amp Draw
3. High Durability and Reliability
4. High Output and Very Good Color Rendering
5. Instant On/Off
6. Low Maintenance

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Frequently Asked Questions (FAQ)

FTL-1

Product ID: 46812

Harmonized System (HS) Code: 9405.10.8020

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Certificate 5, Misc](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)