Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

LEDLB-20E

LED Light Emitter - 20 LEDs - 60 Watts - 750'L X 110'W Beam - Extreme Environment - 9-42VDC

Product ID: 46992

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: LEDLB-20E

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LEDLB-20E LED Light Bar

LEDs: 20 Edixeon® 3 Watt LED Emitters
Dimensions: 12"-L 3"-H 3.57"-D
Watts: 60

Voltage: 9-42 VDC

Spot Beam: 800`L x 80`W

Flood Beam: 250`L x 250`W

Weight: 6.2Lbs
Lighting Configuration: 10° Spot or 35° Flood
Mounting: Stud Bracket
Wiring: Deutsch IPD / LADD DT04-2P connector, 20ft Connecting Harness w/ Flying Leads
Amps: 5 (on 12 volts) 2.5 (on 24 volts)
Lumens: 3600
LED Light Color: 6000K or 3000K
LED Life Expectancy: 50,000 hours
Optics Efficiency: 90%

LEDLB LED Features

Edixeon® 3 Watt LED Emitters
LEDs Driven At 80%
-40 C~ +80C Operating Temp Range

RoHS Compliant

70% Lumen Retention @65,000 hours
LED Chip Op Temp -40C to +125C
IP68 Rated Waterproof to 3ft

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187

Materials: Aluminum Housing, Polycarbonate Lens
Housing Colors: Black or White
Lux-Spot : @Lens: 188,400 @ 1 Meter 24,800
Lux-Flood : @Lens: 199,800 @ 1 Meter 4,450

E-mail: sales@larsonelectronics.com

CE Certified

3 year warranty replacement on this LED light. After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, Larson Electronics will ship a new replacement.

Buy American Compliant

The Larson Electronics LEDLB-20E LED Light Bar offers high light output and extreme durability combined with versatile mounting and power options. This IP68 rated LED light bar is waterproof to three feet and produces 3,600 lumens while drawing only 60 watts of power @5 amps from a 12 volt electrical system. This light can run on any voltage from 9 to 42 volts and provides an extremely rugged lighting solution that is ideal for use in commercial marine environments as well as industrial and manufacturing applications such as machine vision system lighting, heavy equipment illumination, blasting lighting and mining operations.

The LEDLB-20E LED light bar from Larson Electronics produces an 750` long by 110` wide light beam with 3,600 lumens of bright light. In a flood configuration, this becomes an LED spreader light and covers 300` in length by 230` in width, making them ideal for use as work and area lights. Twenty Edison Edixeon® Emitters containing CREE EZBright® three watt LEDs producing 180 lumens each are arranged in rows and paired with high purity 10 degree optics to produce a tightly focused spot beam with limited spread or light spillage. These LED light bars are IP68 rated and waterproof to 3 feet, sealed against intrusion by dust and dirt and very ruggedly constructed to withstand the most demanding environments, conditions and applications. The entire Larson Electronics LEDLB-E series are constructed of extruded aluminum and feature heavier housings, rubber isolated mounts and unbreakable polycarbonate lenses to provide increased durability against vibrations, impacts, waves, hard rains, sand and high winds.

Beam and Black or White Color Options are Available Upon Purchase



Shown above, vehicle headlights only...



Shown above, car headlights supported with LED light bar

Click Photo to Enlarge

Click Photo to Enlarge

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated Edison Edixeon® Emitters. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours.

Voltage Control: These units are able to monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These LEDLB series light bars can operate on current ranging from 9 to 42VDC without any modifications necessary as a result, and includes a connecting 20ft wiring harness with flying leads. This multi-voltage capability makes these units ideal for mobile and stand alone applications such as those found on commercial boats, heavy equipment and vehicles where power systems don't always operate with 12 volts and external generators, transformers or inverters are impractical.

LEDLB-20E 35° Flood Beam (Opt)



LEDLB-20E 10° Spot Beam (Stnd)



Durability: The LEDLB-E series of LED light bars from Larson Electronics offer IP68 rated construction that is designed to withstand extremes of environmental and operating conditions. The LED lights with the 'E' part number designation are designed for extreme durability and are larger and nearly twice as heavy as their standard counterparts. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three feet and resist ingress of dust, dirt and humidity. The housings are formed from thick extruded aluminum and the lenses are unbreakable polycarbonate. The Edixeon® LEDs offer inherent LED resistance to shocks and vibrations contributing to these units 15.6Grms rating of vibration tolerance. We recommend these LED lights for high stress - high vibratory conditions, high humidity climates, very cold areas and rough saltwater conditions. They are also well suited to environments where equipment is used in one temperature extreme and stored in another temperature extreme.

Mounting: Larson Electronics LEDLB series light bars are equipped standard with aluminum mounting blocks which slide within the aluminum housing to allow users to adjust their positioning to match existing or user drilled mounting holes. Each aluminum mounting block has an integrated rubber bushing to absorb vibrations and shocks. To secure the lights in

place users simply slide the mounting bolts through the aluminum mounting block and rubber isolator, through the mounting surface, then secure the bolt with a locking nut on the opposite side of the mounting surface. This mounting system enables mounting to flat or round surfaces and allows for minimal 7 degrees of flexibility of angle placement of the light. We also offer a BC-2 bar clamp mounting system you can view here for even greater mounting versatility.

Note: Most Larson Electronics LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model. Some larger LED lights like the LEDLB-160X2 or LEDLB-200X2 or multiple function LED lights (i.e. high/low beam, modulating, IR/Visible combos) will have different Deutsch connectors.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: LEDLB-20E

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: LEDLB-20E

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: LEDLB-20E

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: LEDLB-20E

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

LEDLB-20E

Product ID: 46992

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:

LEDLB-20E-Finish-Beam Pattern-Light Color
Example: LEDLB-20E-BLK-SP-60K

Finish	
BLACK	-BLK
WHITE	-WHT

Beam Pattern	
SPOT	-SP
FLOOD	-FL

Light Color	
6000K	-60K
3000K	-30K

Links (Click on the below items to view):

- **CE Certificate**(https://www.larsonelectronics.com/images/product/CECert/46992.PDF)
- **Military Specification Certificate 1**(https://www.larsonelectronics.com/images/product/Milspec1/46992.PDF)
- **MSDS (Material Safety Data Sheet**(https://www.larsonelectronics.com/images/product/Msds/46992.PDF)
- **Operations Manual**(https://www.larsonelectronics.com/images/product/Manual/46992.PDF)
- **RoHS Certificate (Restriction of Hazardous Substances)**(https://www.larsonelectronics.com/images/product/RoHSCert/46992.PDF)
- **SpecSheetArabic**(https://www.larsonelectronics.com/images/product/SpecSheetArabic/46992.PDF)
- **SpecSheetFrench**(https://www.larsonelectronics.com/images/product/SpecSheetFrench/46992.PDF)
- **SpecSheetSpanish**(https://www.larsonelectronics.com/images/product/SpecSheetSpanish/46992.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/46992.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/46992.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/46992.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/46992.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/46992.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/46992.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/46992.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/46992.JPG)
- **HigResPic9**(https://www.larsonelectronics.com/images/product/HigResPic9/46992.JPG)
- **HigResPic10**(https://www.larsonelectronics.com/images/product/HigResPic10/46992.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)