Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 47302

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image:

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LEDT8-15-RP 14 watt T-series
UL Listing: United States
Lamp Type: LED Tube
Dimensions: 17.5"
Weight: 381 grams
Voltage: 110 Volts to 277 VAC
Watts: 14 watts
Total Lumens: 1,750
Lumens Per Watt: 125
Lamp Life Expectancy: 50,000+ Hours
Color temperature: 3000K (clear), 4500K (clear), or 5600K (light frost)
Beam angle: 150 degrees
Operating Temp : -20 C to 85 C

Ratings/Approvals
Listed for United States and Canada
UL-1993
CAN/CSA C22.2 No 1993
125 lm/w efficiency
IP20 Rated
80% Lumen Retention @ 50,000+ Hours
Internal Driver
Single End Powered

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail:sales@larsonelectronics.com

The Larson Electronics LEDT8-15-RP 14 watt T-series LED tube lamp is an excellent choice for upgrading existing T8 fluorescent lamp fixtures to LEDs as well as a direct replacement for our own LED light fixtures.

The 14 Watt T-series LED Bulb works with any T8 fluorescent light fixtures, can be configured

for any T series fluorescent bulb fixture and requires no ballast for operation. Internally, you simply bring the black wire to one end and the white wire to the other. The polycarbonate lens diffuses the light and makes this bulb ideal for food safe environments as there is no glass. The aluminum housing serves as a heat sink and provides rigidity and strength for this LED bulb.

In fluorescent light fixtures with electronic ballasts, the operator needs to bypass the ballast and wire the power directly to one or both ends of the LED tube (black wire to one end and white wire to the other). Thus, this is an ideal upgrade for 3 foot fixtures with failed ballasts. These multi-voltage LED fluorescent bulbs run directly off any voltage ranging from 110 volts to 277 volts, including 120 volts, 230 volts, 277 volts, etc.



Click Photo to Enlarge



Click Photo to Enlarge

These are the first generation of our 14 watt LED tubes. Lumen output is 125 lumens per watt for a total of 1,750 lumens per bulb.

These LED fluorescent tube replacements can be used as upgrades or replacements to our own Larson Electronics.com explosion proof fluorescent lights, explosion proof paint spray booth lights as well as any other T series light fixture the operator already has in house. We have specially designed these for our explosion proof light fixtures, however, they can be used as replacements in standard fluorescent light fixtures. In our facilities, we replaced worn or spent fluorescent bulbs with these LED bulbs by removing the ballasts and bringing the white wire to one end the black wire to the other end of the LED tube.

LED Lamp Benefits

1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LEED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off – No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.

13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.
15. Brings out natural appearance of products in sales or manufacturing applications.
16. Preserves integrity of retail products... no heat damage to formulations or thermal fade of branded packaging in display cases.
17. Unlimited indoor applications for overhead lighting, retail fixtures, signage, custom lighting accents, manufacturing and general area illumination.
18. Easily retrofit existing conventional light fixtures, simplifies troffers since no ballasts. needed Durable enough for portable use in exhibitions and tradeshows.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Product ID: 47302

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:

-Voltage
Example: -1224VDC

Voltage	
12/24 VOLT	-1224VDC
HIGH VOLTAGE (120-277)	-1227VAC

Links (Click on the below items to view):

- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(https://www.larsonelectronics.com//images/product/CECCert/47302.PDF)
- **Dimensional Drawing 2D**(https://www.larsonelectronics.com//images/product/DimensionalDrawing/47302.PDF)
- **Operations Manual**(https://www.larsonelectronics.com//images/product/Manual/47302.PDF)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(https://www.larsonelectronics.com//images/product/NECCert/47302.PDF)
- **HigResPic1**(https://www.larsonelectronics.com//images/product/HigResPic1/47302.JPG)
- **HigResPic2**(https://www.larsonelectronics.com//images/product/HigResPic2/47302.JPG)
- **HigResPic3**(https://www.larsonelectronics.com//images/product/HigResPic3/47302.JPG)
- **HigResPic4**(https://www.larsonelectronics.com//images/product/HigResPic4/47302.JPG)
- **HigResPic5**(https://www.larsonelectronics.com//images/product/HigResPic5/47302.JPG)
- **HigResPic6**(https://www.larsonelectronics.com//images/product/HigResPic6/47302.JPG)
- **HigResPic7**(https://www.larsonelectronics.com//images/product/HigResPic7/47302.JPG)
- **HigResPic9**(https://www.larsonelectronics.com//images/product/HigResPic9/47302.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)