

EHL-LED-7W-220V-25

Explosion Proof LED Drop Light - 30 Watt LED - 25ft. SOOW Cord - 220 Volts, 50Hz - Twist Lock Plug

Product ID: 47510

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EHL-LED-7W-220V-25 Explosion Proof LED Handlamp

Unit Type: Explosion Proof LED Handlamp

Dimensions: L-20.8" Dia-5"

Total Weight: 14.8 lbs

Lamp Weight: 4.5 lbs

Voltage: 220VAC, Universal 120-277V @ 50Hz or 60Hz

Total Watts: 30

Total Lumens: 3,000

Luminous Efficacy: 100 Lm/W

Lamp Life: 50,000+ Hours

Color Temp: 5,000K

Color Rendering Index: 73

Ambient Operating Temperature: -40°C to +50°C

Operating Relative Humidity: 5% to +95% Rh

Housing Material: Aluminum Alloy with Nylon Zytel Handle

Mounting: Handheld with Annealed Aluminum Wire Swivel Hook

Lens Material: Tempered Soda Lime Glass; Frosted

Wiring: 25 feet 18/3 SOOW Cable

Cord Cap: 5-15, 6-15, L5-15, L6-15, BS1363, Schuko, or Pigtail

YOU CAN RENT THIS UNIT. CONTACT 1-800-369-6671

[Click here to view the Explosion Proof Light Design Description](#)

Ratings/Approvals

Certified to NEC, CEC, ATEX, and IEC Ex Standards

Class I, Division 1, Groups B, C, D

Class I, Division 2, Groups A, B, C, D

Class II, Divisions 1 & 2, Groups E, F, G

Class III, Divisions 1 & 2

Ex d IIB T6 Gb/Ex tb IIIC T85°C Db

Zone 1, Zone 21, Zone 2, Zone 22

T6 (C1D1) / T4A (C2D1) Temp Rating

IP66 Weatherproof

IK10 Rated

1.5KV Surge Suppression

360° Illumination

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The Larson Electronics EHL-LED-7W-220V-25 Explosion Proof LED Handlamp is ideal for general lighting, detailed tasks and inspections in hazardous locations. This 30-watt unit features 3,000 lumens of illumination. A heavy-duty swivel hook at the top of the handlamp offers versatile mounting on poles, indentions and small openings for hands-free operation. A unique angled board design offers 360° of comprehensive lighting. This explosion proof handlamp is certified to NEC, CEC, ATEX, and IEC Ex standards for worldwide use.

The EHL-LED-7W-220V-25 is designed for handheld or hands-free illumination in hazardous locations. This 30-watt unit is compatible with mainstream outlets, operating on 120-277V AC. When in use, the lamp emits 3,000 lumens of white light with a color temperature rating of 5,000K and CRI rating of 73. An angled board configuration inside the unit offers 360° illumination for full lighting requirements. This durable LED handlamp is constructed of non-sparking aluminum, minimizing the possibility of ignition. This hazardous location unit is approved for Class I, Divisions 1 & 2, Class II, Divisions 1 & 2, Zone 1 & 2, and Zones 21 & 22 environments.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Field Serviceability: This explosion proof LED hand lamp fixture is field serviceable. All major internal components (including LED driver and LED board assembly) can be purchased from Larson Electronics and installed by a licensed electrician with basic tools. With most explosion proof fixtures, the fixture must be returned to the manufacturer for repair work, which presents downtime and long turn around times for repair work. Larson Electronics addresses this issue with the EHL-LED series with field serviceability, allowing operators to perform service work without having to return the drop light to the manufacturer in the event of damage or failure. This reduces overall downtime in the event of damage to the light.

[Click Photos to Enlarge](#)



5-15 Straight Blade Plug
15 Amp / 125V Rated



L5-15 Twist Lock Plug
15 Amp / 125V Rated



L6-15 Twist Lock Plug
15 Amp / 250V Rated



UK BS1363 Straight Blade Plug
13 Amp / 250V Rated / Internal Fuse



Intl Schuko 2-Pin Plug
16 Amp / 250V Rated / Grounded



Flying Leads / Pigtail Wires

Wiring/Plug: This explosion proof LED handlamp is equipped with 25 feet of 18/3 chemical and abrasion resistant SOOW cord that is fitted with an industrial grade cord cap for easy connection to common wall outlets. Plug options include standard 5-15 15 amp straight blade plug for 110V wall outlets with ground, standard 6-15 15 amp straight blade plug for 220-240V wall outlets with ground, NEMA L5-15 15 amp twist lock plug for 125V twist lock outlets, NEMA L6-15 15 amp twist lock plug for 240V twist lock outlets, British BS1363 13 amp fused 3-blade plug for United Kingdom outlets, or a two pin 16 amp rated Schuko plug with ground contact and socket for European outlets up to 250V. Alternatively, we can provide flying leads with no plug for hard wire applications or for operators who prefer to wire in user provided cord caps. Please choose pigtail option below for flying leads with no plug.

Mounting: Operators may mount the portable LED handlamp on poles, hooks, corners, indentions, chains and other compatible openings using a sturdy annealed aluminum wire swivel hook located at the top of the unit. This hands-free option allows operators to use both hands for demanding tasks, greatly decreasing time spent inside the hazardous location. Alternatively, operators may hold the light up using a handle located at the bottom of the lamp. This handheld option is suitable for inspections and temporary, detailed tasks.

Applications: Inspections, portable lighting, tank cleaning, hazardous locations, detailed tasks, industrial facilities, oil refineries, agricultural sites, grain storage centers, food processing and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)









EHL-LED-7W-220V-25

Product ID: 47510

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Canadian CEC Certificate \(Commonly referred to as CSA Certificate\)](#)
- [CE Certificate](#)
- [Certificate 1, Misc](#)
- [Certificate 2, Misc](#)
- [Certificate 3, Misc](#)
- [Dimensional Drawing 2D](#)
- [MSDS \(Material Safety Data Sheet](#)
- [RoHS Certificate \(Restriction of Hazardous Substances\)](#)
- [SpecSheetArabic](#)
- [SpecSheetFrench](#)
- [STEP File \(3D CAD Model\)](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [Video1](#)
- [Video2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)