

XPR-9822E

Rechargeable Explosion Proof LED - Spot/Flood Combo - Class I, Div. I - ATEX Approved

Product ID: 47526

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

XPR-9822E Intrinsically Safe

Lamp Type: LED Light Emitting Diode

Dimensions: Dia-1.75" Length-13.6 "

Weight: 28 Oz

Power: Rechargeable NiMH Batteries

Runtime: 18 hrs High Mode, 9 Hours Low Mode

Lumens: 160 Spot Beam- 200 Flood Beam 360 Total Dual Mode

Lamp Life: 50,000 hrs

Operating Temp Range: 30°C to +60°C

Waterproof: Yes- Rated to 1 Meter

NTRL Listing

Class 1, 2, 3 Div 1, 2

Groups C,D

Explosion Proof/Intrinsically Safe

Waterproof to 1 Meter

FCC approved Part 15 and 18

No EM interference with communication or acute care medical electronics

ATEX Certified: Category 1 Zone 0

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

[Spanish Spec Sheets for Two Way LED Explosion Proof Light](#)

[Explosion Proof Light Design Description](#)

Made in The USA

The XPR-9822E Explosion Proof-Intrinsically Safe LED Flashlight is Atex Certified and designed to handle the demands of working within hazardous locations and environments where potentially explosive vapors, gases and other flammable compounds may be encountered.

This intrinsically safe LED flashlight carries a lifetime warranty and produces a powerful 160 lumen spotlight light beam and 200 lumens in floodlight mode. This LED flashlight adds extra functionality and utility through the inclusion of an independently operable secondary flood type beam. The main beam from this compact and lightweight LED flashlight is tightly focused to produce a beam of bright white light capable of reaching up to 90 feet in length. A secondary flood beam can be operated independently of the main light to produce a 200 lumen flood pattern of light covering approximately 60 square feet useful for close work and general illumination. This unit can also be operated in continuous or momentary flashing strobe mode.

Either beam can be operated alone to produce a 160 lumen spotlight or 200 lumen floodlight beam, or in combination to produce a total of 360 lumens of light. This light can also be switched between half power mode for maximum runtime and full power mode for maximum light output when in floodlight mode. Made in the USA, this explosion proof LED flashlight offers up to 16 hours battery run time in strobe mode on a 3 hour charge from 12 volt vehicle source and US/International wall outlets. The XPR-9822E comes with a quick release charging cradle. This LED flashlight is versatile, rugged and can serve in industrial, public and commercial applications with ease.

The strobe, flood and spot beams of this flashlight are actuated via their own momentary or constant on switches. The high intensity LEDs used in this flashlight can produce a 160 lumen spot beam or a 200 lumen flood beam of light or a 360 lumen combination of each and offer 50,000 hour lifespans. These high efficiency LEDs produce a 16 hour runtime when operating in strobe mode, a 6 hour runtime in flashlight mode, and a 5 hour runtime in floodlight mode. The housing is constructed of lightweight and chemical resistant polymer that offers non slip grip and high durability. This LED flashlight is impact and vibration resistant and waterproof to one meter. This intrinsically safe flashlight is approved Class 1, 2, 3 Div 1, Class 1, 2, 3, Div 2 and offers users the highest level of hazardous location protection available while providing the safety and efficiency of brilliant LED illumination.

ATEX Certified:

Category 1 Zone 0 (Above ground locations where flammable gas is always present or for long periods in environments up to ethyl methyl ether gas groups, where the surface temperature does not exceed 135° and the ignition temperature is Ignition temp >135° = 200°). This correlates to UL Hazardous Locations Services Class I, Division 1, Groups C/D, T4

Charging System:

Versatile configuration works 12 VDC and 100 VAC to 240 VAC at 50/60 HZ - wall outlet plug and vehicle cigarette plug included.

Single quick release cradle can be desk or wall mounted and vehicle mounted with DC connection provided.

Fast charge rate - full charge in 3 hours from fully depleted state - overcharge protection and LED indicators to show battery status.

Energy and function management system assures maximum energy capacity with no risk of over-charge and lower operating cost.

Battery Pack:

Medical grade, rechargeable NiMH.

Full charge every charge with no capacity degradation due to recharge memory.

1000+ recharge cycles.

Earth Friendly NiMH battery does not pollute the environment.

High Quality Construction

1. High Intensity LEDs- 360 Total Lumens
2. Momentary/Constant On Switches
3. Single or Tandem Light Beam Operation
4. Waterproof
5. Chemical/Impact Resistant
6. 16 hour Runtime
7. Intrinsically Safe Approval
8. Wall outlet plug/vehicle cigarette plug included

Superior LED Benefits

1. Extreme long life.
2. High efficiency and low amp draw.
3. High durability and reliability.
4. Small size and light weight.
5. 100% recyclable.
6. No toxins-lead, mercury.
7. High light output..
8. Consistent color over time.
9. High Versatility.
10. No fragile glass used in construction.
12. Vibration/impact resistant.

Frequently Asked Questions (FAQ)



XPR-9822E

Product ID: 47526

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Operations Manual](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)