

Infrared LED Light Emitter - Extreme Environment - Magnetic Base - 90'L X 70'W Spot Beam - 12 Watts

Part #: LEDLB-4E-IR-M

**Buy American Compliant**

The Larson Electronics LEDLB-4E-IR-M infrared LED Light Bar offers high light output and extreme durability combined with a versatile magnetic mounting system that provides convenience and secure attachment to vehicles, equipment and any flat metallic surface. This IP67 rated infrared LED light bar produces an infrared light beam that can only be seen through the use of night vision goggles. 850Nm versions have a very slight red glow around the LED emitters when viewed from a certain angle while 940Nm versions are completely invisible to the naked eye. This light can run on any voltage from 9 to 42 volts and provides an extremely rugged infrared lighting solution that is ideal for use in commercial and industrial security applications as well as military environments.

[Click here to see the LED version of this](#)

The LEDLB-4E-IR-M infrared LED light bar from Larson Electronics produces light in the infrared 850Nm or 940Nm end of the light spectrum depending upon the version selected. Four Edison Edixeon® 3 watt infrared emitters producing 180 lumens each are arranged in rows and paired with high purity 10 degree optics to produce a tightly focused spot beam 90' long by 70' wide with limited spread or light spillage. We offer optional floodlight versions of this light that have 35 degree optics to produce a wider beam spread and more light over a larger area nearer the fixture. These infrared LED light bars are IP67 rated, waterproof (with pressure jets), sealed against intrusion by dust and dirt and very ruggedly constructed to withstand the most demanding environments, conditions and applications. The entire Larson Electronics LEDLB-E series are constructed of extruded aluminum and feature heavier housings, rubber isolated mounts and unbreakable polycarbonate lenses to provide increased durability against vibrations, impacts, waves, hard rains, sand and high winds. This light is equipped with a 200lbs grip magnetic mount base and 16 foot coil cord ending in a cigarette plug connector. This magnetic base allows fast and easy setup of this light on vehicles and equipment and will hold the fixture in place at speeds up to 80 mph provided the mount is properly affixed and secure.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated Edison Edixeon® Emitters. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours.

[Click here to view an article on the Generations of Night Vision and Infrared.](#)


Voltage Control: These units are able to monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These LEDLB series light bars can operate on current ranging from 9 to 42VDC without any modifications necessary as a result. This multi-voltage capability makes these units ideal for mobile and standalone applications such as those found on commercial boats, heavy equipment and vehicles where power systems don't always operate with 12 volts and external generators, transformers or inverters are impractical.

LEDLB-4E-IR-M 35° Flood Beam

(Opt)

LEDLB-4E-IR-M 10° Spot Beam

(Std)



Durability: The LEDLB-E series of LED light bars from Larson Electronics offer IP68 rated construction that is designed to withstand extremes of environmental and operating conditions. The LED lights with the 'E' part number designation are designed for extreme durability and are larger and nearly twice as heavy as their standard counterparts. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three meters and resist ingress of dust, dirt and humidity. The housings are formed from thick extruded aluminum and the lenses are unbreakable polycarbonate. The Edixeon® LEDs offer inherent LED resistance to shocks and vibrations contributing to these units 15.6Grms rating of vibration tolerance. We recommend these LED lights for high stress - high vibratory conditions, high humidity climates, very cold areas and rough saltwater conditions. They are also well suited to environments where equipment is used in one temperature extreme and stored in another temperature extreme.

Magnetic Mounting: The 200 lbs magnet mounting design on the LEDLB-4E-IR-M allows for easy fixture placement and removal. This mounting system includes a power cord with a cigarette plug connector which makes this unit ideal for vehicle and equipment lighting applications where the unit can simply be attached or removed as needed. Please note, the magnetic base on this unit increases the units overall height.

Note: Most Larson Electronics LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model. Some larger LED lights like the LEDLB-160X2 or LEDLB-200X2 or multiple function LED lights (i.e. high/low beam, modulating, IR/Visible combos) will have different Deutsch connectors.

Measurements:

Taken at 5 feet from the lens.

850nm Spot - 1270 uWatts/cm²

850nm Flood - 110 uWatts/cm²

940nm Flood - 33 uWatts/cm²

Specifications / Additional Information**LEDLB-4E-IR-M LED Light Bar****LEDs:** 4 Edixeon® 3 Watt Infrared LED Emitters**Dimensions:** 4"-L 3"-H 3.56"-D**Watts:** 12**Voltage:** 9-42 VDC**Spot Beam:** 90°L x 70°W**Flood Beam:** 70° L x 60°W**Weight:** 2.4 Lbs**Lighting Configuration:** 10° Spot or 35° Flood**Mounting:** 200lbs Magnetic Mount**Wiring:** Deutsch IPD / LADD DT04-2P connector**Amps:** 1 (on 12 volts) .5 (on 24 volts)**Wavelength:** 750Nm, 850Nm or 940Nm**LED Life Expectancy:** 50,000 hours**Optics Efficiency:** 90%**Materials:** Aluminum Housing, Polycarbonate Lens**Housing Colors:** Black or White**Lux-Flood :** @Lens: 185,800 @ 1 Meter 2,672**Lux-Spot :** @Lens: 190,400 @ 1 Meter 8,440**CE Certified**

3 year warranty replacement on this LED light. After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, Larson Electronics will ship a new replacement.

[Scroll Down to Purchase-](#)

[Part #: LEDLB-4E-IR-M \(48192\)](#)

LEDLB LED Features

Edixeon® 3 Watt Infrared LED Emitters

LEDs Driven At 80%

-40 C~ +80C Operating Temp Range

RoHS Compliant

70% Lumen Retention @65,000 hours

LED Chip Op Temp -40C to +125C

IP68 Rated Waterproof to 3ft

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671**Intl:** 1-903-498-3363**E-mail:** sales@larsonelectronics.com

Options:

LEDLB-4E-IR-M- HOUSING COLOR - BEAM PATTERN - IR WAVELENGTH

Example: LEDLB-4E-IR-M-BLK-S-750nm

HOUSING COLOR		BEAM PATTERN		IR WAVELENGTH	
Black	-BLK	Spot	-S	750nm	-750nm
White	-WHT	Flood	-F	850nm	-850nm
				940nm	-940nm

Links (Click on the below items to view):

- [SpecSheet French](#)
- [SpecSheet Arabic](#)
- [SpecSheet Spanish](#)
- [Manual](#)
- [SpectrumChart](#)