Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HALD-48-2L-T5HO

Low Profile, Explosion Proof Light - 4ft, 2 Lamp - Class 1 Div. 2 - Paint Spray Booth Rated - T5HO - 1X4 Lay-In Mounting

Product ID: 48680

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HALD-48-2L-T5HO Paint Booth Lay-In Fixture

UL Listing: United States - Canada

Dimensions: 50-7/8"-L x 10-3/4"-W x 2-1/4"-D

Magnetic Switch: 10 Watts @ 300 V AC Max

Total Watts: 68 Watts

Voltage: Multi - 120-277 Volts 50/60 Hz

Total Lumens: 10,000

Lamp Life Expectancy: 20,000 Hours

Efficiency: 92 Lumens per Watt

Operating Temp Range: T3C Rated

Beam Angle: N/A

Color Temp: 5000 - F54 - T5/850/HO

Color Rendering Index: 85 CRI

Mounting: 1X4 Lay-In Recessed Panel Mounting

Wiring Hub: 1/2" Threaded NPT

Ratings

Class I Division 2, Groups A, B, C, D

Class II Division 2 Groups F,G

T3C (160 degree C)

NTRL Listed U.S. and Canada

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The HALD-48-2L-T5HO from Larson Electronics is a Hazardous Area Fluorescent Light Fixture that is designed to provide a thin fixture profile that allows the maximum use of available space. This fluorescent fixture

is U.S./Canada approved Class I Division 2, Groups A, B, C and D - Class II Division 2, Groups F and G and designed for paint spray booths and locations where flammable chemical/petrochemical vapors are present. The HALD-48-2L-T5HO is designed for 1X4 lay-in mounting.

******PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS HAZARDOUS LOCATION LIGHT FIXTURE******

The HALD-48-2L-T5HO Explosion Proof fixture is a 4 foot long, 2 lamp, Class 1 Division 2 hazardous area fluorescent light and ideal for use in paint spray booths and hazardous locations where space for lighting fixtures is limited. This fixture is T3C temperature rated, comes standard with F54-T5/850/HO bulbs and features an integrated magnetic paint spray system cutoff switch that is activated when this fixture`s lamp door is opened. The lamps are protected by a steel framed, hinged, 3/16" thick glass door that provides direct front access to the four lamps. The lamp housing is only 2 and 1/4 inches thick, designed for 1X4 lay-in recessed mounting, constructed of 20 Gauge steel and coated with a baked on white enamel finish.

This fixture is multi-voltage capable and is approved for use paint spray booths. The HALD-48-2L-T5HO provides operators in hazardous locations with a reliable and durable, low profile lighting solution that provides added safety through the inclusion of an integral paint spray cutoff switch that shuts down paint spray systems when the fixture is opened.

NOTE: The integral magnetic cutoff switch included with this fixture is activated when the lamp door is opened. This switch is not intended to directly control light operation and requires the addition of a separate solid state relay which is then used to control actual system operation. The Cutoff Switch acts only as an activator for an external relay and is rated for 10 watts at a maximum of 300 V AC. Overloading the switch through improper connection will result in switch failure. It is recommened that a certified electrician make any installations and reviews of relay connections intended to take advantage of this light`s cutoff switch. The HALD-48-2L-T5HO has an electronic multi-voltage ballast and works with 120 Volt 60 HZ, 220 Volt 50 HZ, 240 Volt 60 HZ and 277 Volts 60 HZ.

Mounting: This fixture is designed for 1X4 lay-in mounting and requires a mounting hole to be made in booth panels capable of accomodating the fixture housing in order to provide the maximum amount of space in paint spray booth enclosures. Once mounted, this fixture`s glass door frame will extend 3/8" into the spray booth.

Applications: Paint spray booths and enclosed spaces where flammable chemical/petrochemical vapors are present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









HALD-48-2L-T5HO

Product ID: 48680

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- IES (Photometric File)
- MSDS (Material Safety Data Sheet
- Operations Manual
- SpecSheetArabic
- SpecSheetFrench
- SpecSheetSpanish
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- Video1
- Video2
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map