Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

## LEDLB-24E-VISRED

# LED Light Emitter - 12 Red LEDs, 12 White LEDs - 72 Watts - 800'L X 100'W Spot Beam - 9-42VDC

**Product ID: 49519**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**LEDLB-24E-VISRED LED Light Bar**

**LEDs: 24 Edixeon® 3 Watt Emitters - (12) White & (12) Red**
**Dimensions:** 8.25"-L 5.25"-H 3.56"-D
**Watts:** 72
**Voltage:** 9-42 VDC
**Spot Beam: 800`L x 100`W**
**Flood Beam: 275`L x 240`W**
**Weight:** 7.4 Lbs
**Lighting Configuration:** 10° Spot or 35° Flood
**Mounting:** Inverted U Bracket
**Wiring:** 26" 14/3 AWM Whip terminated in Deutsch IPD / LADD DT04-3P connector
**Wiring Harness:** 20` 16/3 SOOW Wiring Harnesses w/ Deutsch IPD / LADD DT06-3S plugs and blunt cut ends
**Amps:** 6 (on 12 volts) 3 (on 24 volts)
**Lumens:** 4,320
**LED Light Color:** White( 6000K) + Red
**LED Life Expectancy:** 50,000 hours
**Optics Efficiency:** 90%
**Materials:** Aluminum Housing, Polycarbonate Lens
**Housing Colors:** Black or White

3 year warranty replacement on this LED light. After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a

**LEDLB LED Features**

Edixeon® 3 Watt LED Emitters
LEDs Driven At 80%
-40 C~ +80C Operating Temp Range
RoHS Compliant
70% Lumen Retention @65,000 hours
LED Chip Op Temp -40C to +125C
IP68 Rated Waterproof to 3 Meters

**CE Certified**

**Special Orders - Special Requirements**

Contact us for special requirements

**Toll Free:** 1-800-369-6671
**Intl:** 1-903-270-1187
**E-mail:** sales@larsonelectronics.com

manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, Larson Electronics will ship a new replacement.

**Buy American Compliant**

**The Larson Electronics LEDLB-24E-VISRED LED Light Bar offers high light output and extreme durability combined with versatile mounting and power options. This IP68 rated LED light bar is waterproof to three meters and produces a combination of white and red light while drawing only 72 watts of power @6 amps from a 12 volt electrical system. This light can run on any voltage from 9 to 32 volts and provides an extremely rugged lighting solution that is ideal for use in commercial marine environments as well as industrial and manufacturing applications such as machine vision system lighting, heavy equipment illumination, blasting lighting and mining operations.**

The LEDLB-24E-VISRED LED light bar from Larson Electronics produces a combination light beam consisting of white and red light while drawing only 72 watts @6 amps from a 12 volt electrical system. Twenty-four Edison Edixeon® Emitters containing CREE EZBright® three watt LEDs are arranged in rows, two rows of white and two rows of red, and paired with high purity 10 degree optics to produce a tightly focused spot beam with limited spread or light spillage. We also offer optional floodlight versions with 35 degree optics to produce a wider beam spread and more light over a larger area nearer the fixture, making flood versions ideal for use as work and area lights.

This specially configured LED emitter is designed to produce visible white light and visible blue light. The wiring harness includes separate power leads that enable the operator to power the white array (top two rows of LEDs) and the red array (bottom two rows of LEDs) separately. The white and red array share a single ground. This enables the operators to switch from visible white light to the red tracking light without leaving the vehicle via a 3-position switch.

These LED light bars are IP68 rated and waterproof to 3 meters, sealed against intrusion by dust and dirt and very ruggedly constructed to withstand the most demanding environments, conditions and applications. The entire Larson Electronics LEDLB-E series are constructed of extruded aluminum and feature heavier housings, rubber isolated mounts and unbreakable polycarbonate lenses to provide increased durability against vibrations, impacts, waves, hard rains, sand and high winds.



This image shows the top row of (12) white LEDs illuminated.

**Click Photo to Enlarge**



This image shows the top row of (12) blue LEDs illuminated.

**Click Photo to Enlarge**

This image shows both white and red LEDs illuminated.

**Click Photo to Enlarge**

**Heat Management:** Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated Edison Edixeon® Emitters. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours.

**Voltage Control:** These units are able to monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These LEDLB series light bars can operate on current ranging from 9 to 32VDC without any modifications necessary as a result. This multi-voltage capability makes these units ideal for mobile and stand alone applications such as those found on commercial boats, heavy equipment and vehicles where power

systems don't always operate with 12 volts and external generators, transformers or inverters are impractical.

**LEDLB-24E-VISRED**
**35° Flood Beam (Opt)**



**LEDLB-24E-VISRED**
**10° Spot Beam (Stnd)**



**Durability:** The LEDLB-E series of LED light bars from Larson Electronics offer IP68 rated construction that is designed to withstand extremes of environmental and operating conditions. The LED lights with the 'E' part number designation are designed for extreme durability and are larger and heavier than the standard LEDLB series lights and are nearly twice as heavy as their standard counterparts. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three meters and resist ingress of dust, dirt and humidity. The housings are formed from thick extruded aluminum and the lenses are unbreakable polycarbonate. The Edixeon® LEDs offer inherent LED resistance to shocks and vibrations contributing to these units 15.6Grms rating of vibration tolerance. We recommend these LED lights for high stress - high vibratory conditions, high humidity climates, very cold areas and rough saltwater conditions. They are also well suited to environments where equipment is used in one temperature extreme and stored in another temperature extreme.
**Mounting:** Larson Electronics LEDLB series light bars are equipped standard with aluminum mounting blocks which slide within the aluminum housing to allow users to adjust their positioning to match existing or user drilled mounting holes. Each aluminum mounting block has an integrated rubber bushing to absorb vibrations and shocks. To secure the lights in place users simply slide the mounting bolts through the aluminum mounting block and rubber isolator, through the mounting surface, then secure the bolt with a locking nut on the opposite side of the mounting surface. This mounting system enables mounting to flat or round surfaces and allows for minimal 7 degrees of flexibility of angle placement of the light. In this LED emitter light bar model, an additional mounting option is provided. The adjustable, shock insulated mounts are attached to a simple, inverted u-bracket type mount. The LED light bar can then be mounted via a single 3/8 bolt through the center of the bracket. We also offer a BC-2 bar clamp mounting system you can view here for even greater mounting versatility.
**Note:** This combination spotlight is terminated in a Deutsch IPD / LADD DT04-3P connector. The mating connector plug is DT06-3S. A 20` 16/3 SOOW wiring harnesses terminated in DT06-3S connectors and blunt cut ends are included with the light.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

# Frequently Asked Questions (FAQ)









Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

**LEDLB-24E-VISRED**

**Product ID: 49519**

**Harmonized System (HS) Code:** 9405.41.84.10
**Export Control Classification Number (ECCN):** EAR99

**Options:**

**LEDLB-24E-VISRED-Beam Pattern-Housing Color**

**Example: LEDLB-24E-VISRED-SP-BLK**

| Beam Pattern | |
|---|---|
| SPOT | -SP |
| FLOOD | -FL |

| Housing Color | |
|---|---|
| BLACK | -BLK |
| WHITE | -WHT |

Links (Click on the below items to view):

- CE Certificate
- Dimensional Drawing 2D
- Military Specification Certificate 1
- MSDS (Material Safety Data Sheet
- Operations Manual
- RoHS Certificate (Restriction of Hazardous Substances)
- STEP File (3D CAD Model)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- Video1
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map