Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDLB-4ET-IR-110V

Medical LED Infrared Light Emitter w/ Handle - 110VAC - 720 Lumen - 850NM - 12 Watts

Product ID: 49647

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LEDLB-4ET-IR-110V LED Light Bar

LEDs: 4 Edixeon® 3 Watt Infrared LED Emitters
Dimensions: 4"-L 3"-H 3.56"-D
Watts: 12
Voltage: 110VAC; & 9-42 VDC
Weight: 3.4 Lbs
Lighting Configuration: 10° Spot or 35° Flood
Mounting: Trunnion Handle
Wiring: Deutsch IPD / LADD DT04-2P connector
Amps: 1 (on 12 volts) .5 (on 24 volts)
Lumens: 720
LED Light Color:Infrared:850Nm
LED Life Expectancy: 50,000 hours
Optics Efficiency: 90%
Materials: Aluminum Housing, Polycarbonate Lens
Housing Colors: Black or White
Lux-Flood : @Lens: 185,800 @ 1 Meter 2,672
Lux-Spot : @Lens: 190,400 @ 1 Meter 8,440
CE Certified
3 year warranty replacement on this LED light. After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs

LEDLB LED Features

Edixeon® 3 Watt Infrared LED Emitters
LEDs Driven At 80%
-40 C~ +80C Operating Temp Range
RoHS Compliant
70% Lumen Retention @65,000 hours
LED Chip Op Temp -40C to +125C
IP68 Rated Waterproof to 3 meters

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, wet will ship a new replacement.

Buy American Compliant

The LEDLB-4ET-IR-110V infrared LED Light Bar offers high light output and extreme durability combined with a versatile trunnion handle to easily manage this units' output for precise control in a variety of applications. This IP68 rated infrared LED light bar produces an infrared light beam in the 850 nanometer (NM) range which is the most common wavelength used in IR light treatments. Included with this high performance light is an inline transformer and six feet of cord fitted with a straight blade plug to allow operation from standard wall outlets.

The LEDLB-4ET-IR infrared LED light bar from Larson Electronics produces light in the 850 Nm infrared end of the light spectrum standard, and the wavelength most commonly recommended for medical use. Four Edison Edixeon® 3 watt infrared emitters producing 180 lumens each are arranged in rows and paired with high purity 10 degree optics to produce a tightly focused spot beam 120` long by 70` wide with limited spread or light spillage. We offer optional floodlight versions of this light that have 35 degree optics to produce a wider beam spread and more light over a larger area nearer the fixture. These LED light bars are IP68 rated and waterproof to 3 meters, sealed against intrusion by dust and dirt and very ruggedly constructed to withstand the most demanding environments, conditions and applications.
The entire Larson Electronics LEDLB-E series are constructed of extruded aluminum and feature heavier housings, rubber isolated mounts and unbreakable polycarbonate lenses to provide increased durability. This light is equipped with a trunnion handle which allows user to hold the unit up to desired areas as well as positioning the light at various angles.


Click to Enlarge Photo

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated Edison Edixeon® Emitters. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours.
Voltage Control: These units come standard with a 120vac plug in. However, these units are able to monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. When the transformer is removed, these LEDLB series light bars can operate on current ranging from 9 to 42VDC without any modifications necessary as a result.

LEDLB-4ET-IR-110V 35° Flood Beam (Opt)



LEDLB-4ET-IR-110V 10° Spot Beam (Stnd)



Durability: The LEDLB-E series of LED light bars offer IP68 rated construction that is designed to withstand extremes of environmental and operating conditions.

The LED lights with the 'E' part number designation are designed for extreme durability and are larger and nearly twice as heavy as their standard counterparts. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three meters and resist ingress of dust, dirt and humidity. The housings are formed from thick extruded aluminum and the lenses are unbreakable polycarbonate. The Edixeon® LEDs offer inherent LED resistance to shocks and vibrations contributing to these units 15.6Grms rating of vibration tolerance. We recommend these LED lights for high stress - high vibratory conditions, high humidity climates, very cold areas and rough saltwater conditions. They are also well suited to environments where equipment is used in one temperature extreme and stored in another temperature extreme.
Click here to learn more about the different Generations of Night Vision and Infrared Lighting.
Adjustable Mounting: The trunnion handle design on the LEDLB-4ET-IR-110V allows positioning the unit at various angles while holding the unit at desired locations. This means that by loosening 2 thumb bolts located on either side of the light, the operator can adjust the positioning angle of this light 270 degrees. Then he/she would simply have to tighten thumb bolts to lock the angle in place. No tools are required for adjusting angle.
Measurements:
Taken at 5 feet from the lens.
850nm Spot - 1270 uWatts/cm^2
850nm Flood - 110 uWatts/cm^2
940nm Flood - 33 uWatts/cm^2

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDLB-4ET-IR-110V

Product ID: 49647

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

LEDLB-4ET-IR-110V-Beam Pattern-Housing Color-Wavelength

Example: LEDLB-4ET-IR-110V-S-Blk-750

Beam Pattern	
SPOT	-S
FLOOD	-F

Housing Color	
BLACK	-Blk
WHITE	-Wht

Wavelength	
750NM	-750
850NM	-850
940NM	-940

Links (Click on the below items to view):

- **CE Certificate**
- **Eye Safety Information/Certificate**
- **Military Specification Certificate 1**
- **MSDS (Material Safety Data Sheet**
- **Operations Manual**
- **RoHS Certificate (Restriction of Hazardous Substances)**
- **Spectrum Curve (Wavelength Graph)**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**