Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDP10W-60ET-DBM-I

LED Light Bar w/ Trunnion Mount on Double Ball Mount Joint - 6, 10-Watt LEDs - 200lb. Magnetic Base

Product ID: 49703

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LEDP10W-60ET-DBM-I LED Light Bar

LEDs: 6 CREE XLamp MC-E® 10 Watt LED Emitters
Dimensions: 8.25"-L 3"-H 3.56"-D
Watts: 60
Voltage: 110 with Transformer- 9-46 VDC Without Transformer
Weight: 5.6 Lbs
Lighting Configuration: 15° Spot or 40° Flood
Mounting: Trunnion with Double Ball Joint and Magnetic Base
Wiring: 10` SOOW Cable with Converter
Amps: 5 (on 12 volts) 2.5 (on 24 volts)
Lumens: 5160
LED Light Color: 6000K
LED Life Expectancy: 50,000 hours
Optics Efficiency: 90%
Materials: Aluminum Housing, Polycarbonate Lens
Housing Colors: Black or White
Lux-Spot : @Lens: 192,900 @ 1 Meter 17,000
Lux-Flood : @Lens: 186,500 @ 1 Meter 1,930
CE Certified
3 year warranty replacement on this LED light. After 30 days, the customer ships the

LEDP10W LED Features

CREE XLamp MC-E® 10 Watt LED Emitters
LEDs Driven At 80%
-40 C~ +80C Operating Temp Range
RoHS Compliant
70% Lumen Retention @65,000 hours
LED Chip Op Temp -40C to +125C
IP68 Rated Waterproof to 3 meters

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, Larson Electronics will ship a new replacement.

Buy American Compliant

The Larson Electronics LEDP10W-60ET-DBM-I LED Light Bar offers high light output and extreme durability combined with a versatile trunnion and double ball joint mount with magnetic base. The magnetic base provides 200 lbs of magnetic grip while a double ball joint and trunnion mount provides the operator with the ability to adjust the unit to a wide variety of positions while mounted. This LED light emitter bar light runs on 110VAC provided by an included inline power transformer.

The LEDP10W-60ET-DBM-I LED light bar from Larson Electronics produces 5,160 lumens of light while drawing only 60 watts @5 amps from a 12 volt electrical system. Six CREE XLamp MC-E® ten watt LEDs producing 860 lumens each are paired with high purity optics to produce a 15 degree spread spot beam approximately 525’ long by 80’ in width. We also offer floodlight versions with a 40 degree beam spread to provide more light over a larger area nearer the fixture, making flood versions ideal for use as work lights. These LED light bars are waterproof to 3 meters, sealed against intrusion by dust and dirt and very ruggedly constructed to withstand the most demanding environments, conditions and applications.

These LED light bars are IP68 rated and waterproof to 3 meters, sealed against intrusion by dust and dirt, and very ruggedly constructed to withstand the most demanding environments, conditions, and applications. The entire Larson Electronics LEDP10W series are constructed of extruded aluminum and feature heavier housings, rubber isolated mounts and unbreakable polycarbonate lenses to provide increased durability against vibrations, impacts, waves, hard rains, sand and high winds.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated CREE XLamp MC-E® Emitters. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours.

Voltage Control: These units are able to monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These LEDP10W series light bars can operate on current ranging from 9 to 46VDC without any modifications necessary as a result. This multi-voltage capability makes these units ideal for mobile and stand alone applications such as those found on commercial boats, heavy equipment and vehicles where power systems don’t always operate with 12 volts and external generators, transformers or inverters are impractical.

LEDP10W-60ET-DBM-I 35° Flood Beam (Opt)



LEDP10W-60ET-DBM-I 10° Spot Beam (Stnd)



Durability: The LEDP10W series of LED light bars from Larson Electronics offer

IP68 rated construction that is designed to withstand extremes of environmental and operating conditions. The LED lights with the 'E' part number designation are designed for extreme durability and are larger and heavier than the standard LEDP10W series lights and are nearly twice as heavy as their standard counterparts. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three meters and resist ingress of dust, dirt and humidity.

The housings are formed from thick extruded aluminum and the lenses are unbreakable polycarbonate. The CREE XLamp MC-E® LEDs offer inherent LED resistance to shocks and vibrations contributing to these units 15.6Grms rating of vibration tolerance. We recommend these LED lights for high stress - high vibratory conditions, high humidity climates, very cold areas and rough saltwater conditions. They are also well suited to environments where equipment is used in one temperature extreme and stored in another temperature extreme.

Adjustable Mounting: A magnetic base with a 200 lb grip temporarily secures this unit to various metallic surfaces while a double ball joint mount allows 360 degrees of rotation and 140 degrees of tilt. To adjust this LED unit simply loosen the thumb bolt located on the side of unit, position the light head as desired, then retighten the thumb screw. The light head can be further adjusted by loosening the thumb screws on either side of the light head and moving the light head through 270 degrees of vertical tilt. This mounting system will hold the unit securely in place, even under rough working or driving conditions, and provides an extreme level of placement versatility.

Note: Most Larson Electronics LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model. Some larger LED lights like the LEDLB-160X2 or LEDLB-200X2 or multiple function LED lights (i.e. high/low beam, modulating, IR/Visible combos) will have different Deutsch connectors.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDP10W-60ET-DBM-I

Product ID: 49703

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

LEDP10W-60ET-DBM-I-Finish-Beam Pattern-Color Temp

Example: LEDP10W-60ET-DBM-I-BLK-S-3k

Finish	
BLACK	-BLK
WHITE	-WHT

Beam Pattern	
SPOT	-S
FLOOD	-F

Color Temp	
3000K	-3k
4500K	-45k
6000K	-6k

Links (Click on the below items to view):

- **CE Certificate**
- **MSDS (Material Safety Data Sheet**
- **Operations Manual**
- **RoHS Certificate (Restriction of Hazardous Substances)**
- **HigResPic1**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**